

# DYNABRADE NITRO SERIES ELECTRIC DYNISHER ABRASIVE FINISHING TOOL



WE LISTEN. WE OBSERVE. WE OPTIMIZE.

## DYNABRADE NITRO SERIES™ ELECTRIC DYNISHER ABRASIVE FINISHING TOOL



#### MODEL DYS1 120 VOLT, 9 AMP, 1,000 WATT

- Achieve superior in-line finishes on metal.
- 800 3,000 RPM, adjustable in 500 RPM increments.
- Variable speed dial allows operator to pre-select speed to suit each application.
- Includes 13378 Arbor for use with 3/4" bore accessories.
- Multi-purpose arbor accepts Dynacushion<sup>®</sup> pneumatic wheels (5" dia x 3-1/2" wide).
- Non-woven nylon wheels can also be used utilizing 3/4" arbor.
- Features a locking trigger for extended use.
- Adjustable handle and guard.
- Comfortable ergonomic design for smooth, repeatable results.



Model No.	Speed	Power	Tool Thread	Weight	Height	Length
DYS1	800 - 3,000 RPM	1,000 W (1.3 hp)	5/8"-11	6.4 lbs (2.9 kg)	6.4" (163 mm)	16.8" (427 mm)







### DYNACUSHION<sup>®</sup> PNEUMATIC WHEELS

### FOR POLISHING AND BLENDING

Dimensions Dia. x W	Part No.	Hub Composition	Arbor Hole	Wheel Part No.	Wheel Type	Belt Size W x L	Max. RPM
<b>5" x 2-3/4</b> " (127 mm x	92935	Aluminum	Universal 1/2",	94482	Standard	2-3/4" x 15-1/2"	3.500
70 mm)	92936	Composite	5/8" or 3/4" Bore	74402	Standard	(70 mm x 394 mm)	3,000
5" x 3-1/2"	92937	Aluminum	Universal 1/2",	0//01	Standard	3-1/2" x 15-1/2"	2 500
(127 mm x 89 mm)	92938	Composite	5/8" or 3/4" Bore	94481	Standard	(89 mm x 394 mm)	3,500





DvnaFire™ Ceramic Alumina (PCER)

DynaCut™ Zirconia Alumina (Z/A)

DynaCut™ Aluminum Oxide (A/O)



92938

### **COATED ABRASIVE BELTS** FOR USE WITH PNEUMATIC WHEELS

**NON-WOVEN NYLON BELTS** FOR USE WITH PNEUMATIC WHEELS

Width

2-3/4"

(70 mm)

3-1/2"

(89mm)

Length	Width	Grit	DynaFire™ PCER	DynaCut™ Z/A	DynaCut™ A/O	Qty	
	2-3/4"	80	-	90018	90077	10	
	(70 mm)	120	-	90020	90078	10	
<b>15-1/2"</b> (394 mm	3-1/2" 6	36	79195	90266	90346		
(374 mm) X 70 mm)		60	79196	90272	90353	10	
		80	79197	90273	90354	10	
		120	79199	90275	90355		

Coarse

(Brown)

\_

89233

90283

89243

DynaBrite® Coarse Non-Woven Nylon



DynaBrite® Medium Non-Woven Nylon

DynaBrite® Very Fine Non-Woven Nylon



### **ARBOR MOUNT PNEUMATIC & ABRASIVE WHEELS**

Length

15-1/2"

(394 mm

x 70 mm)

#### 13073

- 5/8"-11 male spindle.
- For wheels with 5/8" or 1" arbor bore.
- Mount wheels up to 3" wide.



### THREADED ADAPTERS

**MOUNT PNEUMATIC & ABRASIVE WHEELS** 

Medium

(Maroon)

90022

89232

90282

89242

**Very Fine** 

(Blue)

90021

89231

90281

89241

Qty

1

1

#### 58058

Belt

Brand

**DynaBrite**®

**DynaBrite**®

Premium

**DynaBrite**®

DvnaBrite®

Premium

- 5/8"-11 female 5/8"-11 male threads.
- 51 mm (2") long; 19 mm wrench flats.

#### 13060

- 5/8"-11 female 5/8"-11 female threads.
- 102 mm (4") long; 19 mm wrench flats.



## WHEEL INFLATION TOOL

FOR USE WITH **PNEUMATIC WHEELS** 

### 94465

- 1/4" female NPT.
- Controlled inflation for valve assemblies.
- 95633 nozzle replacement available.



58058

- 13060



### WE LISTEN. WE OBSERVE. WE OPTIMIZE.

## **ABRASIVE FLAP WHEELS** FOR DYNABRADE NITRO SERIES® ELECTRIC DYNISHER

### DYNACUT<sup>™</sup> FLAP WHEELS

### **COATED ABRASIVE FLAP WHEELS**

- Ideal for light metal removal and graining flat, concave and convex surfaces and as a first step in an in-line finishing system.

Diameter	Attachment	Width	Max. RPM	60 Grit	80 Grit	Pkg Qty
4"	3/4" Center Hole	4"	6,800	90847	90851	1



### **DYNABRITE® FLAP WHEELS**

### INTERLEAF COATED ABRASIVE / NON-WOVEN NYON FLAP WHEELS

 Combines two in-line finishing steps into one. The coated abrasive flaps provide light metal removal with the DynaBrite<sup>®</sup> flaps generating a satin finish.

Diameter	Attachment	Width	Max. RPM	Coarse 60 Grit	Medium 80 Grit	Medium 120 Grit	Fine 150 Grit	Very Fine 240 Grit	Pkg Qty
4"	3/4" Dia. Arbor	4"	5,000	79470	79471	79472	79473	79474	1
/ 1//"	5/8"-11	2"	E 000	79476	79477	79478	79479	79480	1
4-1/4" Storring Thread	4"	5,000	79482	79483	79484	79485	79486	1	



### NON-WOVEN NYLON ABRASIVE FLAP WHEELS

- Ideal for deburring, cleaning, blending and polishing on aluminum, steel, stainless steel and other metals.

Diameter	Attachment	Width	Max. RPM	Coarse	Medium	Fine	Very Fine	S-Ultra Fine	Pkg Qty
4"	3/4" Dia. Arbor	4"	5,000	79404	79405	79406	79407	79490	1
/ 4//8	5/8"-11	2"	F 000	79493	79494	79400	79401	79489	1
4-1/4"	Thread	4"	5,000	79491	79492	79402	79403	79487	1

### **POLISHING FLAP WHEELS**

- For use with compounds. Ideal for achieving mirror and polished finishes.

Diameter	Attachment	Width	Max. RPM	Part No.	Pkg Qty
4"	3/4" Dia. Arbor —	2"	5,000	79481	1
4	5/4 DIA. ALDOI	4"	3,700	79475	1
4-1/4 "	5/8"-11 Thread	4"	5,000	79488	1



dynabrade.com 🛛 🖬 💿 🕩 🖬

DYNABRADE NITRO SERIES™ ELECTRIC DYNISHER **D21-04**