

AUTOMOTIVE REFINISHING MARKET THE DYNABRADE ESSENTIALS



DYNABRADE NITRO SERIES®



ECU4

EXTENSION RIGHT ANGLE **CUT-OFF WHEEL TOOL**

- 4" (100 mm) Dia.
- Power: 1 hp (746 W)
- Speed: 14.000 RPM
- Tool Thread: 3/8"-24
- · Lock-lever controlled
- Multi-positioning guard for easy right and left hand operations



+ Provides an operator with greater control of the cut-off wheel tool while working overhead, or in difficult to reach areas.

DS32 & DS53

RIGHT ANGLE DISC SANDERS

- Compact and ergonomic design
- · Locking-type disc pad included
- · Easy access to tight area

DS32

Speed: 18,000 RPM

• 2" (50 mm) Dia.

Power: 0.3 hp (224 W)

· Safety-lock lever, rotational rear exhaust

+ Ideal for a guick weld removal, metal bevelling in weld preparation, deburring and deflashing, surface conditioning and paint removal.

RS₁

RECIPROCATING SAW

- Strokes Per Minute: 9.000
- Stroke Length: 3/8" (10 mm)
- · Lightweight and ergonomic design
- · Adjustable rear exhaust



+ Versatile tool for achieving accurate cuts on sheet metals, piping, fiberglass, composites, aluminium and plastic panels.

DGR31 & DGR51

RIGHT ANGLE DIE GRINDERS

- Compact and ergonomic design
- · 3-piece collet, interchangeable inserts
- Low collet runout <.003
- Collet: 1/4"
- · Safety-lock lever, rotational side exhaust

DGR31

- Speed: 18,000 RPM
- Power: 0.3 hp (224 W)

- Speed: 14,000 RPM
- Power: 0.5 hp (373 W)

+ Ideal for fast weld and stock removal, rust and scale removal, heavy deburring.

DGS31 & DGS51

STRAIGHT-LINE DIE GRINDERS

- · Compact and ergonomic design
- · 3-piece collet, interchangeable inserts
- Low collet runout <.003
- Collet: 1/4"
- · Safety-lock lever, rotational side exhaust

- Speed: 25,000 RPM





+ Compact and strong straightline Die Grinder with 360° rotational side exhaust to direct the air away from the operator.

Power: 0.3 hp (224 W)

- Speed: 20,000 RPM
- Power: 0.5 hp (373 W)

50218 & 50219

DIE GRINDER KITS

50218

 Includes: DGR51 & DGS51

 Includes: DGR31 & DGS31






NF1/MNF1/MNF13

NITROFILE & MINI-NITROFILE ABRASIVE BELT TOOLS





• Speed: 20,000 RPM • Power: 0.5 hp (373 W)

DS53

Speed: 14,000 RPM

• 3" (75 mm) Dia.

Power: 0.5 hp (373 W)

MNF1 Belt Size: 1/8" (3 mm) - 1/2" (13 mm) x 12" (305 mm)

Speed: 25,000 RPM • Power: 0.4 hp (298 W)

MNF13 Belt Size: 1/8" (3 mm) - 1/2" (13 mm) x 13" (330 mm)


Speed: 25,000 RPM • Power: 0.4 hp (298 W)

Kits are also available - models NF1VK and MNF1K

NZ1

NITROZIP SURFACE PREPARATION TOOL

- · Includes wheel hub 92239 & RED-TREAD® Eraser wheel 92255
- Speed: 3,500 RPM
- Power: 0.5 hp (373 W)



NZ1K

NITROZIP SURFACE PREPARATION KIT

KIT INCLUDES

- NZ1 NitroZip Surface Preparation Tool (1)
- 92252 1/2" Wheel Hub Assembly (1)
- 92248 1/2" Coarse Wire Wheel (1)
- 92239 3/4" Wheel Hub Assembly (1)
- 92245 3/4" Coarse Wire Wheel (1) 92255 RED-TREAD® Eraser Wheel (1)



DYNABRADE SANDERS

58444

TWO-HAND GEAR DRIVEN SANDER

- 6" (150 mm) Dia. Hook-Face Pad
- Power: 0.45 hp (336 W)
- Speed: 900 RPM
- · Vacuum (Non-Vac model is 58442)
- Rear Exhaust
- Also available in 5" (125 mm) Dia. & 8" (200 mm) Dia., in vacuum and non-vacuum





58435 / 58430

DYNALOCKE® DUAL-ACTION SANDER

 Power: 0.45 hp (336 W) • Speed: 12,000 RPM

• Orbit: 3/16" (5 mm)

58435

• 6" (150 mm) Dia. Hook-Face Pad

58430

• 5" (125 mm) Dia. Hook-Face Pad





3/16" (5 mm) DIAMETER ORBIT General Sanding

NS6 / NS6H / NS6V

DYNABRADE NITRO SERIES® RANDOM ORBITAL (DA) SANDER

- 6" (150 mm) Dia.
- Power: 0.3 hp (224 W)
- Speed: 12,000 RPM
- Orbit: 3/16" (5 mm)



3/16" (5 mm) DIAMETER ORBIT **General Sanding**

NS6H

Vinyl Pad Non-Vacuum

NS₆

NS6V

- Hook-Face
- Hook-Face
- Non-Vacuum Vacuum

*Non-vacuum models also available in 5" (125 mm) dia.

+ Light-duty, economy sander

designed for occasional use.

59178 / 59179 / 59180 / 59181 / 59182 / 59183

DYNORBITAL-SPIRIT® RANDOM ORBITAL SANDER

- 6" (150 mm) Dia, Hook-Face Pad
- Power: 0.25 hp (186 W)
- Speed: 12,000 RPM

NON-VACUUM


59178

• Orbit: 3/8" (10 mm)



59179

59182





General Sanding




59180


59183

VACUUM 59181

Orbit: 3/8" (10 mm)



General Sanding



• Orbit: 3/32" (2.5 mm) • Ultra-Fine Sanding



57405

DYNALINE SANDER

- 3-2/3" (93 mm) x 7" (178 mm), Hook face
- Power: 0.3 hp (224 W)
- SPM: 2,400
- Rear Exhaust
- Stroke Length: 3/8" (10 mm)
- Non-Vacuum





NSE6 / NSE6V

DYNABRADE NITRO-E SERIES® ELECTRIC RANDOM ORBITAL

(DA) SANDER

- 6" (150 mm) Dia.
- Power: 150 W
- Speed: 10,000 RPM
- Orbit: 3/16" (5 mm)



NSE6V

 Hook-Face Hook-Face

Non-Vacuum
 Vacuum

*Models also available in 5" (125 mm) dia.



3/16" (5 mm) DIAMETER ORBIT General Sanding

> + Light-duty, economy sander designed for occasional use.

NSTARTK1

NITRO SERIES® STARTER KIT KIT INCLUDES

- NF1 Abrasive Belt Tool
- NS6H Random Orbital Sander
- DGR31 Right Angle Die Grinder
- Additional Accessories
- Kit Carry Bag



+ This economical tool kit has been developed with a new refinish technician in mind. The kit includes the following Dynabrade Nitro Series® tools; our 6" Random Orbital (DA) Sander (NS6H), NitroFile Belt Tool (NF1) and Die Grinder (DGR31). We have also included our recommended air hose accessories and the necessary maintenance items to keep these tools running efficiently.

58514/ 58516

DYNABIIG® II ORBITAL SANDER

- 2-3/4" (68 mm) x 7-3/4" (178 mm). Hook-Face Pad
- Power: 0.11 hp (82 W)
- Non-Vacuum



58514

• Orbit: 3/16" (5 mm)

- Orbit: 3/32" (2.5 mm)
- RPM: 8,000
 - RPM: 10,000

General Sanding

DYNORBITAL® EXTREME SERIES RANDOM ORBITAL SANDERS



X61HS

6" (150 MM) DYNORBITAL® EXTREME SANDER

- Orbit: 3/16" (5 mm)
- Power: 0.3 hp (224 W)
- Speed: 12,000 RPM
- Hook-Face Pad with Speed Control Valve

Other models available:

- X61: Non-Vacuum with Vinyl Pad
- X61VHS: Vacuum with Hook-Face Pad and Speed Control Valve

More models available on www.dynabrade.com



3/16" (5 mm) DIA. ORBIT General Sanding



3/32" (2.5 mm) DIA. ORBIT Ultra-Fine Sanding

X32

3" (75 MM) MINI-DYNORBITAL® EXTREME SANDER

- Orbit: 3/32" (2.5 mm)
- Power: 0.1 hp (75 W)
- Speed: 12,000 RPM
- Integrated Speed Regulator
- Non-Vacuum
- Hook-Face Pad

Other models available:

- X31: 3/16" (5 mm) Dia. Orbit, Non-Vacuum, Hook-Face Pad
- X31V: 3/16" (5 mm) Dia. Orbit, Vacuum, Hook-Face Pad
- X32V: 3/32" (2.5 mm) Dia. Orbit, Vacuum, Hook-Face Pad
- Integrated Speed Regulator included on all 3" Extreme Models



X62HS

6" (150 MM) DYNORBITAL® Extreme sander

- Orbit: 3/32" (2.5 mm)
- Power: 0.3 hp (224 W)
- Speed: 12,000 RPM
- Hook-Face with Speed Control Valve

Other models available:

- X62: Non-Vacuum with Vinyl Pad
- X62VHS: Vacuum with Hook-Face Pad and Speed Control Valve

More models available on www.dynabrade.com



DYNORBITAL® EXTREME COMBO PACKS

X3161H

- X31 3" Mini-Dynorbital® Extreme, Non-Vacuum.
- X61HS 6" Dynorbital® Extreme with Speed Control Valve, Non-Vacuum.

X3161V

- X31V 3" Mini-Dynorbital® Extreme, Vacuum.
- X61VHS 6" Dynorbital® Extreme with Speed Control Valve, Vacuum.
- * All sanders have a 3/16" orbit include Hook-Face Backup Pads.

X3262H

- X32 3" Mini-Dynorbital® Extreme, Non-Vacuum.
- X62HS 6" Dynorbital® Extreme with Speed Control Valve, Non-Vacuum.

X3262V

- X32V 3" Mini-Dynorbital® Extreme, Vacuum.
- X62VHS 6" Dynorbital® Extreme with Speed Control Valve, Vacuum.
- * All sanders have a 3/32" orbit include Hook-Face Backup Pads.

POLISHING TOOLS







EPICYCLOIDAL MOTION



DB8

ELECTRIC GEARED DUAL-ACTION POLISHER

- 5" (125 mm) 6" (150 mm) Dia.
- High quality "Renny Doyle Series" Geared Dual-Action Polisher
- Includes 5" (125 mm) Backing Plate (DB8P5) and 6" (150 mm) Backing Plate (DB8P6)
- 20' swivel cord
- · Rubberized Dynagrip helps reduce vibration and operator fatigue
- · Powerful, 1,000-watt motor
- · Single-Action lock trigger
- · Ergonomically-designed extended handle for increased operator comfort





(ϵ)

RB3

VARIABLE SPEED ROTARY BUFFER/POLISHER

- 5" (125 mm) 8" (200 mm) Dia.
- · High quality "Nitro" Rotary Polisher for all-round polishing applications
- Includes 5" (125 mm) Backing Pad (57544)
- · Auto shut-off carbon brushes prevents motor damage
- Variable speed dial offers six speed selection between 800 - 3.000 RPM
- Powerful, 1.000-watt motor
- Cuts, polishes and buffs to bring out a mirror finish on even the dullest surface





RANDOM ORBITAL MOTION

ELECTRIC RANDOM ORBITAL BUFFER

- 6" (150 mm) Dia.
- High quality "Nitro" Random Orbital Buffer for excellent buffing applications
- Includes 6" Dia. Hook-Face pad (ROBP1)
- · 12' flexible and oil resistant electric cord
- · Variable speed dial easily adjusts from 1,800 - 4,400 RPM while in use
- · Powerful, 1.000-watt motor
- 21 mm orbit achieves excellent hologram-free finishes on paints and clear coats
- Keeps the painted surfaces cool and produces showroom gloss

ALL BUFFING KITS INCLUDE:

- 22017 DynaOne Polishing Compound, 1 Liter (1)
- 23090 DynaTwo Polishing Compound, 1 Liter (1)
- 50203 Red, 16" x 16" Premium Microfiber Wipe
- 50204 Orange, 16" x 16" Premium Microfiber Wipe Kit Carry Bag

50209

ROTARY BUFFING KIT

- RB3 Variable Speed Rotary Buffer/Polisher
- 57544 5" Hook-Face Pad, 5/8"-11 Thread (1)
- A9550 5" Red Foam, Flat Face Polishing Pad (1)
- A9450 5" Orange Foam, Flat Face Polishing Pad (1)
- 79701 5-1/2" Dynacut™ Top Wool Polishing Pad, Hook & Loop (1)



50226

ROTARY BUFFING KIT

- RB3 Variable Speed Rotary Buffer/Polisher
- 57545 6" Hook-Face Pad, 5/8"-11 Thread (1)
- A9560 6" Red Foam, Flat Face Cutting Pad (1)
- A9460 6" Orange Foam, Flat Face Polishing Pad (1)
- 79706 6-1/2" Dynacut™ Top Wool Polishing Pad, Hook & Loop (1)



50208

50208

RANDOM ORBITAL BUFFING KIT

- ROB1 Random Orbital Buffer/Polisher
- A9560 6" Red Foam, Flat Face Cutting Pad (1)
- A9460 6" Orange Foam, Flat Face Cutting Pad (1)
- 79707 6-1/2" Dynacut™ Microfiber Pad (1)

EB3

EXTENSION BUFFER/POLISHER

- 3" (75 mm) Dia.
- Compact and lightweight design
- Power: 0.5 hp (373 W)
- Speed: 2,700 RPM



*Wool pad not included.

RB₁

5"-8" BUFFER/POLISHER

- 5" (125 mm) 8" (200 mm) Dia.
- Compact and lightweight design
- Power: 1 hp (746 W)
- Speed: 2,800 RPM



*Back-up pad and polishing bonnet not included.

57927

DYNABUG "MODEL T" ORBITAL SANDER

- 6" (150 mm) Dia. Hook-Face Pad
- Speed: 20,000 RPM
- Orbit: 3/32" (2.5 mm)
- Non-Vacuum





ORBITAL MOTION
General Sanding

+ Turbine-style, vaneless air motor requires no oil!

58455

DYNABUFFER RANDOM ORBITAL POLISHER

- 5" (125 mm) Dia.
- Power: 0.21 hp (157 W)
- Speed: 5,500 RPM
- 14 mm Orbit





RANDOM ORBITAL MOTION 14 MM ORBIT

57550

PALM-STYLE ROTARY BUFFER/POLISHER

- 3" (75 mm) Dia.
- Speed: 2.400 RPM
- Power: 0.25 hp (186 W)
- · Adjustable Speed Regulator





ROTARY MOTION Rotary Polishing

57126

DYNABUFFER RANDOM ORBITAL POLISHER

- 3" (75 mm) Dia.
- Power: 0.16 hp (119 W)
- Speed: 7,000 RPM
- 14 mm Orbit





RANDOM ORBITAL MOTION 14 MM ORBIT

DN1

DYNABRADE NITRO SERIES® PISTOL GRIP MINI ORBITAL DENIBBER

- 1-1/4" (32 mm) Dia.
- Speed: 8,500 RPM
- Power: 0.02 hp (15 W)
- 1/8" (3 mm) Orbit





1/8" (3 MM) DIA. ORBIT For Fine Sanding

50225

DYNABRADE NITRO SERIES® PISTOL GRIP MINI ORBITAL SANDER KIT

Kit Includes:

DN1 Dynabrade Nitro Series®
1-1/4" (32 mm) Dia. Pistol Grip
Mini Orbital Sander

54086 1-1/4" (32 mm) Mini-Dynorbital® Disc Pad Foam, Very Soft Density

78994 1-1/4" (32 mm) Dia. A3 Sandpaper (50 qty.)



78995 1-1/4" (32 mm) Dia.

A5 Sandpaper (50 qty.)

78996 1-1/4" (32 mm) Dia.

A7 Sandpaper (50 qty.)


95756 Speed Regulator

POLISHING PRODUCTS

NEW DYNABRADE COMPOUNDS

+ Water based, Silicone-Free, Zero Fillers

+ Body Shop Safe



POLISHING PADS & FOAMS

MOST AGGRESSIVE

1000



DYNACUT™ WOOL PAD

MODEL 79701 5-1/2" (145 MM) MODEL 79706 6-1/2" (165 MM)

- Premium 100% wool polishing pads with an integrated foam interface layer that provides maximum cutting performance on fresh, cured and worn paint surfaces.
- DynaWool™ pads are the most abrasive polishing pad generating the highest cut rate.
- Used with DynaOne Compound when removing deep scratches and after sanding with P1500 grit discs.
- *Wool not intended for use on Random Orbital Buffers



DYNACUT™ MICROFIBER PAD

MODEL 79708 5-1/2" (145 MM) MODEL 79707 6-1/2" (165 MM)

- This microfiber pad features a blend of two different microfiber grades (black and white in color) that provides the ability to cut, polish and finish in one step.
- With both cutting fibers, this pad can remove light to moderate scratches, polish to perfection and buff to a high shine with one single pad.
- Use with DynaOne Compound for best results.

*Microfiber not intended for use on Rotary Buffers

• Conical foams for excellent finishing results • Long lasting and heat resistant cell structure



BLUE POLISHING PAD

MODEL A9630 3" (75 MM) MODEL A9650 5" (125 MM) MODEL A9660 6" (150 MM) MODEL A9680 8" (200 MM)

DENSITY: Hard TYPE: Extra Cutting Pad

- + Ideally combined with: Dynabrade DynaZero Compound
- This pad is designed for maximum cut.



RED POLISHING PAD

MODEL A9530 3" (75 MM) MODEL A9550 5" (125 MM) MODEL A9560 6" (150 MM) MODEL A9580 8" (200 MM)

DENSITY: Medium TYPE: Cutting Pad

- + Ideally combined with:
 Dynabrade DynaOne Compound
- This pad has a strong initial cut and softens slightly under heat, which ensures a great finish.



LEAST AGGRESSIVE

ORANGE POLISHING PAD

MODEL A9430 3" (75 MM) MODEL A9450 5" (125 MM) MODEL A9460 6" (150 MM) MODEL A9480 8" (200 MM)

DENSITY: Soft TYPE: Universal Pad

- Ideally combined with:
 Dynabrade DynaQuick and
 DynaTwo Compounds
- Pad can also be used as a one-step solution with the DynaQuick.

HOOK-FACE BUFFING AND POLISHING PADS



TERRY CLOTH

 Application and removal of waxes and polishes.



SYNTHETIC WOOL

 Easier to control and more aggressive than foam pads.



NATURAL SHEEPSKIN

 Durable well balanced natural wool fibers for fast finishing.

| Model No. | Pad Dimensions | Pad Material | Туре |
|-----------|-------------------|-------------------|-----------|
| 90027 | 3" (76 mm) | Terry Cloth | Polishing |
| 90028 | | Synthetic Wool | |
| 90080 | | Natural Sheepskin | |
| 90034 | 3-1/2" (89 mm) | Natural Sheepskin | |
| 90036 | 5" (127 mm) | Natural Sheepskin | |
| 90081 | | Natural Sheepskin | |



90082

NATURAL SHEEPSKIN

• 7" (178 mm) Dia. Polishing Pad



90083

POLISHING BONNET

8" (203 mm) Dia.
 Cutting Pad Assembly



MINI RAPTOR 2

AUTOMOTIVE VACUUM SYSTEMS

PORTABLE PROFESSIONAL CLEANING SYSTEM







