

**Important: This is an oil free tool.
Do not use air oil in the inlet or system.**

Parts Page Reorder No. PD03•19
Effective May, 2003
Supersedes PD02•30

Wet Dynabug® "Model T"

Models:

57908 — With 5" Diameter Hook Pad

57909 — With 6" Diameter Hook Pad


Air Motor and Machine Parts

⚠ WARNING

Always operate, inspect and maintain this tool in accordance with the Safety Code for portable air tools (ANSI B186.1) and any other applicable safety codes and regulations. Please refer to Dynabrade's Warning/Safety Operating Instructions for more complete safety information.

Index Key

No.	Part #	Description
1	53856	Throttle Lever
2	58091	Housing - 5" Model
	58080	Housing - 6" Model
3	58085	Polyurethane Elbow
4	57988	Inlet Hose Assembly
5	12156	O-Ring
6	95405	Button Head Screws (8)
7	57982	Clip Retainer
8	96493	Set Screw
9	57997	Base Plate - 5" Model
	57987	Base Plate - 6" Model
10	58092	Spacer
11	57981	Turbine Wheel Assembly
12	97121	O-Ring
13	57983	Base Plate Door
14	58084	Motor Shaft
15	01025	O-Ring (3)
16	58086	5" Channel Hook Pad
	58093	6" Channel Hook Pad
17	95979	Pin
18	53863	Gasket
19	53852	Plate Seal
20	01464	Seal
21	01472	Tip Valve
22	01468	Spring
23	01494	Inlet Bushing
24	58083	Nozzle
25	95288	O-Ring (3)
26	58076	Valve Shaft
27	50586	Key
28	95730	O-Ring (2)
29	58078	Collar
30	58077	Flow Control Valve
31	57991	Snap Ring
32	96221	1/4" Tubing - 20'
33	58079	Siphon Weight
34	56027	Insert
35	58089	Siphon Weight Assembly
36	95697	Snap Ring
37	53857	Valve Stem
38	57064	Speed Regulator



Recommended Option For Contour Sanding
(Fits between Sanding Back-Up Pad and Abrasive)
Interface Pads
5" - 53978
6" - 53980

KEY

- G** Grease: G₁ = Lubriplate 630 AA
- A** Adhesive: A₂ = Loctite #271
A₈ = Loctite #567
- T** Torque: N·m x 8.85 = In. - lbs.

Important Operating, Maintenance and Safety Instructions

Carefully read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool.

Warning: Hand, wrist and arm injury may result from repetitive work motion and overexposure to vibration.

Operating Instructions:

Warning: Eye, face, sound, respiratory, and body protection must be worn while operating power tools. Failure to do so may result in serious injury or death. Follow safety procedures posted in workplace.

1. With power source disconnected from tool, securely fasten abrasive/accessory on tool.
2. Install air fitting into inlet bushing of tool. Important: Secure inlet bushing of tool with a wrench before attempting to install the air fitting to avoid damaging valve body housing.
3. Connect power source to tool. Be careful not to depress throttle lever in the process.

Maintenance Instructions:

1. Check tool speed regularly with a tachometer. If tool is operating at a higher speed than the RPM marked on the tool, the tool should be serviced to correct the cause before use.
2. Some silencers on air tools may clog with use. Clean and replace as required.
3. Use only genuine Dynabrade replacement parts. To reorder replacement parts, specify the **Model #**, **Serial #**, and **RPM** of your machine.
4. A Motor Tune-Up Kit (P/N **96169**) is available which includes assorted parts to help maintain motor in peak operating condition. Please refer to Dynabrade's Preventative Maintenance Schedule for a guide to expectant life of component parts.
5. Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters, ketones, chlorinated hydrocarbons or nitro carbons.
6. Only use **CLEAN WATER** as your source for the **57064** Siphon Water Assembly, any contaminate in the water will effect overall performance and longevity of tool.

Safety Instructions:

Products offered by Dynabrade should not be converted or otherwise altered from original design without expressed written consent from Dynabrade, Inc.



- **Important:** User of tool is responsible for following accepted safety codes such as those published by the American National Standards Institute (ANSI).
- Always disconnect power supply before changing abrasive/accessory or making machine adjustments.
- Inspect abrasives/accessories for damage or defects prior to installation on tools.
- Please refer to Dynabrade's Warning/Safety Operating Instructions Tag (Reorder No. **95903**) for more complete safety information.

Notice

All Dynabrade motors use the highest quality parts and metals available and are machined to exacting tolerances. The failure of quality pneumatic motors can most often be traced to an unclean air supply or the lack of lubrication. Air pressure easily forces dirt or water contained in the air supply into motor bearings causing early failure. It often scores the cylinder walls and the rotor blades resulting in limited efficiency and power. Our warranty obligation is contingent upon proper use of our tools and cannot apply to equipment which has been subjected to misuse such as unclean air, wet air or a lack of lubrication during the use of this tool.

One Year Warranty

Following the reasonable assumption that any inherent defect which might prevail in a product will become apparent to the user within one year from the date of purchase, all equipment of our manufacture is warranted against defects in workmanship and materials under normal use and service. We shall repair or replace at our factory, any equipment or part thereof which shall, within one year after delivery to the original purchaser, indicate upon our examination to have been defective. Our obligation is contingent upon proper use of Dynabrade tools in accordance with factory recommendations, instructions and safety practices. It shall not apply to equipment which has been subject to misuse, negligence, accident or tampering in any way so as to affect its normal performance. Normally wearable parts such as bearings, contact wheels, rotor blades, etc., are not covered under this warranty.

Model Number	Pad Size	Motor RPM	Sound Level	Air Flow Rate CFM/SCFM (LPM)	Air Pressure PSIG (Bars)	Orbit Diameter Inch (mm)	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
All Models	Various	20,000 Max.	88 dB(A)	2/17 (481)	90 (6.2)	3/16 (4.8) Max.	1.5 (.68)	8 (203)	4 (102)

Additional Specifications: Air Inlet Thread 1/4" NPT

Motor Assembly/Disassembly Instructions – “Model T” Dynabug®

Important: Manufacturers warranty is void if tool is disassembled before warranty expires.

A complete repair kit, part number **96169**, is available which includes special tools for correct disassembly/assembly of tool.

To Disassemble

1. Disconnect tool from power source.
2. Remove sanding pad (if necessary).
3. Unscrew **95405** Button Head Screws (4).
4. Lift **57982** Clip Retainer up about 1/2", to expose **57997** or **57987** Base Plate.
5. Remove **58085** Elbow from **57997** or **57987** Base Plate.
6. Remove **57988** Hose from **57997** or **57987** Base Plate.
7. Remove **58085** Polyurethane Elbow from **57997** or **57987** Base plate.
8. Disassemble housing assembly from base plate assembly, by pulling apart.
9. Invert assembly and insert spanner wrench to **58084** Motor Shaft, and remove (left-hand threads).
10. Remove **58092** Spacer. **Note:** Orientation of spacer on motor shaft.
11. Remove **57981** Turbine Wheel Assembly. **Note:** Turbine orientation of wheel assembly on motor shaft.

To Assemble:

Important: Be certain parts are clean and in good repair before assembling.

1. Slide **57983** Base Plate Door onto **58084** Motor Shaft.
2. Replace **57981** Turbine Wheel Assembly on motor shaft using the same orientation as when it was disassembled.
3. Replace **58092** Spacer on motor shaft using the same orientation as when it was disassembled.
4. Apply a slight amount of #271 Loctite® (or equivalent) to **58084** Motor Shaft threads, torque 15 N•m/133 in. - lbs.
5. Install subassembly into base plate assembly.
6. Apply a slight amount of grease to the flared end of **57988** Inlet Hose and assemble onto housing. Install **12156** O-Ring. Slide other end of tube over barb fitting in base plate (use adhesive if necessary).
7. Insert end of **58085** Polyurethane Elbow into open end of **58084** Motor Shaft.
8. Install housing assembly onto base plate assembly.
9. Slide **57982** Clip Retainer down onto **57997** Base Plate and install (4) **95405** Button Head Screws. Torque 3.4 N•m/30 in. - lbs.

Tool Assembly Complete. Please allow 30 minutes for adhesives to cure before operating tool.

Valve and Speed Regulator Assemblies:

1. Secure housing in vice using **57092** Collar or padded jaws.
2. Remove **01494** Inlet Bushing, **01468** Spring, **01472** tip valve and **01464** Seal from housing.
3. Remove **95697** Snap Ring. Pull the speed regulator and valve stem out of the housing. Remove the **01025** O-Rings (2).
4. Place new **01025** O-Rings (2) on the speed regulator and place in housing with valve stem. Install new **95697** Snap Ring.
5. Place new **01464** Seal in housing. Using tweezers or needle nose pliers, place the tip valve into housing so that the pin goes through the valve stem hole. Place new **01468** Spring into housing so small end is towards tip valve.
6. Place 1 drop of #567 Loctite® (or equivalent) on the threads of the inlet bushing and tighten into housing to 23 N•m/200 in. - lbs.

Note: This tool is an oil-free Dynabrade Tool. Therefore no air lube should be placed into the tool. Operate the machine for approximately 30 seconds before application to workpiece to determine if machine is working properly and safely.

58077 Flow Control Operating Instructions - See page 4.

Loctite® is a registered trademark of the Loctite Corp.

Optional Accessories




96169 Motor Tune-Up Kit

- Includes assorted parts to help maintain and repair motor.



50971 Lock Ring Tool

- Lock Ring Tool has a 3/8 in. square socket for use with 3/8 in. drive; breaker bar, ratchet head, or torque wrenches.



57092 Repair Collar

- Specially designed collar for use in vise to prevent damage to motor housing during disassembly/assembly.



56027 Insert

- Insert used as a filter in conjunction with the siphon weight assembly. Periodically change for best performance.



Interface Pads

- Soft foam allows the abrasive to conform to contours.
- Easily mounts between the sanding back-up pad and the hook 'n loop abrasive.
- Converts standard pad into a fine finishing and finessing pad.




5" - 53978

6" - 53980

Flow Control Operating Instructions

58077 Flow Control Operating Instructions

- Water flow can be easily adjusted at the rear of the tool, find the 58077 Flow Control Valve just right of the air inlet adapter.



Visit Our Web Site: www.dynabrade.com

Email: Customer.Service@Dynabrade.com



DYNABRADE, INC., 8989 Sheridan Drive • Clarence, NY 14031-1490 • Phone: (716) 631-0100 • Fax: 716-631-2073 • International Fax: 716-631-2524
 DYNABRADE EUROPE S.à.r.l., Zone Artisanale • L-5485 Wormeldange—Haut, Luxembourg • Telephone: 352 76 84 94 1 • Fax: 352 76 84 95 1

©DYNABRADE, INC., 2003

PRINTED IN USA