
31101
31102
95158-4
95167-4
95169

Dynascaler®
Air-Powered
PARTS


MODEL NUMBER: 31600 Dynaflange Floor Model

EFFECTIVE JUNE, 1990




SEE REVERSE SIDE FOR HANDLE ASSEMBLY

31610 HANDLE ASSEMBLY



31620 EDGE GUIDE ASSEMBLY



IMPORTANT

- Tool RPM rating must never exceed abrasive / accessory RPM rating, regardless of the tool's capacity.
- Check tool speed regularly with a tachometer. If tool is operating at a higher speed than the RPM marked on the tool, the tool should be serviced to correct the cause before use.
- 11299 Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components; operates 28 CFM @ 90 PSI; has 3/8" female ports.

Gear case of this DYNABRADE air tool should be lubricated every 50 hours by using 95541 grease gun and 95542 grease. To reorder:

95541 — Push-type grease gun; for one-hand operation.

95542 — Grease (10 oz. tube; 283.5 g) Multi-purpose for all types of bearings, cams, gears. High film strength; excellent resistance to water, steam, etc. workable range 0° F to 300° F.

IMPORTANT: ALL DYNABRADE AIR TOOLS MUST BE USED WITH A FILTER-REGULATOR-LUBRICATOR TO MAINTAIN ALL WARRANTIES.

TO ORDER REPLACEMENT PARTS SPECIFY THE MODEL AND SERIAL NUMBER OF YOUR MACHINE.

DYNABRADE, INC.
72 East Niagara St., Tonawanda, NY 14150-2398
(716) 694-4600 • Fax: (716) 694-4746 • Telex: 646540
1-800-828-7333 (USA) • 1-800-344-1488 (Canada)

©DYNABRADE, INC., 1990

PRINTED IN U.S.A.