Reorder No. D06.08

Dynabrade Right Angle Mini-Orbital Sander

For Quick, Efficient Removal of Dust Nibs and Defects



Right Angle Mini-Orbital Sander

Dynabrade's Right Angle Mini-Orbital Sander is designed for spot repair on gelcoat and clearcoat paint systems, plus finesse sanding of small areas. Utilizing a powerful .4 hp (298 W) air motor, this tool allows quick, efficient removal of dust nibs and defects. Precise 1/8" (3 mm) orbital action minimizes swirl marks on the work piece, ideal for dry and wet applications (with water from an outside source). Right Angle Mini-Orbital Sander is also lightweight and easy to use – the perfect combination of power and comfort!

Model 58037 Front Exhaust Model 5

Model 58039 Rear Exhaust

 Tool runs at 12,000 RPM and includes 1-1/4" (32 mm) diameter rubber sanding pad (54018). Also accepts optional 3/4" (19 mm) diameter rubber sanding pad (54017).

Model 58038 Front Exhaust

Model 58034 Rear Exhaust

Tool runs at 12,000 RPM and includes 1-1/4" (32 mm) diameter locking-type foam-face sanding pad (54031). Also accepts optional 1-1/4" (32 mm) diameter locking-type vinyl-face sanding pad (54033).

Model 58035 Front Exhaust

• Tool runs at 15,000 RPM and includes 1-1/4" (32 mm) diameter vinyl-face sanding pad (54088). Also accepts optional 3/4" (19 mm) diameter vinyl-face sanding pad (54087).

Gear Oil with

Gun Shown

	lugi'
ry	Model 58037
der	Front Exhaust Model 58039 Rear Exhaust, Extended Muffler

- Each model includes 95848 Gear Oil and 95541 Push-Type Gun, for lubricating tool gears through unique "dual wick" system. Increasing gear life extends the life of your tool!
- Optional safety-lock throttle lever is available (included in some regions).

Model Number	Exhaust	Motor Hp (W)	Motor RPM	Sound Level	Maximum Air Flow CFM/SCFM	Hose I.D. Size Inch (mm)	Orbit Pattern	Air Inlet Thread	Weight lb (kg)	Length Inch (mm)	Height Inch (mm)
58035	Front	.4 (298)	15,000	85	3/21 (595)	1/4" (6)	3 mm	1/4" NPT	1.6 (0.7)	5.4 (137)	3.8 (97)
58037	Front	.4 (298)	12,000	85	3/20 (566)	1/4" (6)	3 mm	1/4" NPT	1.6 (0.7)	5.4 (137)	3.8 (97)
58038	Front	.4 (298)	12,000	85	3/20 (566)	1/4" (6)	3 mm	1/4" NPT	1.6 (0.7)	5.4 (137)	4 (102)
58034	Rear	.4 (298)	12,000	79	3/21 (595)	1/4" (6)	3 mm	1/4" NPT	1.4 (0.6)	7.5 (190)	4 (102)
58039	Rear	.4 (298)	12,000	79	3/21 (595)	1/4" (6)	3 mm	1/4" NPT	1.4 (0.6)	7.5 (190)	3.8 (97)

95848 *Dynabrade Gear Oil**

- 2.5 oz. (74 ml) tube.
- Formulated for Dynabrade geared tools utilizing a wick-type lubrication system.

95541 Push-Type Grease/Oil Gun*

One-hand operation.



*Included with tool. Also sold separately.

SANDING PADS

For Adhesive-Backed Abrasives



Vinyl-Face Pad

• 1/4" (6 mm) thick sponge, vinyl-face.



Medium Density Rubber Pad

• 1/4" (6 mm) thick sponge, 60 durometer rubber.



Soft Locking-Type Pad

Foam-face and vinyl-face.

Part No.	Diameter Inch (mm)	Pad Type	Locking Type	Maximum RPM
54017	3/4" (19)	Rubber		12,000
54018	1-1/4" (32)	Rubber		12,000
54031	1-1/4" (32)	Foam	~	12,000
54033	1-1/4" (32)	Vinyl	/	12,000
54087	3/4" (19)	Vinyl		15,000
54088	1-1/4" (32)	Vinyl		15,000

DISTRIBUTED BY:

95745

Speed Control Dial

- Adjust tool speed.
- Sold separately.



COATED ABRASIVE DISCS

1-1/4" (32 mm) Diameter

· PSA (Adhesive-Backed).

Part No.	Aluminum Oxide	Silicon Carbide	Grit
93191	V		1,000
93280		V	80
93281		V	120
93283		V	180
93284		V	220

Visit our Website for more Tools and Related Accessories www.dynabrade.com

DYNABRADE. INC.

DYNABRADE

8989 Sheridan Drive • Clarence, New York 14031-1490 • Phone: (716) 631-0100 Fax: 716-631-2073 • *US Consumers Call Toll Free: 1-800-828-7333*

DYNABRADE INTERNATIONAL

8989 Sheridan Drive • Clarence, New York 14031-1490 • Phone: (716) 631-0100 Fax: 716-631-2524 • Canadian Consumers Call Toll Free: 1-800-344-1488

DYNABRADE EUROPE S.à r.i.

Zone Artisanale • L-5485 Wormeldange—Haut, Luxembourg Phone: +352 768 494 1 • Fax: +352 768 495

DYNABRADE DO BRASIL

Rua Oneda, 632 • Sao Bernardo do Campo • SP - CEP 09895-280 Phone (11) 4390-0133 • Fax (11) 4399-1067 Try Our U.S. Consumer Toll Free Number 1-888 DYNABRADE (or 1-800-828-7333)







