

AN AMERICAN Classic REBORN

Dating back to 1939, National Detroit has set the standard for high-quality, American made pneumatic tools for the automotive aftermarket industry. Dynabrade continues this tradition of excellence by offering these legacy tools that are still proudly made in the USA.



900 Gear-Driven Sander

"Mud Hog" Offers Fast, Controllable Stock Removal

Model 900 8" (203 mm) Dia. Sanding Pad

- Slow-speed 900 RPM tool is ideal for leveling and spotting high and low spots on work surface.
- Moves Sanding Pad in epicycloidal motion for rapid, controllable stock removal.
- Strips to bare metal three times faster. Buffs clear coat repairs in half the time!
- Includes Dynabrade Vinyl-Face Sanding Pad, 56234 (8" dia.).



**NATIONAL DETROIT
ORIGINAL!**



**EPICYCLOIDAL
MOTION**

900 Applications

- Stripping, Stock Removal, Leveling, Paint Removal, Sanding Body Filler, Shaping

For the most current specifications of any tool, visit Dynabrade.com.

Model	Pad Dia. Inch (mm)	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Air Pressure PSIG (Bar)	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
900	8 (203)	.25 (182)	800	84 dB(A)	23 (651)	3/8 (10)	1/4" NPT	90 (6.2)	5.2 (2.4)	5.5 (141)	10.8 (274)

DAQ Dual-Action Sander

Unique "Wobble" Effect for Aggressive Sanding

Model DAQ5 5" (127 mm) Dia. Sanding Pad

Model DAQ6 6" (152 mm) Dia. Sanding Pad


- Unique "wobble" effect allows Sanding Pad to rise and fall, for aggressive interrupted contact.
- Heat generation is minimized and abrasive does not load up, allowing longer abrasive life!
- 10,000 RPM dual action, from rotary to 3/8" random orbital.
- Comfortable bicycle grip tool handle.
- Includes Dynabrade Vinyl-Face Sanding Pad, 56106 (5" dia.) or 56107 (6" dia.).



**NATIONAL DETROIT
BEST SELLER!**



**MAXIMUM
AIR PRESSURE
75 PSIG**



**ROTARY
MOTION**



**3/8" (10 MM)
DIA. ORBIT**

DAQ Applications

- Sanding filler & primer
- Shaping & forming filler, wood & fiberglass
- Removing paint, rust & scale
- Featheredging, Smoothing Welds, Removing Flash, Deburring, beveling, corner breaking

Model	Pad Dia. Inch (mm)	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Air Pressure PSIG (Bar)	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
DAQ5	5 (127)	.25 (182)	10,000	84 dB(A)	23 (651)	3/8 (10)	1/4" NPT	75 (5.17)	4.4 (2)	8.5 (216)	4.25 (108)
DAQ6	6 (152)	.25 (182)	10,000	84 dB(A)	23 (651)	3/8 (10)	1/4" NPT	75 (5.17)	4.4 (2)	8.5 (216)	4.25 (108)



Dynabrade, Inc.
1-800-828-7333
dynabrade.com/aftermarket

Reorder No. D21-16

