



AUTOMOTIVE AFTERMARKET SOLUTIONS



WE LISTEN. WE OBSERVE. **WE OPTIMIZE.**



INCREASE PRODUCTION

Dynabrade was founded on the tradition of giving professional tool operators and technicians tools of the highest quality, allowing their work to be completed more quickly than conventional methods. American Made Dynabrade tools and all new Dynabrade Nitro Series™ tools for collision repair and vehicle restoration in this catalog will help technicians move more vehicles through the garage in less time overall.

DECREASE LABOR

Dynabrade tools accomplish tasks more quickly or in a different fashion than traditional methods. Technicians are able to reduce time spent completing an application utilizing Dynabrade tools, which not only saves time but lowers expenses related to repair and refinishing.

INCREASE VALUE

The value Dynabrade delivers extends beyond providing high-quality, long-lasting tools and accessories. Using source capture equipment promotes a clean, safe, and healthy work environment for operators; while substantial cost savings can also be achieved by focusing on reducing cycle times for labor intensive operations.

“Using Dynabrade has been invaluable to making sure my builds look their best. From metal finishing to buffing my paint work I can fine tune my finished product. The tools are sturdy, comfortable and long lasting. There is a tool for everything we do with the quality I rely on.” ~ Miguel Perez

Miguel Perez
Extreme Paint Shop & Refinish Kulture
Palm City, FL





BODY SHOP

6



MULTI-PURPOSE TOOLS

24



PAINT SHOP

40



CLEAN AIR SOLUTIONS

48



ACCESSORIES

56



ABRASIVES

70



A TRADITION OF INNOVATION

Dynabrade tools have been manufactured by skilled craftsmen and women in Buffalo New York, USA for **more than 50 years**, providing operators and technicians with reliable portable air tools able to complete the most challenging applications. Teal colored tools contained within this catalog have been purposefully selected from the **over 800 Industrial tool models** that Dynabrade manufactures as the best possible tool in its category for an automotive technician. These tools are intended for heavy-duty, all day, everyday use in fast-paced, high-volume work environments.

Tools for every stage in the repair or restoration of a vehicle are available from Dynabrade. Belt tools, cut-off tools, die grinders, disc sanders and other surface preparation tools typically found in the body shop are all represented in the following pages. These tools accomplish more than just prep work, they create the foundation painters and finishers to work from before delivering the final product.

Multipurpose tools, like random orbital sanders, bridge the gap between the body shop and the paint booth and are commonly used by both body and paint technicians. Dynabrade produces the widest range of sanders and polishers in the industry so that technicians can optimize their tool choice for their specific application.

As a tool manufacturer founded on innovation, Dynabrade is excited to share for the first time a state-of-the-art polishing process hyper focused on eliminating steps in clear coat polishing applications. Dynabrade buffing tools, pads, compounds and abrasives combine to create a repeatable polishing recipe that allows technicians to quickly move more vehicles through the final repair/restoration stages.



CONTINUING THE TRADITION

Dynabrade Nitro Series™ tools are high-quality, purpose-built tools designed to provide automotive technicians with entry level, Dynabrade quality air tools. By partnering with and learning from automotive technicians Dynabrade understands that an automotive technician's daily routine can be much different than an industrial tool operator's. No two jobs are the same for a body or paint tech and job often requires a diverse selection of tools.

Like traditional Dynabrade tools, Dynabrade Nitro Series™ spans a wide variety of categories including belt tools, die grinders, disc sanders, cut-off tools as well as surface preparation tools, buffers, and polishers. Within these categories Dynabrade Nitro Series™ tools are designed to address the specific challenges automotive technicians face. A prime example is cut-off tool ECU4, featuring an extended reach for greater access to recessed areas and multi-position guard improving technician sightlines and promoting technician safety in the body shop.

Painters and finishers also benefit from Dynabrade Nitro Series™ innovations with several new buffer/polisher models now available. Model EB3 is sure to solve the challenges buffing contours and side-view mirrors present. As a compact and lightweight tool including an extension, technicians will enjoy effortless maneuverability and the ability to polish difficult to reach painted surfaces.

Dynabrade innovation in the automotive after-market is not limited to air tools. In addition to a state-of-the-art polishing system Dynabrade is also excited to introduce Extreme Orange and DynaSoft™ flexible abrasive discs. Specifically designed to be used wet or dry and available in grits up to 3,000, Dynabrade now offers body and paint technicians complete solutions to their daily tasks.





BODY SHOP

Whether repairing a vehicle damaged in an accident or from weather, to restoring or customizing a classic; auto body professionals utilize a broad selection of tools in their daily tasks. Dynabrade provides technicians with dependable, ergonomic and powerful tools used for vehicle tear-down, frame & panel repair, and welding applications. The work

of the body technician must be meticulously completed, following manufacturer S.O.P.'s, and with great attention to detail because their work is the foundation for the final finish produced from the paint shop. Dynabrade tools optimize body shop applications helping technicians move vehicles quickly through a repair plan and into the paint shop.

The benefit of using Dynabrade tools extends beyond the technician to the overall bottom line of the repair facility or collision shop where significant savings can be realized. Savings can be realized through efficient abrasive use, decrease in cycle times as well as increased operator and shop safety.

VERSATILITY IN THE BODY SHOP




Using a Dynabrade Nitro Series™ NitroFile belt tool body shop technicians can quickly grind through spot welds for a fraction of the cost of using expensive spot weld cutters. Abrasive belt tools also blend welds, grind through seized bolts or even remove seam sealer making them a must-have, versatile tool for any shop.



The Dynabrade Nitro Series™ NitroZip surface preparation tool can be used with an eraser wheel to delicately remove adhesive-backed decals without excessive heat build-up, keeping painted finishes protected. When used with a wire wheel the Dynabrade Nitro Series™ NitroZip quickly removes rust and cleans around rivets.



Die Grinders provide a great deal of options for technicians within the body shop. Having a 1/4" (6 mm) collet allows for the use of burs along with coated and non-woven abrasives in a variety of shapes and sizes.



DYNABRADE NITRO SERIES™ NITROFILE ABRASIVE BELT TOOL

Abrasive belt tools can be used throughout a body shop for a variety of sanding, blending and finishing applications. Able to use both coated and non-woven abrasives allows technicians to perform a wide range of applications from spot weld and door skin removal to surface preparation when plastic welding a bumper.

FEATURES

- ▶ Sanding head pivots 360°, for working in previously inaccessible areas
- ▶ Quick and easy belt and contact arm changes
- ▶ Front exhaust directs dust away from operator and extends belt life
- ▶ Ergonomic, offset handle with safety-lock throttle lever
- ▶ Runs belts 1/4"-3/4" wide by 18" long (3 x1 9 mm by 457 mm)

INCLUDES

11206 Contact Arm for 1/2" wide belts



Model NF1

GEARLESS MOTOR

SPEED
20,000 RPM

POWER
0.5 hp (373 W)

18" (457 MM) BELT

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Air Pressure PSIG (Bar)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
NF1	81 dB(A)	22 (623)	1/4" NPT	3/8 (10)	90 (6.2)	2.8 (1.3)	5 (127)	15 (381)

BENEFITS



Grinding hard to reach spot welds, or even through a seized or stripped bolt is easy with Dynabrade belt tools that allow technicians to access tight areas with greater control.



Using a belt rather than a drill bit is a quick, efficient and economical way to remove spot welded panels while leaving material to reattach the new or repaired panel.

ELECTRIC DYNAFILE® II ABRASIVE BELT TOOL

For garages and technicians using corded tools the Electric Dynafile®II is an ideal option for their sanding, blending and surface prep applications. Contact arms are interchangeable with pneumatic NitroFile.

FEATURES

- Comfortable switch with "lock on" feature
- Easily accessible brushes for quick replacement
- Sanding head pivots 360°, for working in previously inaccessible areas
- Side handle mounts on either side for left or right-handed operators
- Double-insulated motor for operator safety
- Runs belts 1/8"-3/4" wide by 18"-24" long
- 8' long electric cord

INCLUDES

11203 Contact Arm

ELECTRIC DYNAFILE® II VERSATILITY KIT

INCLUDES

40610 Electric Dynafile® II
Three Contact arms: 11203, 11202 and 11204
Eight abrasive belts of various grits
An assortment of platen pads
Durable carrying case



Model 40610

POWER
720 W

**360° PIVOT BELT
HEAD ASSEMBLY**

18" (457 MM) BELT



Model 40611

Model Number	Motor RPM	Maximum Watts Out	Abrasive Belt Size Inch (mm)	Voltage	Current Amps	Phase	Frequency	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
40610	11,000	720	1/8"-3/4" (3-19) W x 18-24 (457-610) L	120 V (AC)	6	1	60 Hz	5 (2.3)	5.5 (140)	19 (483)

Additional Specifications: Maximum 2,520 SFPM (768 SMPM)

Available in the USA only

RELATED PRODUCTS



Contact Arms
Page 61



Abrasive Belts
Page 91



General
Clean-up
Page 49

DYNABRADE NITRO SERIES™

MINI-NITROFILE

A compact belt tool designed for the frequent grinding applications technicians are challenged by where space is limited and access is restricted.

FEATURES

- ▶ Sand and deburr in tight spots
- ▶ Lightweight, ergonomic and maneuverable
- ▶ Accepts coated and abrasive impregnated non-woven nylon belts
- ▶ Swing away belt guard for easy abrasive change
- ▶ Multi-position grinding head pivots 180°

INCLUDES

15026 Contact Arm for 1/2" wide x 12" long abrasive belts



Model MNF1

GEARLESS MOTOR

SPEED
25,000 RPM

POWER
0.4 hp (298 W)

12" (305 MM) BELT

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Abrasive Belt Size Inch (mm)	Air Pressure PSIG (Bar)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
MNF1	78 dB(A)	22 (623)	1/4" NPT	1/4 (6)	1/2"-12" (13 x 305)	90 (6.2)	1.2 (0.5)	3.5 (89)	11.75 (298)

BENEFITS



The belt housing on mini-belt tools swings open for easy abrasive changes without the need for extra tools.



Being compact and lightweight makes mini-belt tools great for working in tight areas or overhead.

MINI-DYNAFILE® II

A compact belt tool designed for the frequent grinding applications technicians are challenged by where space is limited and access is restricted. The Mini-Dynafite®II is manufactured to withstand grueling applications, and be used for extended periods of time.

FEATURES

- Grind, sand, and deburr in tight spots
- Lightweight, ergonomic and maneuverable
- Accepts coated and abrasive impregnated non-woven nylon belts
- Swing away belt guard for easy abrasive change
- Multi-position grinding head pivots 180°

INCLUDES

15026 Contact Arm for 1/2" wide x 12" long abrasive belts

MINI-DYNAFILE® II VERSATILITY KIT

INCLUDES

15003 Mini-Dynafite® II
Three Contact arms: 15026, 15028 and 15030
Eight abrasive belts of various grits
Sample 1/2" wide coated abrasive and non-woven nylon
Durable carrying case



Model 15003

GEARLESS MOTOR

SPEED
25,000 RPM

POWER
0.4 hp (298 W)

12" (305 MM) BELT

Model 15006



Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Air Pressure PSIG (Bar)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
15003	80 dB(A)	20 (566)	1/4" NPT	1/4 (6)	90 (6.2)	1.8 (0.8)	3.5 (89)	11.75 (248)

RELATED PRODUCTS



Contact Arms
Page 61



Air Delivery
Accessories
Page 59



Non-Woven
Abrasive Belts
Page 95



General
Clean-up
Page 48

DYNABRADE NITRO SERIES™ 4"(102 MM) DIAMETER EXTENSION RIGHT ANGLE CUT-OFF WHEEL TOOL

FEATURES

- ▶ Model accepts 4" (102 mm) diameter Type 41 reinforced Cut-Off Wheels, with 3/8" center hole
- ▶ Composite grip absorbs vibration and reduces cold air transmission to operator
- ▶ Lock-lever controlled, multi-position guard



Model ECU4

SPEED

14,000 RPM

POWER

1 hp (746 W)

Model Number	Sound Level	Tool Thread	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Air Pressure PSIG	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
ECU4	87 dB(A)	3/8"-24	40 (1,132)	1/4" NPT	3/8 (10)	90 (6.2)	4 (1.8)	1.9 (49)	14.75 (375)

***IMPORTANT:** Speed of tool must not exceed maximum operating speed of accessory.
Never mount non-reinforced grinding wheels. Always wear eye, face & body protection.

BENEFITS



The Dynabrade Nitro Series™ ECU4 shown here provides an operator with greater control of the tool while working above head, in a difficult to reach area.

IMPORTANT: Always wear eye, face and body protection.



Cutting through panels is easy and accurate using Dynabrade cut-off tools. Powerful air motors drive abrasive wheels efficiently, and the variety of formats - straight, offset, right angle - allow operators greater control in their application.

3" (76 MM) DIAMETER 7° OFFSET CUT-OFF WHEEL TOOL

FEATURES

- Accepts 3" (76 mm) diameter reinforced Type 41 cut-off wheels with a 3/8" center hole.
- Gearless motor design for reduced maintenance and vibration.
- Front exhaust helps cool the cut-off wheel and enhances visibility while cutting.

4" (102 MM) DIAMETER EXTENSION RIGHT ANGLE CUT-OFF WHEEL TOOL

FEATURES

- Accepts 4" (102 mm) diameter reinforced Type 41 cut-off wheels with a 3/8" center hole (Wheel width of 1/32" - 1/8")
- Governor-controlled motor maintains motor rpm under heavy load
- 6" extension allows for two-hand grip, providing added control when creating long, straight cuts

3" (76 MM) DIAMETER RIGHT ANGLE CUT-OFF WHEEL TOOL

FEATURES

- Accepts 3" (76 mm) diameter reinforced Type 41 cut-off wheels with a 3/8" center hole
- Right-angle gears provide high torque, and utilize the Dynabrade "dual-wick" system for long life
- Adjustable wheel guard enhances visibility and provides maximum technician protection

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
52420	82 dB(A)	28 (793)	1/4" NPT	3/8"-24 Male	3 (1.3)	3.13 (79)	8 (202)
54736	83 dB(A)	40 (1,133)	1/4" NPT	3/8"-24 Male	3.7 (1.7)	11.37 (288)	3.1 (78)
54730	83 dB(A)	41 (1,161)	1/4" NPT	3/8"-24 Male	3.2 (1.4)	3.07 (113)	8 (202)

Additional Specifications: Air Pressure 90 PSIG (Bar)

***IMPORTANT:** Speed of tool must not exceed maximum operating speed of accessory.
Never mount non-reinforced grinding wheels. Always wear eye, face & body protection.



Model 52420

SPEED
20,000 RPM

POWER
0.5 hp (373 W)



Model 54736

SPEED
13,500 RPM

POWER
0.7 hp (522 W)



Model 54730

SPEED
18,000 RPM

POWER
0.7 hp (522 W)

RELATED PRODUCTS



Lubrication
Page 69



Dynaswivel®
Page 58



Abrasives
Page 70



Clean Air
Equipment
Page 53

4" (102 MM) DEPRESSED CENTER WHEEL GRINDER RIGHT ANGLE


For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

FEATURES

- ▶ Aluminum right angle head, composite housing model, rear exhaust
- ▶ "Dual-wick" lubrication system saturates gears with oil for increased performance, extended life and reduced downtime
- ▶ Accepts optional 4" (102 mm) diameter Type 27 reinforced Depressed Center Wheels, with 3/8" center hole (wheel width of 3 to 6 mm)
- ▶ Adjustable wheel guard provides maximum operator protection
- ▶ Safety-lock lever is included
- ▶ Model has side handle for left or right-hand use

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
54775	83 dB(A)	40 (1,133)	1/4" NPT	3/8 (10)	2.9 (1.3)	3.07 (78)	8 (202)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar) • Tool Thread 3/8" -24 Male



Includes 95848 Gear Oil and 95541 Gear Oil Gun. Lubrication every 8 hours of run time extends gear life.

4" (102 MM) DEPRESSED CENTER WHEEL GRINDER RIGHT ANGLE

For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

FEATURES

- ▶ Steel housing models
- ▶ "Dual-wick" lubrication system saturates gears with oil for increased performance, extended life and reduced downtime
- ▶ Accepts optional 4" (102 mm) diameter Type 27 reinforced Depressed Center Wheels, with 3/8" center hole (wheel width of 3 to 6 mm)
- ▶ Adjustable wheel guard provides maximum operator protection
- ▶ Safety-lock lever is included

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
54773	81 dB(A)	40 (1,133)	1/4" NPT	3/8 (10)	3.5 (1.6)	3 (78)	11.3 (288)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar) • Tool Thread 3/8" -24 Male



Model 54775

SPEED
13,500 RPM

POWER
0.7 hp (522 W)

DIAMETER
4" (102 mm)



Model 54773

SPEED
12,000 RPM

POWER
0.7 hp (522 W)

DIAMETER
4" (102 mm)

DYNABRADE NITRO SERIES™ RECIPROCATING SAW

A versatile tool used for cutting sheet metal, piping and plastic panels. Straight, accurate cuts are achievable thanks to this lightweight and easy to maneuver saw.

FEATURES

- The perfect tool for cutting materials such as plastics, fiberglass, composites, aluminum and sheet metal
- Small, lightweight design provides greater accessibility and increases operator productivity
- Adjustable rear exhaust directs air away from work piece
- Ergonomic rubber grip offers improved comfort during extended use

INCLUDES

90928 24 tooth saw blade
90929 32 tooth saw blade

Saw blades also available for purchase separately.



Model RS1

**9,000 STROKES
PER MINUTE**

Model Number	Strokes Per Minute	Stroke Length	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
RS1	9,000	3/8"	83 dB(A)	10 (280)	3/8 (10)	1/4" NPT	1.5 (68)	2 (50)	10.4 (264)

RELATED PRODUCTS



DynaJet In-Line
Blow Gun
Safety-Tip
Design
Page 60



Dynaswivel®
Page 58



Lubricants
Page 69



Abrasives
Page 70

DYNABRADE NITRO SERIES™ RIGHT ANGLE DIE GRINDER

For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

FEATURES

- ▶ Compact, lightweight contemporary tool design permits easy access to tight areas
- ▶ Thermoplastic rubber tool grip reduces cold air transmission and absorbs vibration
- ▶ Smooth, efficient air motor
- ▶ Includes safety-lock lever; rotational rear exhaust to direct away from operator
- ▶ 3-piece collet, interchangeable inserts, low collet runout < .003" (0,07 mm)



Model DGR31
Model DGR32

SPEED
18,000 RPM

POWER
0.3 hp (224 W)

COLLET
1/4" or 6 mm

DYNABRADE NITRO SERIES™ RIGHT ANGLE DIE GRINDER

For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

FEATURES

- ▶ Compact, lightweight contemporary tool design permits easy access to tight areas
- ▶ Thermoplastic rubber tool grip reduces cold air transmission and absorbs vibration
- ▶ Smooth, efficient air motor
- ▶ Includes safety-lock lever; rotational rear exhaust to direct away from operator
- ▶ 3-piece collet, interchangeable inserts, low collet runout < .003" (0,07 mm)



Model DGR51
Model DGR52

SPEED
14,000 RPM

POWER
0.5 hp (373 W)

COLLET
1/4" or 6 mm

Model Number	Collet Insert	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
DGR31	1/4"	86 dB(A)	18 (510)	1/4" NPT	3/8 (10)	1.2 (.54)	1.6 (41)	6.5 (165)
DGR32	6 mm	86 dB(A)	18 (510)	1/4" NPT	3/8 (10)	1.2 (.54)	1.6 (41)	6.5 (165)
DGR51	1/4"	84 dB(A)	26 (736)	1/4" NPT	3/8 (10)	1.6 (.73)	2.7 (68)	7.1 (180)
DGR52	6 mm	84 dB(A)	26 (736)	1/4" NPT	3/8 (10)	1.6 (.73)	2.7 (68)	7.1 (180)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

RIGHT ANGLE DIE GRINDER

FEATURES

- ▶ Rear Exhaust Models with Standard Muffler
- ▶ Governor-controlled motor maintains speed under load
- ▶ Kevlar® phenolic vanes for longer life
- ▶ Needle bearing assures proper shaft alignment
- ▶ Lightweight ergonomic design for greater comfort and control
- ▶ Dual wick lubrication system, saturated with gear oil for extended gear life for over 700 hours



Model 48316

SPEED
15,000 RPM

POWER
0.4 hp (298 W)

COLLET
1/4" and 6 mm

RIGHT ANGLE DIE GRINDER

FEATURES

- ▶ Composite Housing Models
- ▶ All models include 1/4" and 6 mm Collet Insert
- ▶ Thermal-insulated handle reduces cold air transmission to operator
- ▶ Tools include lightweight aluminum head
- ▶ Safety-lock throttle lever prevents accidental startup of tool



Model 54343

SPEED
12,000 RPM

POWER
0.4 hp (298 W)

COLLET
1/4" and 6 mm

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Collets Included	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
48316	79 dB(A)	25 (708)	1/4" & 6 mm	1/4" NPT	1/4 (6)	1 (.47)	2.9 (73)	6.5 (164)
54343	80 dB(A)	38 (1,076)	1/4" & 6 mm	1/4" NPT	3/8 (10)	2.2 (1)	2.88 (73)	7.8 (200)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

RELATED PRODUCTS



DynaJet In-Line
Blow Gun
Safety-Tip
Design
Page 60



Carbide Burrs
Page 99



Dynaswivel®
Page 58



Filter/Regulator/
Lubricator
Page 58

DYNABRADE NITRO SERIES™ STRAIGHT-LINE DIE GRINDER

FEATURES

- ▶ Compact, lightweight contemporary tool design
- ▶ Thermoplastic rubber tool grip reduces cold air transmission and absorbs vibration
- ▶ Smooth, efficient air motor
- ▶ Includes safety-lock lever; rotational rear exhaust to direct away from operator
- ▶ 3-piece collet, interchangeable inserts, low collet runout < .003" (0,07 mm)



Model DGS31
Model DGS32

SPEED
25,000 RPM

POWER
0.3 hp (224 W)

COLLET
1/4" or 6 mm

DYNABRADE NITRO SERIES™ STRAIGHT-LINE DIE GRINDER

FEATURES

- ▶ Compact, lightweight contemporary tool design
- ▶ Thermoplastic rubber tool grip reduces cold air transmission and absorbs vibration
- ▶ Smooth, efficient air motor
- ▶ Includes safety-lock lever; rotational rear exhaust to direct away from operator
- ▶ 3-piece collet, interchangeable inserts, low collet runout < .003" (0,07 mm)



Model DGS51
Model DGS52

SPEED
20,000 RPM

POWER
0.5 hp (373 W)

COLLET
1/4" or 6 mm

Model Number	Collet Insert	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
DGS31	1/4"	84 dB(A)	18 (510)	1/4" NPT	3/8 (10)	.98 (.44)	1.8 (44)	6.2 (157)
DGS32	6 mm	84 dB(A)	18 (510)	1/4" NPT	3/8 (10)	.98 (.44)	1.8 (44)	6.2 (157)
DGS51	1/4"	83 dB(A)	26 (736)	1/4" NPT	3/8 (10)	1.35 (.61)	2 (51)	7 (178)
DGS52	6 mm	83 dB(A)	26 (736)	1/4" NPT	3/8 (10)	1.35 (.61)	2 (51)	7 (178)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

STRAIGHT-LINE DIE GRINDER

Dynabrade 0.4 hp die grinders offer an innovative design for peak efficiency and longer life. Ideal for rapid material removal, deburring, finishing and polishing.

FEATURES

- Governor-controlled motor maintains consistent motor speed under load and delivers optimal power
- Case-hardened tool cylinder to retain core toughness and prevent cracking
- Comfortable tactile grip is co-molded to composite housing, providing comfortable non-slip grip



Model 48325

SPEED
25,000 RPM

POWER
0.4 hp (298 W)

COLLET
1/4" and 6 mm

STRAIGHT-LINE DIE GRINDER

FEATURES

- Gearless for reduced maintenance
- Includes 1/4" & 6 mm collet inserts



Model 51305

SPEED
18,000 RPM

POWER
0.5 hp (373 W)

COLLET
1/4" and 6 mm

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Collets Included	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
48325	79 dB(A)	23 (651)	1/4" & 6 mm	1/4" NPT	1/4 (6)	.9 (.4)	1.7 (44)	6.5 (166)
51305	74 dB(A)	26 (736)	1/4" & 6 mm	1/4" NPT	3/8 (10)	1.8 (.8)	9.25 (48)	1.8 (48)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



Lubrication
Page 69



Carbide Burrs
Page 99



Dynaswivel®
Page 58



Filter/Regulator/
Lubricator
Page 58

DYNABRADE NITRO SERIES™ 2" (51 MM) DIA. RIGHT ANGLE DISC SANDER

Ideal for quick weld removal, metal beveling in weld preparation, deburring and deflashing, surface conditioning and paint removal. Ergonomic tools accept locking-type abrasive discs (coated and non-woven nylon).

FEATURES

- ▶ Compact, lightweight contemporary tool design permits easy access to tight areas
- ▶ Thermoplastic rubber tool grip absorbs vibration and reduces cold air transmission
- ▶ Includes locking-type disc pad, 2" (51 mm) diameter (R-type pad)
- ▶ Smooth, efficient air motor
- ▶ Includes safety-lock lever; rear exhaust

DYNABRADE NITRO SERIES™ 3" (76 MM) DIA. RIGHT ANGLE DISC SANDER

Ideal for quick weld removal, metal beveling in weld preparation, deburring and deflashing, surface conditioning and paint removal. Ergonomic tools accept locking-type abrasive discs (coated and non-woven nylon).

FEATURES

- ▶ Compact, lightweight contemporary tool design permits easy access to tight areas
- ▶ Thermoplastic rubber tool grip absorbs vibration and reduces cold air transmission
- ▶ Includes locking-type disc pad, 3" (76 mm) diameter (R-type pad)
- ▶ Smooth, efficient air motor
- ▶ Includes safety-lock lever; rear exhaust

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Tool Thread	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
DS32	86 dB(A)	18 (510)	1/4" – 20	1/4" NPT	3/8 (10)	1.2 (.54)	2.5 (63)	6.8 (174)
DS53	84 dB(A)	26 (736)	1/4" – 20	1/4" NPT	3/8 (10)	1.6 (.73)	2.8 (71)	7.9 (200)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

2" (51 MM) NITRO WELD REMOVAL KIT

Model 22243

INCLUDES

DS32 NITRO 2" Disc Sander
94300 1/4" Composite Dynaswivel
73593 10 DynaFire Ceramic Locking Type Sanding Disc, 50mm, P36
73066 10 Cotton Fibre Deburring and Finishing Locking Type Disc, P36, MED
22001 Apron
Durable carrying case

3" (76 MM) NITRO WELD REMOVAL KIT

Model 22244

INCLUDES

DS53 NITRO 3" Disc Sander
94300 1 - 1/4" Composite Dynaswivel
73597 10 DynaFire Ceramic Locking Type Sanding Disc, 75mm, P36
73063 10 Cotton Fibre Deburring and Finishing Locking Type Disc, P36, MED
22001 Aprons
Durable carrying case



2" (51 MM) DIA. RIGHT ANGLE DISC SANDER

FEATURES

- ▶ Right Angle, Front Exhaust
- ▶ Wick-lube system extends gear life
- ▶ Governor-controlled motor maintains speed under load
- ▶ Includes 51348 Locking-Type Pad (2" (51 mm) diameter)

TECH TIP

Motor Tune-Up Kits will extend the life of an air tool when used with a preventative maintenance schedule.



Model 47821

SPEED
15,000 RPM

POWER
0.4 hp (298 W)

3" (76 MM) DIA. RIGHT ANGLE DISC SANDER

Ideal for quick weld removal, metal beveling in weld preparation, deburring and deflashing, surface conditioning and paint removal. Ergonomic tools accept locking-type abrasive discs (coated and non-woven nylon).

FEATURES

- ▶ Composite tool housing
- ▶ Thermal-insulated handle reduces cold air transmission to operator
- ▶ Wick-lube system extends gear life
- ▶ Safety-lock throttle lever prevents accidental startup of tool



Model 54400

SPEED
18,000 RPM

POWER
0.7 hp (522 W)

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Tool Thread	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
47821	85 dB(A)	25 (708)	1/4" NPT	1/4 (6)	1/4" – 20 Male	1.1 (.5)	3.5 (89)	4.4 (111)
54400	83 dB(A)	41 (1,161)	1/4" NPT	3/8 (10)	3/8" – 24 Male	2.3 (1)	3.5 (89)	8.5 (216)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

RELATED PRODUCTS



Lubrication
Page 69



Dynaswivel®
Page 58



General
Clean-up
Page 49

DYNABRADE NITRO SERIES™ NITROZIP SURFACE PREPARATION TOOL

Using a Dynabrade Nitro Series™ NitroZip equipped with a wire wheel allows technicians to remove rust and seam sealers in preparation for repair or replacement of damaged vehicle components. Sharp wire wheels cut quickly, and do not “load” with thick, gummy sealer. Wheels can be resharpened by reversing the direction of the wire rotation and running on a hard surface.

FEATURES

- ▶ Dynabrade Nitro Series™ NitroZip tool outperforms conventional spiral-wound wheels without clogging
- ▶ Excellent power for effectively removing seam sealer and paint
- ▶ Tool duplicates sand-blasting effect without surface fatigue
- ▶ Excellent for removing two-sided adhesive molding tape and decal material with use of rubber eraser wheel
- ▶ Eraser Wheel has serrations for improved cooling effect air flow. Also resists heat buildup and reduces jumping and vibration

TECH TIP

When using the Dynabrade Nitro Series™ NitroZip with a wire or eraser wheel apply gentle pressure to the work surface keeping the tool in motion for easy surface preparation and decal removal.



Model NZ1

SPEED

3,500 RPM

POWER

0.5 hp (373 W)

Wheel sold separately

BENEFITS



When equipped with a wire wheel the Dynabrade Nitro Series™ NitroZip removes seam sealer quickly and without clogging leaving the surface below ready for rework.



Using an eraser wheel the Dynabrade Nitro Series™ NitroZip quickly removes decals without harming the paint below, as well as removing adhesives without smearing on the painted surface.

DYNABRADE NITRO SERIES™
NITROZIP KIT

INCLUDES

- NZ1 Standard Tool
- 92252 1/2" Wheel Hub Assembly (1)
- 92248 1/2" Coarse Wire Wheel (1)
- 92239 3/4" Wheel Hub Assembly (1)
- 92245 3/4" Coarse Wire Wheel (1)
- 92255 RED-TRED® Zip Eraser Wheel (1)



Model NZ1K

SPEED
3,500 RPM

POWER
0.5 hp (373 W)

Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
--------------	-------------	-------------------------------	------------------	---------------------	-------------------	------------------	------------------


NZ1	83 dB(A)	28 (792)	1/4" NPT	3/8 (10)	2.6 (1.2)	4.4 (113)	11.7 (298)
-----	----------	----------	----------	----------	-----------	-----------	------------

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)


RELATED PRODUCTS




Coarse Wire Wheels
Page 61



Beige Eraser Wheel
Page 61



Hub
Page 61



Lubrication
Page 59



MULTI-PURPOSE TOOLS

Random orbital, orbital, and in-line sanders are used throughout the stages of vehicle repair and restoration from prep work in the body shop to finish work before buffing in the paint shop. The wide range of Dynabrade sanders offered for applications throughout the shop allow technicians to always have the right sander for the job. Cutting through layers of clear, paint and primer or leveling body filler can be performed faster and with

fewer abrasives when the tool and abrasive are matched to the size and severity of the application. Optimizing these applications can call for an aggressive 3/8" (10 mm) orbit palm sander or even a "Mudhog" (gear-driven sander) with a coarse grit abrasive to move vehicles more quickly to the paint booth.

Tools like the DynaLocke® provide technicians with a single tool capable of performing like a disc sander and a dual

action in multiple different tasks by switching between rotary and random orbital sanding action. Jitterbug, or power block, sanders are ideal when sanding corners or leveling large surface like a hood or roof top. Versatility within the shop is a critical component to optimizing a process for fast and repeatable results, and having the right tool or tools for the job can make all the difference.

DYNORBITAL® VERSATILITY



Feather Edging

When sanding to bare metal Dynabrade random orbital sanders can be operated at full throttle to remove surface defects as well as prepare deep dents. The random orbital can then be throttled back for feather-edging applications, providing technicians with greater control and helping prevent the removal of too much material in preparation for new paint.



Clear Coat Repair


Using a sequence of grits, the Dynorbital® Extreme quickly levels worn clear coat, a critical step to matching or re-establishing the finish or a repaired portion of a vehicle to the factory finish. Without a level surface prior to buffing or polishing the final finish can appear dull or faded rather than a high-gloss polish.



Headlight Repair

In addition to paint prep and clear coat repair Dynabrade random orbital sanders are often used to restore the clarity of headlight covers. After leveling the scratches and dings created by gravel and other debris impacting headlight covers, a palm-style buffer is used to apply the final finish.

DYNORBITAL-SPIRIT® RANDOM ORBITAL SANDER



COMPACT GRIP

Ergonomically designed to fit naturally in operator hands

RECESSED THROTTLE LEVER

Eliminates pressure point on operator's hand

COMFORT PLATFORM

Provides hand and wrist support

SPEED CONTROL

Adjust speed for sensitive substrates


WEIGHT-MATED PAD

Minimizes vibration

3" (76 mm) – 75 grams


5" (127 mm) – 100 grams

6" (152 mm) – 130 grams




**3/8" (10 mm)
DIAMETER ORBIT**

Aggressive Sanding
Orange Throttle Lever



**3/16" (5 mm)
DIAMETER ORBIT**

General Sanding
Gray Throttle Lever



**3/32" (2.5 mm)
DIAMETER ORBIT**

Ultra-Fine Sanding
Black Throttle Lever

BENEFITS




The Dynorbital-Spirit® is the lightest random orbital sander from Dynabrade and is ideal for vertical feather-edging applications where technicians are working in front of their body or at eye level with a vehicle raised on a lift. Weighing less than two pounds the Spirit sander reduces operator fatigue and relieves stress on wrists and arms. Improve shop air quality by combining with Dynabrade Mini-Raptor Vacs®.

MATERIAL REMOVAL APPLICATIONS

Dynorbital-Spirit® sanders with a 3/8" (10 mm) orbit make quick work of heavy material removal applications. The wide throw sands a greater surface area than general and fine finishing sanders.



**3/8" (10 mm)
DIAMETER ORBIT**
Aggressive Sanding
Orange Throttle Lever



NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59100	3 (76)	Hook-face	81 dBA	1.6 (.7)	7 (178)
59005	5 (127)	Hook-face	81 dBA	1.5 (.7)	6.5 (165)
59010	6 (152)	Hook-face	82 dBA	1.6 (.7)	7 (178)
59178	6 (152)	Hook-face	82 dBA	1.6 (.7)	7 (178)

SELF-GENERATED VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59103	3 (76)	Hook-face	84 dBA	1.5 (.7)	8.5 (216)
59008	5 (127)	Hook-face	82 dBA	1.6 (.7)	8.5 (216)
59013	6 (152)	Hook-face	85 dBA	1.7 (.7)	9 (229)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59104	3 (76)	Hook-face	79 dBA	1.5 (.7)	7 (178)
59009	5 (127)	Hook-face	83 dBA	1.5 (.7)	7.25 (184)
59014	6 (152)	Hook-face	84 dBA	1.6 (.7)	7.75 (197)
59181	6 (152)	Hook-face	83 dBA	1.6 (.7)	7.75 (197)

Additional Specifications:

Pad Thread 5/16"-24 Male • Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6 mm)
Air Flow Rate 14 SCFM (396 L/PM) • Height 3-1/2" (89 mm) • Air Pressure 90 PSIG (6.2 Bar)
Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744



SPEED
12,000 RPM

POWER
0.25 hp (186 W)

**TECH
TIP**

For a swirl-free finish, always start the sander on the work surface and stop the sander off the surface.

RELATED PRODUCTS



Sanding Pads
Page 62



Coated Abrasives
Discs
Page 78



Swivel Adaptor
Page 58




Raptor Vac®
Vacuum
Systems
Page 48

GENERAL SANDING

Dynorbital-Spirit® sanders with a 3/16" (5 mm) orbit are an excellent choice for general purpose sanding, able to remove material and feather-edge surfaces when combined with a wide range of abrasive grits.



**3/16" (5 mm)
DIAMETER ORBIT**
General Sanding
Gray Throttle Lever



NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59105	3 (76)	Hook-face	79 dBA	1.4 (.6)	6.5 (165)
59020	5 (127)	Hook-face	80 dBA	1.4 (.6)	6.5 (165)
59025	6 (152)	Hook-face	81 dBA	1.5 (.7)	7 (178)
59179	6 (152)	Hook-face	81 dBA	1.5 (.7)	7 (178)

SELF-GENERATED VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59108	3 (76)	Hook-face	83 dBA	1.4 (.6)	8.5 (216)
59023	5 (127)	Hook-face	82 dBA	1.5 (.7)	8.5 (216)
59028	6 (152)	Hook-face	85 dBA	1.6 (.7)	9 (229)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59109	3 (76)	Hook-face	83 dBA	1.4 (.6)	7.25 (184)
59024	5 (127)	Hook-face	81 dBA	1.5 (.6)	7.25 (184)
59029	6 (152)	Hook-face	83 dBA	1.6 (.7)	7.75 (197)
59182	6 (152)	Hook-face	82 dBA	1.6 (.7)	7.75 (197)

Additional Specifications:

Pad Thread 5/16"-24 Male • Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6 mm)
Air Flow Rate 14 SCFM (396 L/PM) • Height 3-1/2" (89 mm) • Air Pressure 90 PSIG (6.2 Bar)
Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744



SPEED

12,000 RPM

POWER

0.25 hp (186 W)



See Page 62

DynaMaze® Vacuum Pad


- Exclusive mesh design accepts all abrasive types and hole configurations.
- Efficient, hook-face technology.
- Increased vacuum capability promotes operator safety.
- Reduced vibration for operator comfort.
- Unique single-piece hub design ensures tool balance and further reduces vibration.

ULTRA-FINE SANDING

Dynorbital-Spirit® sanders with a 3/32" (2.5 mm) orbit are best utilized in fine finishing and surface repair applications. Delicate enough to level clear coats in preparation for buffing and final finishing.



**3/32" (2.5 mm)
DIAMETER ORBIT**
Ultra-Fine Sanding
Black Throttle Lever



NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59110	3 (76)	Hook-face	81 dBA	1.3 (.6)	7 (178)
59035	5 (127)	Hook-face	81 dBA	1.4 (.6)	6.5 (165)
59040	6 (152)	Hook-face	82 dBA	1.6 (.7)	7 (178)
59180	6 (152)	Hook-face	80 dBA	1.5 (.7)	7 (178)

SELF-GENERATED VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59113	3 (76)	Hook-face	85 dBA	1.4 (.6)	9 (229)
59038	5 (127)	Hook-face	81 dBA	1.5 (.7)	8.5 (216)
59043	6 (152)	Hook-face	86 dBA	1.5 (.7)	9 (229)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Style	Sound Level	Weight Pound (kg)	Length Inch (mm)
59114	3 (76)	Hook-face	84 dBA	1.4 (.6)	7.75 (197)
59039	5 (127)	Hook-face	83 dBA	1.4 (.6)	7.75 (184)
59044	6 (152)	Hook-face	80 dBA	1.5 (.7)	7.75 (197)
59183	6 (152)	Hook-face	81 dBA	1.5 (.7)	7.75 (197)

Additional Specifications:

Pad Thread 5/16"-24 Male • Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6 mm)
Air Flow Rate 14 SCFM (396 L/PM) • Height 3-1/2" (89 mm) • Air Pressure 90 PSIG (6.2 Bar)
Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744



SPEED

12,000 RPM


POWER

0.25 hp (186 W)

RELATED PRODUCTS



Sanding Pads
Page 62



Coated Abrasives
Discs
Page 78



Coupler and
Plug Assembly
Page 59



Raptor Vac®
Vacuum
Systems
Page 48

DYNORBITAL® EXTREME RANDOM ORBITAL SANDER SERIES

Dynabrade proudly introduces our most refined random orbital sander to date. The Dynorbital® Extreme boasts the greatest power and most consistent speed of any palm-style orbital sander. Power and speed combine to quickly and reliably produce the desired finish, while ergonomic features keep operators safe and comfortable throughout their day. Symmetrical design allows left or right-handed operators to work comfortably, while the compact size of the Dynorbital® Extreme fits naturally in most operator's hands.

FEATURES


- ▶ Recessed throttle lever
- ▶ Integrated comfort platform
- ▶ Comfort grip
- ▶ Lip Seal Shroud
- ▶ Weight-Mated Sanding Pad
- ▶ Integrated Swivel Cuff
- ▶ Increased Port Size

**TECH
TIP**

For a swirl-free finish, always start the sander on the work surface and stop the sander off the surface.




Model X61 VHS



**3/16" (5 mm)
DIAMETER ORBIT**

General Sanding
Teal Throttle Lever



**3/32" (2.5 mm)
DIAMETER ORBIT**

Ultra-Fine Sanding
Black Throttle Lever

BENEFITS



Extreme Power

New motor design has the highest power-to-weight ratio in the industry, with 0.3 hp at 1.8 lbs. Most consistent speed under load in industry, running at 92% of rated tool speed. New rotor design enhances power with less friction.



Extreme Comfort

Ergonomic design with integrated comfort platform for more wrist support and overall operator comfort. Soft grip co-molded to rigid composite base housing for maximum comfort and durability. Recessed throttle lever eliminates pinch and pressure points on an operator's palm.



Extreme Performance

Achieve consistent, superior finishes in less time. Premium sanding pad is weight-mated for the lowest vibration levels. Made from the highest quality materials for extreme durability and longevity.

NON-VACUUM

Model Number	Diameter Inch (mm)	Pad Type	Orbit Dia. Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)
X51	5 (127)	Hook-face	3/16 (5)	74 dBA	1.78 (0.8)	6.9 (176)
X51H	5 (127)	Hook-Face	3/16 (5)	73 dBA	1.78 (0.8)	6.9 (176)
X52	5 (127)	Hook-face	3/32 (2.5)	73 dBA	1.74 (0.8)	6.9 (176)
X52H	5 (127)	Hook-Face	3/32 (2.5)	72 dBA	1.74 (0.8)	6.9 (176)
X61	6 (152)	Hook-face	3/16 (5)	72 dBA	1.86 (0.8)	7.4 (188)
X61H	6 (152)	Hook-Face	3/16 (5)	78 dBA	1.86 (0.8)	7.4 (188)
X62	6 (152)	Hook-face	3/32 (2.5)	73 dBA	1.82 (0.8)	7.4 (188)
X62H	6 (152)	Hook-Face	3/32 (2.5)	75 dBA	1.82 (0.8)	7.4 (188)

CENTRAL VACUUM

Model Number	Diameter Inch (mm)	Pad Type	Orbit Dia. Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)
X51V	5 (127)	Hook-Face	3/16 (5)	74 dBA	1.94 (0.9)	9.1 (230)
X52V	5 (127)	Hook-Face	3/32 (2.5)	74 dBA	1.9 (0.9)	9.1 (230)
X61V	6 (152)	Hook-Face	3/16 (5)	73 dBA	2.02 (0.9)	9.5 (242)
X62V	6 (152)	Hook-Face	3/32 (2.5)	73 dBA	1.98 (0.9)	9.5 (242)

SPEED CONTROL SERIES - FOR VARIABLE SPEED

Model Number	Diameter Inch (mm)	Pad Type	Orbit Dia. Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)
X51VHS	5 (127)	Hook-Face	3/16 (5)	74 dBA	2.04 (0.94)	9.1 (230)
X51HS	5 (127)	Hook-Face	3/16 (5)	73 dBA	1.88 (0.85)	6.5 (165)
X61VHS	6 (152)	Hook-Face	3/16 (5)	73 dBA	2.12 (0.96)	9.5 (242)
X61HS	6 (152)	Hook-Face	3/16 (5)	75 dBA	1.96 (0.89)	7.4 (188)

Additional Specifications:

Height: 3.7" (95 mm) • Air Inlet: 1/4" NPT • Air Hose I.D.: 1/4" (6 mm) • Air Pressure: 90 PSIG (6.2 Bar)
Maximum Air Flow: 19 SCFM (538 L/PM)



SPEED
12,000 RPM

POWER
0.3 hp (224 W)



TECH TIP

Adding flow control airline connector 95756 allows technicians to "dial in" the speed of the Dynorbital® Extreme for each application.

RELATED PRODUCTS



Sanding Pads
Page 62



Coated Abrasives
Discs
Page 78



Speed Control
Page 58




M Class
Vacuum
System
Page 52

TWO-HAND ROS SANDER

With nearly twice the power of a traditional palm-style random orbital sander two-hand sanders efficiently power larger diameter discs and abrasives. The added handle and throttle lever provide technician with greater control especially when working on vertical sides of a vehicle.

FEATURES


- 5" (125 mm) and 6" (150 mm) models are 12,000 RPM. Pads have 5/16"-24 male thread
- 8" (200 mm) models are 10,000 RPM. Pads mount with 5 screws
- Central Vacuum models include combination lip seal/overskirt shroud, which offers enhanced vacuum capability



**3/8" (10 mm)
DIAMETER ORBIT**
Aggressive Sanding

Model Number	Vacuum Type	Diameter Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
58415	Non-Vacuum	5 (127)	82 dBA	2.5 (1.2)	11 (280)	4.94 (126)
58419	Non-Vacuum	6 (152)	84 dBA	2.5 (1.2)	11.37 (288)	4.94 (126)
58420	Central Vacuum	5 (127)	81 dBA	2.7 (1.2)	11.37 (288)	4.94 (126)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG



**3/16" (5 mm)
DIAMETER ORBIT**
General Sanding

Model Number	Vacuum Type	Diameter Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
58400	Non-Vacuum	5 (127)	82 dBA	2.5 (1.2)	11 (280)	4.93 (126)
58405	Non-Vacuum	6 (152)	81 dBA	2.6 (1.2)	11.37 (288)	4.93 (126)
58410	Non-Vacuum	8 (203)	82 dBA	4.0 (1.8)	12.5 (319)	5.62 (142)
58409	Central Vacuum	6 (152)	84 dBA	2.7 (1.2)	11.37 (288)	4.93 (126)
58414	Central Vacuum	8 (203)	85 dBA	4.2 (1.9)	12.5 (319)	5.62 (142)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 23 SCFM / 651 L/Min



Model 58405

SPEED

12,000 RPM

POWER

0.45 hp (336 W)

DIAMETER

5" (125 mm), 6" (150 mm)



Model 58414

SPEED

**8" Models 10,000 RPM
5", 6" Models 12,000 RPM**

POWER

0.45 hp (336 W)

DIAMETER


**5" (125 mm), 6" (150 mm),
8" (200 mm)**

GEAR-DRIVEN SANDER

Gear-Driven Sanders or "Mudhog" sanders are utilized for quick, aggressive removal and leveling of body filler, glues and coatings. These slow-speed, high-torque sanders have an epicycloidal motion that typically combines with coarse grit abrasives to optimize preparation stages allowing operators to spend less time sanding.

FEATURES

- Ergonomically designed for low vibration and reduced sound levels
- Speed control lever is conveniently located for easy thumb adjustment
- Insulated tool housing reduces cold air transmission to the hand



**EPICYCLOIDAL
MOTION**

Aggressive Sanding

Model Number	Diameter Inch (mm)	Vacuum Type	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
58442	6 (152)	Non-Vacuum	3/8 (10)	3.6 (1.7)	5.62 (143)	11.5 (293)
58443	6 (152)	Central	3/8 (10)	3.8 (1.7)	5.62 (143)	11.5 (293)
58445	8 (203)	Non-Vacuum	3/8 (10)	3.9 (1.8)	5.56 (142)	12.5 (293)
58446	8 (203)	Central	3/8 (10)	4.3 (2.0)	5.56 (142)	12.5 (319)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 23 SCFM / 651 (L/Min)



Model 58442

SPEED

900 RPM

POWER

0.45 hp (336 W)

DIAMETER

6" (150 mm), 8" (200 mm)



Model 58443

RELATED PRODUCTS



Sanding Pads
Page 62



A/O Film
and Paper
Discs
Page 72



Optional
Vacuum Hose
Assembly
Page 66




M Class
Vacuum
System
Page 52

DYNALOCKE®

The DynaLocke® is truly “two tools in one,” easily changing from a rotary Disc Sander to Random Orbital Sander with a turn of the dial. Repair technicians can increase their productivity by accomplishing paint stripping and feather edging applications with one tool.


FEATURES

- ▶ Switch is recessed within tool grip for comfort and to prevent accidental engaging
- ▶ Speed control lever is conveniently located for easy thumb adjustment
- ▶ Insulated tool housing reduces cold air transmission to the hand



ROTARY MOTION

Stripping and Blending



3/16" (5 mm)
DIAMETER ORBIT
General Sanding

Model Number	Diameter Inch (mm)	Sound Level	Maximum Air Flow SCFM (L/Min)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
58460	3 (76)	81 dB(A)	23 (651)	2.35 (1.0)	5.37 (137)	10.31 (263)
58461	3 (76)	86 dB(A)	23 (651)	2.35 (1.0)	5.37 (137)	10.31 (263)
58430	5 (127)	82 dB(A)	23 (651)	2.7 (1.2)	5.12 (131)	11 (280)
58435	6 (152)	82 dB(A)	23 (651)	2.8 (1.2)	5.12 (131)	11 (280)
58436	6 (152)	85 dB(A)	23 (651)	2.7 (1.2)	5.12 (131)	11 (280)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 23 SCFM (651 L/Min) • Tool Thread 5/16" - 24 Female



Model 58436

SPEED

12,000 RPM

POWER

0.45 hp (336 W)

DIAMETER

3" (75 mm), 5" (125 mm),
6" (150 mm)

TECH TIP

Tool should be completely stopped before changing sanding action.

BENEFITS





The DynaLocke® quickly strips paint to bare metal when set to rotary mode and converts to random orbital to complete the feather-edging portion of the application.

DYNABUG® “MODEL T” SANDER

"Model T" sanders are incredibly lightweight, fine-finishing sanders that require very little air flow to reach peak performance, making them ideal for shops without large compressors. Square or circular pads available in several sizes combine with 3/32" orbit provide technicians with a versatile finishing orbital sander.

FEATURES

- ▶ Lightweight... only 1 lb.! Palm-style, ergonomic design features low profile grip for greater operator comfort and control
- ▶ Operates 9 SCFM at 90 PSIG. Can be run by as little as 3 horsepower compressor



ORBITAL MOTION

Featheredge, Finish,
Sand and Blend

Model Number	Pad Size Inch	Pad Diameter Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57920	4 x 4.31	—	68 dB(A)	1 (.5)	5 (127)	3 (76)
57922	—	5 (127)	68 dB(A)	1 (.5)	5.5 (140)	3 (76)
57923	4.25 x 4.5	—	68 dB(A)	1 (.5)	5.5 (140)	3 (76)
57924	—	5 (127)	68 dB(A)	1 (.5)	5.5 (140)	3 (76)
57926	—	6 (152)	68 dB(A)	1 (.5)	5 (127)	3 (76)
57927	—	6 (152)	68 dB(A)	1 (.5)	5 (127)	3 (76)
57929	4.25 x 4.5	—	73 dB(A)	1 (.5)	5 (127)	3 (76)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 9 SCFM / 255 L/Min

WET DYNABUG® “MODEL T” SANDER

Model Number	Pad Diameter Inch (mm)	Sound Level	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57908	5 (127)	76 dBA	1.5 (0.7)	8 (203)	4 (102)
57909	5 (127)	76 dBA	1.5 (0.7)	8 (203)	4 (102)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 17 SCFM / 481 L/Min

RELATED PRODUCTS



Coupler and
Plug Assembly
Page 59



General
Clean-up
Page 51

Model 57920



SPEED

20,000 RPM

TURBINE-STYLE

Turbine-style, vaneless air motor needs no oil making "Model T" perfect for areas where sensitive finishes are being produced.

**TECH
TIP**

Model 57909



SPEED

20,000 RPM

TURBINE-STYLE

DYNABUG® II SANDER

Compact and lightweight, Dynabug® II Orbital Sanders access tight areas while limiting operator fatigue – especially when sanding on vertical surfaces. Dynabug® II tools are ideal for feathering applications where creating surfaces with excellent mechanical adhesion qualities is critical in preparation for painting and final finish.

FEATURES

- Designed to be light weight, ergonomic with a comfort platform to provide additional hand and wrist support



ORBITAL MOTION

General Sanding

Model Number	Pad Size Inch (mm)	Pad Type	Vacuum Type	Orbit	Sound Level	Weight Pound (kg)	Length Inch (mm)
58500	3 x 4-1/4 (76 x 108)	Hook-face	Non-Vacuum	3/32" (2.5 mm)	78 dBA	1.7 (.78)	6.8 (171)
58503	3-1/4 x 5 (82 x 127)	Hook-face	Non-Vacuum	3/32" (2.5 mm)	78 dBA	1.7 (.78)	7.2 (182)
58507	2-2/3 x 6 7/8 (68 x 175)	Hook-face	Non-Vacuum	3/32" (2.5 mm)	82 dBA	2.2 (.98)	8 (283)
58510	3 x 4 (76 x 102)	Hook-face	Non-Vacuum	3/32" (2.5 mm)	84 dBA	1.7 (.78)	6.5 (171)
58511	2-2/3 x 6 7/8 (68 x 175)	Hook-face	Non-Vacuum	3/32" (2.5 mm)	84 dBA	1.8 (.82)	8 (203)
58516	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Non-Vacuum	3/32" (2.5 mm)	83 dBA	1.8 (.82)	8.5 (215)
58502	3 x 4-1/4 (76 x 108)	Hook-face	Central	3/32" (2.5 mm)	83 dBA	1.8 (.82)	7 (179)
58505	3-1/4 x 5 (82 x 127)	Hook-face	Central	3/32" (2.5 mm)	81 dBA	1.8 (.82)	7.5 (190)
58512	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Central	3/32" (2.5 mm)	84 dBA	1.9 (.86)	8.75 (222)
58513	2-2/3 x 6-7/8 (68 x 175)	Hook-face	Non-Vacuum	3/16" (5 mm)	81 dBA	1.9 (.86)	8.1 (206)
58514	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Non-Vacuum	3/16" (5 mm)	81 dBA	1.9 (.86)	8.6 (218)
58515	2-2/3 x 7-3/4 (68 x 196)	Hook-face	Central	3/16" (5 mm)	80 dBA	2.0 (.91)	8.9 (226)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6) • Air Pressure 90 PSIG
Maximum Air Flow 13 SCFM (368 L/Min) • Height 3.7" (94 mm)



Model 58516

SPEED

3/16" (5 mm) Models
8,000 RPM

3/32" (2.5 mm) Models
10,000 RPM

POWER

0.11 hp (82 W)



Model 58502

BENEFITS



Dynabug® sanders are an ideal choice for use in feather edging applications. The square pad and delicate orbital motion allow technicians to sand in corners without undercutting. When equipped with a long-nap pad and non-woven nylon abrasives Dynabug® and Dynabug®II sanders are excellent scuffing and blending tools.

DYNABUG® SANDER

Dynabug® orbital sanders are available in two separate orbit patterns - 3/16" or 3/32" - and are recommended for general sanding of horizontal surfaces or for fine sanding and feathering. Being slightly larger and heavier than the Dynabug® II relieves operators of having to apply heavy downward force when leveling a surface in preparation for paint and finishing.

FEATURES

- Dynabug® sanders can be equipped with a long-nap pad (57852) used with non-woven nylon abrasives for scuffing applications



ORBITAL MOTION


For General Sanding

Model Number	Vacuum Type	Orbit	Speed RPM	Sound Level	Weight Pound (kg)	Length Inch (mm)
57800	Non-Vacuum	3/16" (5 mm)	8,000	82 dBA	2.5 (1.2)	11 (280)
57804	Central	3/16" (5 mm)	8,000	81 dBA	2.5 (1.2)	11.37 (288)
57810	Non-Vacuum	3/32" (2.5 mm)	10,000	84 dBA	2.5 (1.2)	11 (280)
57814	Central	3/32" (2.5 mm)	10,000	84 dBA	2.5 (1.2)	11.37 (280)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Height 4.93" 126 mm • Maximum Air Flow 16 SCFM / 453 L/Min

LONG BOARD SANDER

Two-hand control for blocking applications and for use in vertical applications.



ORBITAL MOTION

For General Sanding

Model Number	Pad Size Inch (mm)	Orbit	Sound Level	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
58551	4" x 16" (100 x 400)	3/16" (5 mm)	85 dBA	5.8 (2.6)	11 (280)	4.93 (126)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG (6.2 BAR)
Maximum Air Flow 23 SCFM / 651 L/Min

RELATED PRODUCTS



Sanding Pads
Page 65



Vacuum Hose
Assembly
Page 66



General
Clean-up
Page 51



Model 57800

SPEED

8,000 RPM

POWER

0.24 hp (179 W)



Model 57814

SPEED

10,000 RPM

POWER

0.28 hp (209 W)



Model 58551

SPEED

10,000 RPM

POWER

0.5 hp (373 W)




Maximum
90 PSIG (6.2 BAR)

DYNALINE SANDER

In-Line Sanders are ideal for leveling filler or blocking using adhesive backed coated and non-woven abrasives. Use long nap, hook-face pad number 57582 with model 57400 with non-woven abrasives for scuffing and blending.

FEATURES

- Uses adhesive-backed coated and non-woven nylon sheets and rolls
- Quality constructed pad is weight-mated to tool for low vibration, smooth operation and superior finishes
- Comfort platform provides additional hand and wrist support
- 2,400 strokes per minute at 90 PSIG (6.2 Bar)



IN-LINE MOTION

For Stripping
and Blending

Model Number	Vacuum Type	Sound Level	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57400	Non-Vacuum	79 dBA	2.6 (1.2)	7 (178)	3.75 (95)
57404	Central Vacuum	84 dBA	2.6 (1.2)	7 (178)	3.75 (95)
51350	Non-Vacuum	81 dBA	3.1 (1.4)	11 (279)	3.75 (95)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (6) • Air Pressure 90 PSIG
Maximum Air Flow 18 SCFM (510 L/Min)



Model 57400

SPEED

2,400 RPM

POWER

0.3 hp (186 W)



Model 51350

TECH TIP

Sanding Pad can be rotated 360° for adjusting to most efficient position per application.




BENEFITS



The in-line sanding motion of a Dynaline sander provides technicians with a powered option for completing traditional hand blocking applications. When used with non-woven abrasives Dynaline sanders are a great option for scuffing and surface preparation applications.

“After 60 plus years in the auto repair world, the oldest saying still rings true! 'Time is Money'. In early times most tasks were done by hand. The right power tool did not exist! For Professional Grade Tooling and Equipment you can't do better than Dynabrade. Engineered to perform and last!” ~Jon Kosmoski, still at it since 1956

Jon Kosmoski
Kosmoski Specialty Company
Minneapolis, MN





PAINT SHOP

Dynabrade tools and accessories in the paint shop are manufactured to create consistent, high-gloss finishes in the fewest steps possible. Buffers and polishers in a wide variety of sizes and formats provide

technicians with options to finish large areas like hoods and trunk lids as well as small and hard to reach areas like headlights, side view mirrors, and even navigate around motorcycle frames to polish fuel tanks. Air and electric

powered buffing and polishing tools utilizing wool, foam, or terry cloth bonnets are available to technicians so that each application can be optimized for the desired cut rate leading to an optimal finish.

SUPERIOR FINISHES IN THE PAINT SHOP




Dynabrade offers small diameter buffers for use on headlights and small areas where other buffers cannot reach or maneuver around. Pictured here is a Sander/Buffer combination tool that allows technicians to toggle between rotary and random orbital motions with the flip of a switch. Providing versatile tools that can accomplish multiple tasks is one way Dynabrade helps maximize productivity.



When establishing a final finish, it is important to apply compound to the surface of the pad and then blot additional compound on the area to be polished. Because of the self-diminishing abrasive technology in Dynabrade compounds it is critical to have fresh compound throughout the area to be polished, adhering to this step will ensure even and consistent results.



The Dynabrade finishing system consisting of buffers, pads and compounds can be seen here achieving a high-gloss, showroom finish on a dark painted front quarter panel. The buffer is easily controlled having two grip points, while the buffing pad conforms to the contours of the vehicle creating a consistent finish.



PALM-STYLE ROTARY BUFFERS


Ideal for buffing door/window columns and posts, plus recessed areas and contoured surfaces. Best for repair of sanding scratches in clear coat.

FEATURES

- Low profile housing
- Adjustable speed regulator

INCLUDES

50125 rigid 3" backing pad
90027 Terry Cloth Pad
90028 Wool Pad



ROTARY MOTION

For Rotary Polishing

Model 57550



DIAMETER
3" (76 mm)

SPEED
2,400 RPM


POWER
0.25 hp (186 W)

TECH TIP

Use Dynabrade DynaRed® and DynaOrange® to achieve a superior high gloss finish after compounding.

PALM-STYLE MINI-DYNORBITAL®

- Ideal for repairing dust nibs and minor surface defects
- Convenient, non-marring hanger bracket for easy tool storage
- Includes 1-1/4" dia. locking-type Sanding Pad



**3/16" (5 mm)
DIAMETER ORBIT**

For Sanding and Polishing

Model 69502



DIAMETER
1-1/4" (32 mm)

SPEED
2,400 RPM

POWER
0.25 hp (186 W)


Model Number	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Tool Thread	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
57550	79 dB(A)	18 (510)	1/4 (6)	1/4"-20 Male	1.9 (.9)	4.25 (108)	5.37 (137)
69502	75 dB(A)	6 (170)	1/4 (6)	Locking	1.3 (.6)	3.31 (84)	6 (152)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG (6.2 Bar)

3" (76 MM) DIAMETER SANDER/BUFFER


FEATURES

- Dual-purpose tool offers random orbital sanding and rotary buffing
- Repairs dust nibs and blemishes in paints and clear coats
- Also used to repair hazy/cloudy headlights, and other clear/colored acrylic surfaces
- 3" (76 mm) diameter allows use on contoured surfaces and tight areas
- In rotary mode, offers all the benefits of model 69550



ROTARY MOTION

For Rotary
Polishing



3/16" (5 mm) DIAMETER ORBIT

For Sanding and Polishing

3" (76 MM) DIAMETER BUFFER

Ideal for buffing door/window columns and posts, plus recessed areas and contoured surfaces. Best for repair of sanding scratches on clear coat.

FEATURES

- Accepts 3" (76 mm) wool and foam buff pads
- Runs at 12,000 RPM free-speed, then slows to under 4,000 RPM in use
- Lightweight, palm-style design offers great comfort and control.
- Adjustable speed regulator included



Model 69540

DIAMETER
3" (76 mm)

SPEED
12,000 RPM

POWER
0.2 hp (186 W)



Model 69550

Model Number	Sound Level Sanding	Sound Level Buffing	Maximum Air Flow SCFM (L/Min)	Air Inlet Thread	Hose I.D. Size Inch (mm)	Air Pressure PSIG (Bar)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
69540	71 dB(A)	74 dB(A)	12 (334)	1/4" NPT	1/4 (6)	90 (6.2)	1.5 (.67)	3.7 (94)	6.1 (154)
69550	N/A	74 dB(A)	12 (334)	1/4" NPT	1/4 (6)	90 (6.2)	1.5 (.67)	2.6 (70)	6.1 (154)

RELATED PRODUCTS



Polishing Pads
& Foams
Page 103




Polishing
Compounds
Page 100

DYNABRADE NITRO SERIES™ 3" (76 MM) EXTENDED BUFFER

Compact and lightweight the Dynabrade Nitro Series™ extended buffer is perfect for use in tight areas or contoured painted surfaces like side-view mirrors.

FEATURES

- ▶ Tool includes 50126 Hook-Face Backup Pad
- ▶ Tactile, thermoplastic grip
- ▶ 3/8"-24 male spindle, rear exhaust
- ▶ Rotational rear exhaust directs cold air away from operator



ROTARY MOTION
For Rotary Buffering



Model EB3

DIAMETER
3" (76 mm)

SPEED
2,700 RPM

POWER
0.5 hp (373 W)

Model Number	Sound Level	Spindle Thread	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
EB3	81 dB(A)	3/8" - 24 male	23 (644)	3/8 (10)	1.6 (.72)	1.9 (49)	11.25 (286)


Additional Specifications: Air Inlet Thread 1/4" NPT • Air Pressure 90 PSIG (6.2 Bar)

DYNABRADE NITRO SERIES™ 5" (125 MM) - 8" (203 MM) BUFFER

Dynabrade Nitro Series™ buffers polish large areas like hoods and trunk lids quickly and with consistent results.

FEATURES

- ▶ 2,800 RPM free speed. Accepts 5" to 8" diameter buffs
- ▶ Lightweight and compact in size
- ▶ Rear exhaust, variable speed safety-lock lever throttle
- ▶ Soft-grip handle can be positioned for right or left hand operation
- ▶ Insulated handle reduces cold air transmission to the operator
- * Back-up pad (50853) and polishing bonnet (90082) not included



ROTARY MOTION
For Rotary Buffering



Model RB1

DIAMETER
5"- 8" (125 mm - 203 mm)

SPEED
2,800 RPM

POWER
1 hp (746 W)

Model Number	Pad Size Inch (mm)	Sound Level	Spindle Thread	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
RB1	8 (203)	89 dB(A)	5/8" - 11 Male	48 (1359)	3/8 (10)	4.8 (122)	12.5 (318)	2.5 (64)
RB2	8 (203)	89 dB(A)	M14	48 (1359)	3/8 (10)	4.8 (122)	12.5 (318)	2.5 (64)

Additional Specifications: Air Inlet Thread 3/8" NPT • Hose I.D. Size 3/8" • Air Pressure 90 PSIG (6.2 Bar)

3" (76 MM) DIAMETER BUFFER


Compact and lightweight with a specially engineered ergonomic, co-molded housing that fits naturally in and insulates a technicians hands from cold air transfer.

FEATURES

- Tool comes mounted with 54021 Adapter (1/4"-20 male thread)
- Governor-controlled motor maintains speed under load
- Extended rear exhaust muffler, safety-lock lever, rotary action

INCLUDES

50120 3" diameter Hook-Face Pad
90027 Terry Cloth Bonnet
90028 Wool Buffering Bonnet



ROTARY MOTION
For Rotary Buffing

Model Number	Sound Level	Tool Thread	Maximum Air Flow SCFM (L/Min)	Hose Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
49440	79 dB(A)	1/4" - 28 Female	26 (736)	1/4 (6)	1.9 (.9)	2.6 (67)	13 (331)

Additional Specifications: Air Inlet Thread 3/8" NPT • Air Pressure 90 PSIG (6.2 Bar)



Model 49440

DIAMETER
3" (76 mm)

SPEED
3,200 RPM


POWER
0.4 hp (298 W)

6" (152 MM) - 8" (203 MM) DIAMETER BUFFER

Dynabrade buffers that utilize planetary gear sets have been specifically designed for demanding, high-torque applications covering large areas like on commercial trucks, busses and delivery vehicles.

FEATURES

- Planetary gear set is easily lubricated for extended tool life
- Safety-lock throttle and soft-grip handle both adjust for left or right hand use



ROTARY MOTION
For Rotary Buffing

Model Number	Sound Level	Tool Thread	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
51392	78 dB(A)	5/8" - 11 Male	41 (1,167)	3/8 (10)	4.5 (2.1)	3.75 (95)	13.25 (333)

Additional Specifications: Air Inlet Thread 3/8" NPT • Air Pressure 90 PSIG (6.2 Bar)



Model 51392

DIAMETER
6" - 8" (152 mm - 203 mm)

SPEED
2,800 RPM

POWER
1 hp (744 W)

RELATED PRODUCTS



Polishing Pads & Foams
Page 103



Polishing Compounds
Page 100

DYNABRADE NITRO SERIES™ ELECTRIC ROTARY POLISHER

The NITRO Rotary Polisher is a very powerful 1450W / 2500 RPM polisher with spindle thread M14x2 has ergonomic features and is designed for pad diameters up to 8" (200 mm). The tool has an electronic variable speed dial for RPM's between 500- 2100 RPM and has a thermal overload protection. The 7 meters Long power cable gives the user a huge workspace freedom.

FEATURES

- ▶ Variable speed dial easily adjusts from 500-2100 rpm while in use
- ▶ Top-quality brushes are externally accessible
- ▶ Flexible and oil resistant 7 meters electric cord provides added manoeuvrability throughout the shop
- ▶ Soft start trigger with Lock-ON button




Model 51592

DIAMETER

6" - 8" (152 mm - 203 mm)

SPEED

2,500 RPM



ROTARY MOTION

For Rotary Polishing

Model Number	Pad Diameter	Maximum Watts Out	Spindle Thread	Voltage EU Plug	Phase	Frequency	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
51590	152 mm	1200	M14 x 2	220-240 V	1	50-60 Hz	4.1 (2.1)	7.75 (197)	15.5 (394)
51592	203 mm	1450	M14 x 2	220-240 V	1	50-60 Hz	5.1 (2.3)	7.75 (197)	15.5 (394)

2-STEP KIT 3" (76 MM) DYNABUFFER WITH DYNARED

Model 22820

INCLUDES

- 57126 3" (76 mm) Dia. Dynabuffer Random Orbital Polisher
- 58037A 1/4" (32 mm) Diam. Mini Orbital Sander
- 74000 2 Black Conical Polishing Foam 87mm 1 Hole
- 74001 2 Blue Conical Polishing Foam 87mm 1 Hole
- 22770 Dynabrade PSA Denibbing Discs P3000 (100 pcs/tube)
- 22017 1L DynaRed Polish Compound
- 22050 4 Microfibre Wipes Orange
- 22001 Apron
- Durable carrying case



22820

2-STEP KIT 5" (125 MM) DYNABUFFER WITH DYNARED

Model 22821

INCLUDES

- 58455 5" (127 mm) Dia. Dynabuffer Random Orbital Polisher
- 58037A 1-1/4" (32 mm) Diam. Mini Orbital Sander
- 74009 2 Black Conical Polishing Foam 138mm 1 Hole
- 74010 2 Blue Conical Polishing Foam 138mm 1 Hole
- 22770 Dynabrade PSA Denibbing Discs P3000 (100 pcs/tube)
- 22017 1L DynaRed Polish Compound
- 22050 4 Microfibre Wipes Orange
- 22001 Apron
- Durable carrying case



22821

DENIBBING AND POLISHING KIT

Model 22822

INCLUDES

- 69502 Mini-Dynorbital Silver 7500rpm
- 58455 5" (127 mm) Dia. Dynabuffer Random Orbital Polisher
- 73502 Microfiber Polishing Pad 135mm
- 74012 Grey Conical Polishing Foam 138mm 1 Hole
- 74010 Black Conical Polishing Foam 138mm 1 Hole
- 22770 Dynabrade PSA Denibbing Disc P3000 (100 pcs/tube)
- 22017 1L DynaRed Polish Compound
- 22021 1L DynaOrange Polish Compound
- 22050 2 Microfibre Wipes Orange
- 22045 Spray Bottle
- 22048 Spray Trigger
- Durable carrying case



22822

NITRO ELECTRIC POLISHING KIT

Model 22824

INCLUDES

- 22707 Sport Bag
- 51592 8" (200 mm) Dia. Electric Right Angle Polisher
- 57543 6" Hook Face Pad with M14x2 spindle
- 22011 1L DynaTeal Polish Compound
- 22017 1L DynaRed Polish Compound
- 74016 2 Grey Conical Polishing Foam 160mm 1Hole
- 74014 2 Blue Conical Polishing Foam 160mm 1Hole
- 22050 2 Microfibre Wipes Orange



22824

2-STEP KIT 5" (125 MM) DYNABUFFER WITH DYNATEAL

Model 22826

INCLUDES

- 58455 5" (127 mm) Dia. Dynabuffer Random Orbital Polisher
- 58037A 1-1/4" (32 mm) Diam. Mini Orbital Sander
- 74009 2 Black Conical Polishing Foam 138mm 1 Hole
- 74010 2 Blue Conical Polishing Foam 138mm 1 Hole
- 22770 Dynabrade PSA Denibbing Discs P3000 (100 pcs/tube)
- 22011 1L DynaTeal Polish Compound
- 22050 4 Microfibre Wipes Orange
- 22001 Apron
- Durable carrying case



22826

PREMIUM POLISHING KIT

Model 22823

INCLUDES

- 58455 5" (127 mm) Dia. Dynabuffer Random Orbital Polisher
- 73502 Microfiber Polishing Pad 135mm
- 74012 Grey Conical Polishing Foam 138mm 1 Hole
- 74010 Black Conical Polishing Foam 138mm 1 Hole
- 53965 Interface Pad 150mm 15 holes
- 24676 Clog Free Sanding Disc 150mm Diam. 15 holes P2000 (25pcs)
- 22017 1L DynaRed Polish Compound
- 22021 1L DynaOrange Polish Compound
- 22050 2 Microfibre Wipes Orange
- 22045 Spray Bottle
- 22048 Spray Trigger
- Durable carrying case



22823

2-STEP KIT 3" (76 MM) DYNABUFFER WITH DYNATEAL

Model 22825

INCLUDES

- 57126 3" (76 mm) Dia. Dynabuffer Random Orbital Polisher
- 58037A 1-1/4" (32 mm) Diam. Mini Orbital Sander
- 74000 2 Black Conical Polishing Foam 87mm 1 Hole
- 74001 2 Blue Conical Polishing Foam 87mm 1 Hole
- 22770 Dynabrade PSA Denibbing Discs P3000 (100 pcs/tube)
- 22011 1L DynaTeal Polish Compound
- 22050 4 Microfibre Wipes Orange
- 22001 Apron
- Durable carrying case



22825

3" (76 MM) NITRO EXTENDED BUFFER POLISHING KIT WITH DYNARED

Model 22245

INCLUDES

- EB3 NITRO 3" Extension Buffer / Polisher
- 22017 1L DynaRed Polish Compound
- 56150 2 Microfiber polishing pads 80mm
- 74002 2 Grey Conical Polishing Foam 87mm 1Hole
- 74001 2 Blue Conical Polishing Foam 87mm 1Hole
- 22050 2 Microfibre Wipes Orange
- Durable carrying case



22845



CLEAN AIR SOLUTIONS


Dynabrade Raptor Vac® sanding systems tackle a variety of applications from everyday shop cleanup to demanding sanding applications and even metallic dust collection. The combination of HEPA filtration and certified M-Class, Division 1 and Division 2 vacuums contribute to an optimal work environment by assuring the efficient capture

of dusts like body filler, or aluminum dusts respectively. The power cord and vacuum hose combine with the mobility of a cart or casters to provide up to 40 feet of reach for operators; giving them flexibility to move throughout the shop.

Dynabrade clean air solutions are highly customizable and exceptionally easy to

maintain. Additional hoses and connectors allow for the expansion of a vacuum from a one-person unit to a system for two operators working simultaneously. Unlike many other vacuum systems the filters and bags in Dynabrade Raptor Vacs® are easily accessible and allow for easy maintenance throughout the life of the system.

VACUUMS FOR HEALTH AND SAFETY




HEPA Filtration

HEPA filters utilized in Raptor Vacs® are highly efficient and capture particulates as fine as 0.3 micron.



Breathe Fresh Air

Capturing respirable dusts created while sanding or grinding helps ensure operators are breathing clean air, contributing to a safer workplace.



Maximize abrasive life

Vacuuming sanding dust as it is being made helps prevent dust from loading on an abrasive disc or sheet enabling the abrasive to be used completely and helping prevent swirl marks.



Minimized Down Time

Easy access filters and bags used in Raptor Vacs® make maintenance simple and quick. The Mini-Raptor Vac® power unit can be easily replaced at the end of the motor service life, in under 15 minutes.




Certified Equipment

Breathe easy knowing the Dynabrade full line of clean air solutions are certified to meet each area of collection, including aluminum dust.



Vacuum Tools

Dynabrade has pioneered the use of portable air tools with vacuums. All compatible tools can be found on our new web page and in a full catalog dedicated to clean air tools and equipment.



MINI-RAPTOR VAC® PACKS MOBILE AUTOMOTIVE VACUUM SYSTEMS

Designed for peak efficiency, the Pro-Pack equips a single operator with a complete system for sanding and dust collection. Featuring a Vacuum Auto On/Off, the Premium Pack saves time and energy by automatically turning suction on and off with tool use.

PREMIUM PACK

FEATURES

- ▶ Premium cart with accessory shelf
- ▶ Tool & hose hanger
- ▶ Mini-raptor vac® auto on/off
- ▶ Industrial locking casters
- ▶ Stainless canister with HEPA filter & bag
- ▶ 6 meters vacuum hose assembly, non-conductive

**TECH
TIP**

M-Class vacuums capture particulates
10X finer than L-Class vacuums.

RAPTOR VAC® AUTO ON/OFF

61570

- ▶ Tool use activates vacuum suction
- ▶ 1/2" Air Inlet & Outlet
- ▶ 230v

* Shown with optional 61561 Mini Raptor Vac® Single Tool Connection Kit



Model 10089

**2 YEAR
WARRANTY**



M-Class



BENEFITS



The Mini-Raptor Vac® Pro-Pack provides technicians with a complete package for all their sanding, storage and mobility needs. The single tech work station seen here is easily expandable to a two-person station by adding a Y-connector and second hose. The shelf and storage containers keep additional tools and abrasives organized and close at hand, while the small footprint keeps floor space free of clutter.

STANDARD PACK

Fending off dust and creating an efficient and safe work environment begins with the Mini-Raptor Vac® – Standard Pack. The combination of Dynabrade Random Orbital Sander, Raptor Vac® and cart provides a mobile sanding solution for dusty shops.

FEATURES

- Carriage handle & dolly
- Stainless canister with HEPA filter & bag
- 6 meters vacuum hose assembly, non-conductive

TECH TIP

For wet pickup remove dry use only filter and bag and install optional 61126 filter sleeve.



Model 10088



M-Class



2 YEAR WARRANTY

INCLUDED IN PACK

Model Number					
10088	X		X	X	
10089	X	X		X	X

COMPONENT SPECIFICATIONS



Model Number	Amp	Capacity Gallon/Liter	Watts	Water Static Lift Inch / cm/ mbar	Air Flow CFM (L/Min)	Sound Level	Height Inch (mm)	Width Inch (mm)	Length Inch (mm)
61110	5A	16 (60.5)	1050	60 / 152 / 149	115 (3,256)	82 dBA	28 (71)	21 (53)	18 (46)



Model Number	Platform Dimensions	Weight lb (kg)	Shipping Weight lb (kg)	Height Inch (mm)	Width Inch (mm)	Length Inch (mm)
61486	18" (457 mm) x 24" (610 mm)	75 (34)	89 (40)	43.5 (110)	25.3 (64)	30.7 (78)

RELATED PRODUCTS



Raptor Vac®
Auto On/Off
Page 68



Power Unit
Assembly
Page 68



Vacuum Hose
Assembly
Page 66

M-CLASS VACUUM SYSTEM

ELECTRIC PORTABLE VACUUM SYSTEM

Designed for general source capture and dry cleanup. For collecting dust and debris such as wood, plastics, fiberglass and body filler. Conductive stainless steel canister, for dry vacuuming only in normal locations.

FEATURES

- ▶ Vacuum starts automatically with startup of tool
- ▶ Bypass Motor System uses environmental air to cool the motor and extend vacuum life
- ▶ Heavy-duty stainless steel recovery tank, with 20 gallon (78 liter) capacity for clean filter assurance. This size allows filter to remain at substantial distance from collected debris, reducing clogging and extending motor life
- ▶ Convenient orange warning light indicates that filter needs replacement
- ▶ Self-cleaning filter system

INCLUDES

Two 20' (6 m) Conductive Coaxial Hoses with Integrated Air Lines
 "Y" Connector
 Two Composite Couplers
 Vacuum Hose Swivel Cuff
 Two Disposable Collection Bags
 HEPA H13 Filter with 99.95 % efficiency on 0.3 micron



Model 61402 M-Class - 120 V, 60 Hz, 15 Amp Plug (UK)

2 YEAR
WARRANTY

CERTIFICATIONS



European Countries:



NON-CONDUCTIVE

Model Number	Country	Capacity Gallon (Liter)	Voltage/Frequency	Watts	Amp (Plug for Region)	Water Static Lift Inch / cm / mbar	Air Flow CFM (L/Min)	Sound Level	Ship Weight Lb. (kg)	Height In. (mm)	Width In. (mm)	Length In. (mm)
61409	UK	20 (78)	230 V / 50 Hz	1,250	5 (CCE7)	94 / 238 / 234	125 (3540)	73 dB(A)	85 (39)	48 (122)	27 (69)	24 (61)
61408	Europe	20 (78)	230 V / 50 Hz	1,250	5 (CCE7)	94 / 238 / 234	125 (3540)	73 dB(A)	85 (39)	48 (122)	27 (69)	24 (61)
61412	Switzerland	20 (78)	230 V / 50 Hz	1,250	5 (CCE7)	94 / 238 / 234	125 (3540)	73 dB(A)	85 (39)	48 (122)	27 (69)	24 (61)

CONDUCTIVE

Model Number	Country	Capacity Gallon (Liter)	Voltage/Frequency	Watts	Amp (Plug for Region)	Water Static Lift Inch / cm / mbar	Air Flow CFM (L/Min)	Sound Level	Ship Weight Lb. (kg)	Height In. (mm)	Width In. (mm)	Length In. (mm)
61403	UK	20 (78)	230 V / 50 Hz	1,250	5 (CCE7)	94 / 238 / 234	125 (3540)	73 dB(A)	85 (39)	48 (122)	27 (69)	24 (61)
61409	Europe	20 (78)	230 V / 50 Hz	1,250	5 (CCE7)	94 / 238 / 234	125 (3540)	73 dB(A)	85 (39)	48 (122)	27 (69)	24 (61)
61413	Switzerland	20 (78)	230 V / 50 Hz	1,250	5 (CCE7)	94 / 238 / 234	125 (3540)	73 dB(A)	85 (39)	48 (122)	27 (69)	24 (61)

Additional Specifications: Air Inlet Thread 3/8" NPT • Air Pressure 90 PSIG (6.2 Bar)

PNEUMATIC WALL-MOUNT VACUUM

For use on metallic surfaces, a perfect solution for the occasional capture of potentially hazardous dusts such as aluminum and commercial alloys. The included wall-mounting brackets allow for convenient storage and removal providing technicians with added mobility throughout the garage.

FEATURES

- ▶ The most cost-effective solution to metallic dust collection
- ▶ Designed for dry source capture, to be used for general maintenance in potentially hazardous locations
- ▶ Lightweight, stainless steel construction (SAE 304) handheld design provides great mobility
- ▶ Air jet is adjustable from 80" to 90" of water static lift
- ▶ Aerosol leak tested for quality assurance
- ▶ Unit is static-dissipating (kit included) and conductive
- ▶ Recovery capacity of 1.5 gallons (6 liters) in optional Disposable Filter Bag

INCLUDES

HEPA H14 Filter
Brackets for Mounting to Wall or to Vacuum Cart
Wall-mounting hardware
1/2" by 2' (25 mm x 0.6 m) Conductive Air Line Supply
Composite Coupler
Vacuum Hose Swivel Adapter
Three Collection Bags

CERTIFICATIONS

Designed for use in:
Class I, Category 2, Groups A, B, C, D, T6; Class II, Category 2, Groups E, F, G
Hazardous Locations as defined in the National Electric Code (NFPA 70)



European Countries:
ATEX Third Party Certified
CE EX II 2 GD c IIC T6 (85° C)



Model 61471 Category 2 - (Europe)



Model 61473 Category 2 - (Europe)

**2 YEAR
WARRANTY**

Model Number	Capacity Gallon (Liter)	Max. Capacity Lb. (kg)	Air Inlet Pressure PSIG (Bar)	Air Consumption CFM (L/Min)	Air Flow CFM (L/Min)	Water Static Lift Inch / cm / mbar	Sound Level	Ship Weight Lb. (kg)	Height In. (mm)	Width In. (mm)	Length In. ()
61471	1.5 (6)	5 (2.3)	90 (6.2)	35 (991)*	50 (1,416)	80 / 203 / 199	68 dB(A)	28 (13)	16 (41)	18 (46)	30 (76)
61473	1.5 (6)	5 (2.3)	90 (6.2)	35 (991)*	50 (1,416)	80 / 203 / 199	68 dB(A)	28 (13)	16 (41)	18 (46)	30 (76)

*NOTE: Be sure to add air consumption for EACH TOOL attached to Vacuum, for total CFM (L/Min) requirement.

RELATED PRODUCTS



ROS Sanders
Pages 26-31



Cleaning
Kit
Page 66



Optional
Vacuum Hose
Assembly
Page 66

COMPACT IMMERSION VACUUM SYSTEM ELECTRIC AND PNEUMATIC PORTABLE VACUUMS

For collecting metallic dust & debris such as aluminum and commercial alloys. Collects and renders inert up to a maximum of 5 lbs. (2.27 kg) of dust.

FEATURES

- ▶ Legally certified explosion proof / dust ignition proof by an OSHA approved Nationally Recognized Testing Laboratory (NRTL)
- ▶ Coalescing Filter Element (CFE) for moisture removal
- ▶ Degassing Vent allows gas to be evacuated automatically from the unit
- ▶ Vacuums and included tool kit are static-dissipating and conductive
- ▶ Corrosion resistant Stainless steel recovery tank

ELECTRIC AND PNEUMATIC VACUUMS INCLUDE:

One 20' (6 m) Conductive Coaxial Hoses with Integrated Air Lines
One Composite Coupler
One Vacuum Hose Swivel Adapter
Conductive Collection Bag
HEPA H14 Filter with 99.995% efficiency on 0.3 micron

Model Number	Regional Description	Capacity Gallon (Liter)	Dust Recovery Pound (kg)	Voltage/Frequency	Watts	Amp (Plug for Region)	Water Static Lift Inch / cm / mbar	Air Flow CFM (L/Min)	Sound Level	Height In. (cm)	Width In. (cm)	Length In. (cm)
61511	ATEX Cat. 2 for Zones 1 & 21	6.25 (24)	5 (2.27)	220-240 V / 50-60 Hz	1,000	13 (UK)	69 / 175 / 172	132 (3,738)	85 dB(A)	43 (109)	26 (66)	26 (66)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar) • Ship Weight 179 lb. (81 kg)

Model Number	Regional Description	Capacity Gallon (Liter)	Dust Recovery Pound (kg)	Air Consumption CFM/(L/Min)	Air Flow CFM/(L/Min)	Water Static Lift Inch / cm / mbar	Sound Level	Height In. (cm)	Width In. (cm)	Length In. (cm)
61512	ATEX Cat. 2 for Zones 1 & 21	6.25 (24)	5 (2.27)	45 (1,274)*	110 (3,115)	180 / 457 / 448	80 dB(A)	48 (122)	22 (56)	20 (51)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar) • Ship Weight 168 lb. (76 kg)

*NOTE: Be sure to add air consumption for EACH TOOL attached to Vacuum, for total CFM (L/Min) requirement.

BENEFITS



A common misconception is that metallic dust is required to be captured using a wet vacuum system. The National Fire Protection Agency states that up to 5 pounds of metallic dust can be collected in a dry state. Category 2 Raptor Vacs® are certified for DRY pickup of potentially hazardous metallic dusts, like aluminum, that are commonly found in many modern vehicles. The wall-mount Raptor Vac® provides a low cost entry point for metallic dust collection.



PNEUMATIC VACUUM for use in:

Group A atmospheres, containing acetylene

Group B atmospheres, containing flammable gas, flammable liquid-produced vapor, or combustible liquid-produced vapor mixed with air

Group C atmospheres, containing flammable gas, flammable liquid-produced vapor, or combustible liquid-produced vapor mixed with air

ELECTRIC and PNEUMATIC VACUUM for use in:

Group D atmospheres, containing flammable gas, flammable liquid-produced vapor, or combustible liquid-produced vapor mixed with air that may burn or explode

Group E atmospheres, containing potentially combustible dusts, including aluminum, magnesium, and their commercial alloys

Group F atmospheres, containing combustible carbonaceous dusts, such as coal, carbon black, charcoal, coke dust

Group G atmospheres, containing wood and plastic dusts



CERTIFIED
Explosion-proof and
dust ignition-proof

For safe recovery
of combustible and
conductive dusts

2 YEAR
WARRANTY



ELECTRIC

Model 61511 Category 2 – 230 V, 50 Hz (Europe)

CERTIFICATIONS



Designed for use in:
Class I, Category 2, Group D T3C
Class II, Category 2, Groups E, F and G
Hazardous Locations as defined in
the National Electric Code (NFPA 70)



European Countries:
ATEX Third Party Certified
CE EX II 2 GD Ex d IIA T3 Gb
Ex t IIIC T 200° C Db IP 6X

PNEUMATIC

Model 61512 Category 2 (Europe)

CERTIFICATIONS

Designed for use in:
Class I, Category 2, Group D T3C
Class II, Category 2, Groups E, F and G
Hazardous Locations as defined in
the National Electric Code (NFPA 70)



European Countries:
ATEX Third Party Certified
CE EX II 2 GD c IIC T6 (85° C)

RELATED PRODUCTS



ROS Sanders
Pages 26-31



Cleaning Kit
Page 66



Vacuum Hose
Assembly
Page 66



Conductive
Collection Bag
Page 67



meet the demands of a specific application. Accessories like these are details that help separate an efficient garage that moves vehicles quickly through the repair process and out to the customer, from garages that fight poor finishes and rework.

ACCESSORIES FOR OPTIMIZATION



Air tools all require specific air volume and pressure to reach their full production and efficiency potential. Using Dynabrade air delivery accessories like Mega-Flow couplers and plugs will help ensure tools do not stall under working load and operate at recommended speeds. Dynaswivels® create a “universal joint” that connects an air tool to

an airline, increasing maneuverability, reduces operator fatigue and extends hose life. Using a F-R-L will filter, regulate, and lubricate the air entering the motor chamber preserving critical components from exposure to dirt and water, ensures adequate air pressure, and increases the longevity of the air tool.

SANDING PAD INNOVATION



Sanding pads are more than a component that an abrasive disc or sheet attaches to; they are a critical component to creating the finest, most consistent surface finishes. Dynabrade random orbital sanding pads are weight-mated to each pad diameter, reducing vibration that leads to poor finishes and ergonomic concerns for the user. The single-piece hub design is a feature pioneered by Dynabrade that further reduces


pad vibration and contributes to extended tool life and dependability. Extreme Sanding Pads are the newest innovation is vacuum sanding employing a hybrid dust collection method. The teal sanding pads utilize vacuum holes and channels that direct dusts to the center of the pad where suction and pickup is greatest, increasing abrasive life by reducing buildup.

CLEAN AIR EQUIPMENT



Capturing dust as it is being created in the sanding process is the best way to ensure airborne particulates do not become dust nibs on a newly painted surface elsewhere in a shop. HEPA filtration is utilized in all dry Dynabrade Raptor Vacs® and helps ensure that even very fine dusts are captured before they can settle and contaminate a work piece,

be inhaled by a technician, or cause a fire or explosion in the case of some metallic dusts found in modern vehicles. With integrated or available Auto On/Off features Raptor Vacs® help keep technicians productive by only operating as a tool is being used and also help reduce noise and energy consumption within the shop.



FILTER/REGULATOR/LUBRICATOR

Using a Dynabrade F-R-L at every work station will extend the service life of the tools at an operator's bench. A F-R-L will filter debris/water hidden inside air lines, allow operators to regulate air pressure locally, and deliver air tool oil much more consistently than a manual oiling process.

- ➊ Mounting brackets for easy installation
 - ➋ Manual filter/drain protects tools from water and contamination
 - ➌ Modular connections easily adaptable
 - ➍ Regulator and pressure gauge monitor and adjust air pressure
 - ➎ Adjustable oil drop, set drip rate based on tool consumption
 - ➏ Zinc construction for enhanced durability
- ▶ 106 SCFM for high demand tools
 - ▶ 5-micron filter
 - ▶ Includes 3/8" NPT reducer bushings
 - ▶ Use with Dynabrade Air Lube (95842)



Model Number	Inlet/Outlet Port Size	Maximum Air Pressure	Maximum Air Flow	Maximum Air Temperature
10690	1/2" NPT	150 PSIG (10.3 Bar)	106 SCFM (3,000 LPM)	150° F (65° C)

AIR LINE CONNECTORS

Improve tool maneuverability and minimize operator fatigue with a "universal-joint". Two pivot points that swivel 360° relieve stress on the hose and hardware.

- ▶ Composite – no marring paint or clear coat
- ▶ Aluminum, Stainless Steel, Brass – durable metal construction
- ▶ Flow Control – finger-tip air-flow control dial or lever

Part Number	Thread Size	Style	Air Flow Range	Material
94300*	1/4" NPT	Standard	up to 33 SCFM (935 LPM)	Composite
94407**	1/4" NPT	Flow Control	up to 46 SCFM (1,303 LPM)	Composite
95460	1/4" NPT	Standard	up to 25 SCFM (708 LPM)	Aluminum & Stainless
95734	1/4" NPT	Flow Control	up to 25 SCFM (708 LPM)	Aluminum & Stainless
95756	1/4" NPT	Flow Control	up to 25 SCFM (708 LPM)	Chrome Plated Brass



94300



94407



95460



95756

COUPLER AND PLUGS

MEGA FLOW PLUGS

- ▶ Ported design delivers maximum air volume to the tool
- ▶ Durable zinc-plated steel construction
- ▶ Provides up to twice the air flow of a standard plug design

Body Size	Part Number	Thread Size NPT	Air Flow Range SCFM (LPM)
1/4"	95675	1/4" Male	up to 74 (2,095)
	95677	1/4" Female	
	96005	3/8" Male	



STEEL AND BRASS SAFETY COUPLERS

- ▶ Durable nickel-plated steel and brass construction
- ▶ Single action quick-connect by just inserting plug into coupler
- ▶ Release pressure before disconnecting

Coupler Body Size	Part Number	Thread Size NPT	Air Flow Range SCFM (LPM)
1/4"	95674	1/4" Female	up to 74 (2,095)
	95684	1/4" Male	



COMPOSITE-STYLE COUPLERS

- ▶ Easy disconnect by single push-button action
- ▶ Heavy-duty construction that is lightweight, shock-proof, low-vibration, and crush-resistant
- ▶ Composite-style design provides maximum air flow to tools

Body Size	Part Number	Thread Size NPT	Air Flow Range SCFM (LPM)
1/4"	94960	1/4" Female	up to 54 (1,529)
	94980	1/4" Male	



COUPLER AND PLUG COMBINATIONS

PLUGS WITH STEEL/BRASS SAFETY COUPLERS

- ▶ Includes one coupler and one plug
- ▶ Maximum working pressure: 150 PSIG (10 Bar)
- ▶ Temperature Range: -4°F to 212°F (-20°C to 100°C)

Coupler & Plug Size	Part Number	Coupler Thread Size NPT	Plug Thread Size NPT	Air Flow Range SCFM (LPM)
1/4"	95676	1/4" Female	1/4" Male	up to 74 (2,095)
	95850	1/4" Female	1/4" Female	
	95685	1/4" Male	1/4" Male	
	95851	1/4" Male	1/4" Female	



PLUGS WITH COMPOSITE, PUSH-BUTTON COUPLERS

- ▶ Includes one coupler and one plug
- ▶ Maximum working pressure: 150 PSIG (10 Bar)
- ▶ Temperature Range: -4°F to 212°F (-20°C to 100°C)

Coupler & Plug Size	Part Number	Coupler Thread Size NPT	Plug Thread Size NPT	Air Flow Range SCFM (LPM)
1/4"	94990	1/4" Female	1/4" Male	up to 74 (2,095)
	94991	1/4" Female	1/4" Female	
	94992	1/4" Male	1/4" Male	
	94993	1/4" Male	1/4" Female	



AIR HOSE ASSEMBLY SPARK RESISTANT & ANTISTATIC

LIGHTWEIGHT AIR LINES – 8 MM I.D.

- ▶ Light Weight airline
- ▶ Includes reusable fittings, ensuring air line integrity and less pressure drop
- ▶ Narrow bending radius prevents “choking” of air tool



Part Number	Length Feet (Meters)	Line I.D. Inches (mm)	Line O.D. Inches (mm)	Fittings Included	Color
70400	3	8	Male 6mm (1/4") / Male 6mm (1/4")	Spark Resistant	Orange
70401	6				
70300	3			Antistatic	Grey
70301	6				

Other sizes or Hose only available upon request

Part Number	Connects to Inside Diameter	Connection Thread
94897	5/16" (8)	1/4" NPT Male



DYNAJET IN-LINE BLOW GUN

SAFETY TIP DESIGN

- ▶ Blow gun permanently mounted between coupler and air hose to purge air line of water and contaminants
- ▶ Durable aluminum construction, weighs only 2 oz. (.06 kg)
- ▶ Reduces line pressure down to 30 PSIG (2 Bar)
- ▶ Meets O.S.H.A. requirements of special relief hole in nozzle, which limits pressure to 30 PSIG (2 Bar) when dead-ended and used on an air line of 150 PSIG (10.3 Bar) or less
- ▶ Ideal to blow debris from work surface



Proper Installation for DynaJet Blow Gun Connection



Part Number	Thread Size	Weight	Recommended Air Flow Range SCFM (L/Min)
94467	1/4" Female NPT	.06 kg	up to 35 SCFM (991 L/Min)

10.3 Bar (150 PSIG) maximum

CONTACT ARM ASSEMBLIES/PARTS

Dynabrade contact arms are available for use with 1/4" - 1/2" wide abrasive belts. More varieties allow for access in tight areas, and many unique ways to present an abrasive to the work piece. Below are the most common contact arms used in collision repair or restoration — additional options are available.

Tools Used On	Part Number	Belt Width	Wheel Diameter	Wheel Type	Platen Pad	Comments
NitroFile	11203	1/2"	5/8"	Rubber, 70 durometer	1/2" Wide, Soft	—
NitroFile	11204	1/4" or 1/2"	1"	Rubber, 70 durometer	None	Offset Design, for Slack Sanding
NitroFile	11206	5/8" or 3/4"	3/4"	Rubber, 70 durometer	3/4" Wide, Hard	—
Mini-NitroFile	15028	1/4" or 1/2"	1"	Rubber, 90 durometer	None	Offset Design, for Slack Sanding
Mini-NitroFile	15031	1/2"	7/16"	Steel	1/2" Wide, thin	13" Belts



DYNABRADE NITRO SERIES™ NITROZIP ACCESSORIES

Dynabrade Nitro Series™ NitroZip wire wheels are used for a variety of material removal and surface preparation applications from removing seam sealer to rust and paint removal. Red-Tred® Eraser wheels are ideal for removing adhesive-backed decals and striping without harming the painted surface below.

WIRE AND ERASER WHEELS

Part Number	Size	Grade	Tip Type	Use
92245	4" dia. x 3/4" wide	Coarse	Bent	Sealants
92246	4" dia. x 3/4" wide	Medium	Bent	Rust
92247	4" dia. x 3/4" wide	Fine	Straight	Paint Removal
92248	4" dia. x 3/4" wide	Coarse	Bent	Sealants
92255	4" dia. x 1-1/4" wide	Aggressive Removal	—	Decals/Adhesive
92240	4" dia. x 1-1/4" wide	Light Removal	—	Decals/Adhesive



DECAL REMOVAL AND ERASER WHEEL

Decal Removal Wheel – 4" diameter x 1 1/4" wide

Model 92255 RED-tred® Eraser wheel only

Model 92242 RED-tred® Eraser wheel with hub for use with Dynabrade Nitro Series™ NitroZip

Model 92240 Beige Eraser wheel only

Model 92252 Beige Eraser wheel with hub

WHEEL HUB ASSEMBLY

Mounts wire wheels and the 92255 Eraser Decal Removal Wheel

Model 92239 For 3/4" wide wheel

Model 92252 For 1/2" wide wheel



92239

SANDING PADS

Dynabrade random orbital sanding pads are precision engineered for ultra-smooth performance and longer life. Exclusive single-piece hub design reduces pad vibration and

ensures smooth performance. Premium urethane sanding pads are perfectly weight-mated to Dynabrade tools, and achieve consistent swirl-free finishes. All Dynabrade sanding pads

feature our exclusive single-piece hub design, which reduces pad vibration and ensures smooth performance.



HOOK-FACE



Non-Vacuum

Vacuum

Short nap pads for use with reattachable discs. Long nap pads for use with non-woven nylon discs. Available in Non-Vacuum and Vacuum pads.

DYNAMAZE



(ø 152 mm) – model: 22290

SIMPLE, EFFECTIVE, FAST AND EASY TO USE
Self-gripping pad for all abrasives which match with all hole configurations due to its unique mesh system.

SUPERVAC



(ø 152 mm) – model: 22330

EXCELLENT CLEANUP CAPACITY
The self-gripping pad includes 132 holes and 15 holes in the standard position. For use with self-gripping abrasive discs with a mesh structure. Excellent for all perforation types.

GEAR-DRIVEN SANDER PADS

HOOK-FACE

Diameter Inch (mm)	Part Number	Vacuum Type	Max. RPM	Thickness Inches (mm)	Holes	Screws
5 (127)	57760	Non-Vacuum	12,000	3/8 (10)	—	5
6 (152)	57387	Non-Vacuum	10,000	3/8 (10)	—	6
6 (152)	57764	Non-Vacuum	12,000	3/8 (10)	—	5
6 (152)	57765	Vacuum	12,000	3/8 (10)	6	5
8 (203)	56236	Non-Vacuum	10,000	1/2 (13)	—	5
8 (203)	56237	Vacuum	10,000	1/2 (13)	8	5



RANDOM ORBITAL SANDER PADS

HOOK-FACE

Diameter Inch (mm)	Part Number	Vacuum Type	Holes	Nap	Thickness Inches (mm)	Density
3 (76)	56087	Non-Vacuum	–	Short	5/8 (16)	Medium
5 (127)	54325	Non-Vacuum	–	Short	3/8 (10)	Medium
5 (127)	54326	Vacuum	5	Short	3/8 (10)	Medium
5 (127)	54334	Vacuum	17	Short	3/8 (10)	Medium
6 (152)	54327	Non-Vacuum	–	Short	3/8 (10)	Medium
6 (152)	56158	Non-Vacuum	–	Short	3/8 (10)	Soft
6 (152)	54328	Vacuum	6	Short	3/8 (10)	Medium
6 (152)	54339	Vacuum	17	Short	3/8 (10)	Medium
8 (203)	56236	Non-Vacuum	–	Short	3/8 (10)	Medium
8 (203)	56327	Vacuum	8	Short	3/8 (10)	Medium



DYNAMAZE UNIVERSAL VACUUM PADS

Diameter	Part Number	Thread	Thickness	Density
127 mm	22293	5/16"-24	10 mm	Medium
	22294	5/16"-24	16 mm	Soft
	22297	M8	10 mm	Medium
	22298	M8	16 mm	Soft
152 mm	22290	5/16"-24	10 mm	Medium
	22291	5/16"-24	16 mm	Soft
	22295	M8	10 mm	Medium
	22296	M8	16 mm	Soft
	22299	5 screws	10 mm	Medium
203 mm	22292	5/16"-24	10 mm	Medium



DYNALINE INLINE SANDER PADS

HOOK-FACE

Pad Dimensions Inch (mm)	Part Number	Vacuum Type	Thickness Inches (mm)	Nap	Screws
2 3/4" x 8" (70 mm x 203 mm)	57456	Non-Vacuum	3/8 (10)	Short	2
	57471	Non-Vacuum	3/8 (10)	Long	2
	57457	Vacuum	3/8 (10)	Short	6
3 2/3" x 7" (93 mm x 178 mm)	57856	Vacuum	3/8 (10)	Short	10



DYNABUG® SANDING PADS

HOOK-FACE

Pad Dimensions Inch (mm)	Part Number	Vacuum Type	Thickness Inches (mm)	Nap	Screws
3 2/3" x 7" (93 mm x 178 mm)	57851	Non-Vacuum	3/8 (10)	Short	4
	57852	Non-Vacuum	3/8 (10)	Long	4
	57856	Vacuum	3/8 (10)	Short	4



DYNABUG® II PADS

3/8" (10 mm) thick, medium density pads mount with four screws.

HOOK-FACE

Pad Dimensions Inch (mm)	Model Number	Vacuum Type	Thickness Inches (mm)	Holes	Screws
2 3/4" x 7 3/4" (68 mm x 196 mm)	56326	Vacuum	3/8 (10)	8	4
3" x 4" (68 mm x 196 mm)	56351	Non-Vacuum	3/8 (10)	—	4
3" x 4 1/4" (74 mm x 109 mm)	56315	Non-Vacuum	3/8 (10)	—	4
	56316	Vacuum	3/8 (10)	4	4
3 1/4" x 5" (80 mm x 130 mm)	56317	Non-Vacuum	3/8 (10)	—	4



DYNAFOAM INTERFACE PADS

Interface pads attach between sanding pad and Hook-Face abrasive. Soft foam increases conformability allowing operator to easily follow contours. Converts standard pad into a fine finishing and finessing pad.

FOR RANDOM ORBITAL SANDERS

Part Number	Diameter Inch (mm)	
53974	3" (76 mm)	○
53976	3 1/2" (89 mm)	○
53978	5" (127 mm)	⦿
53980	6" (152 mm)	⦿
53965	6" (152 mm)	⦿
53982	8" (203 mm)	⦿

FOR DYNALINE & DYNABUG® SANDERS

Part Number	Diameter Inch (mm)	
53984	2 3/4" (70 mm) x 11" (279 mm) For the Dynaline	□
53986	2 3/4" (70 mm) x 8" (203 mm) For the Dynaline	□
53988	3 2/3" (93 mm) x 7" (175 mm) For the Dynaline and Dynabug®	□



VACUUM ACCESSORIES

Each cleaning kit includes an extension hose and variety of attachments used for general shop cleanup and dust collection in hard-to-reach areas. Specialized conductive and Division 1 Certified cleaning kits protect technicians from static discharge and acceptably capture aluminum dusts.

MINI-RAPTOR VAC® CLEANING KIT

Model 96605

For models 10029, 10030, 10031, 10059, 10060, and 10061
Vacuum Hose, 8 ft. (2.5 m) x 2.5"



CONDUCTIVE CLEANING KIT

Model 96607

For models 10029, 10030, 10031, 10049, 10050, 10051, and 61421
Vacuum Hose, 10 ft. (3 m) length



RAPTOR VAC® DIVISION 1 CLEANING KIT

Model 96606

For models 61495 and 61496
Vacuum Hose, 10 ft. (3 m) length



WALL-MOUNTED RAPTOR VAC® DIVISION 1 CLEANING KIT

Model 62831

For model 61470
Vacuum hose, 20 ft. (6 m) length

Model 62832

Vacuum hose, 8 ft. (2.5 m) length available upon request



1" ERGONOMIC VACUUM HOSE ASSEMBLY

Model 31972

Conductive vacuum hose with integrated air line
20 ft. (6 m) length
(1) 1/4" NPT coupler
(2) 1/4" NPT plugs
Mesh protective over-hose

Model 31982

Non-conductive hose assembly



VACUUM HEPA AND WET FILTERS

Part 61122

- For use with Mini-Raptor Vac® 61100
99.95% efficiency on 0.3 micron

Part 61126

- Wet collection sleeve for use with
Mini-Raptor Vac® 61100

Part 62415


- For use with Wall-Mount Raptor Vac® 61470

Part 80459

- For use with Raptor Vac® 61421

Part 61907


- For use with Raptor Vac® Compact
Immersion 61495 and 61496



VACUUM BAGS & LINERS

Part 61125

- Disposable HEPA replacement bag for use with
Mini-Raptor Vac®



VACUUM PRE-FILTERS

Part 62778

- For use with Wall-Mount Raptor Vac® 61470




CONDUCTIVE & GROUNDED ACCESSORIES

Part 62449

- Grounded air line for use with Raptor Vac® 61495
and 61496

Part 61166

- Mini-Raptor Vac® Conductive Grounding Kit for
use with single inlet connection



ADDITIONAL VACUUM ACCESSORIES

MINI-RAPTOR VAC® AUTO ON/OFF (230 V)

Part 61570

- ▶ Auto On/Off available upon request for Mini-Raptor Vac® Packs
- ▶ Tool use activates vacuum suction
- ▶ 230V



SYSTAINER BOX SYSTEMS

Available for Mini-Raptor Vac® Packs

Part 61502 4 in. (102 mm) tall box

Part 61503 6 in. (152 mm) tall box

Part 61505 Mounting Kit

- ▶ Single compartment stack & lock storage boxes
- ▶ Mounting Kit prevents tipping and sliding



MINI-RAPTOR VAC® POWER UNIT ASSEMBLY

Part 61127

- ▶ User friendly power unit replacement, for quick and easy replacement



SAFETY COUPLER

Model 22628

- ▶ 320 Profile - 1/2" BSPT Male NBR+



AIR Y-CONNECTOR

Part 61564

- ▶ Connect two tools to vacuum auto on/off simultaneously



TOOL/VAC HOSE HANGER

Part 61506

- ▶ Storage of second tool and vacuum hose



LUBRICANTS AND GREASE

DYNABRADE AIR LUBE (10W/NR)

- Part 95821** 4 oz. (118 ml)
Part 95842 1 pt. (473 ml)
Part 95843 1 gal. (3.8 L)
Part 96101 Display Box
 24 – 4 oz. (118 ml) bottles

- Formulated for pneumatic equipment
- Absorbs up to 10% of its weight in water
- Prevents rust and formation of gum/sludge and extends time between recommended maintenance



GEAR OIL

- Part 95848** 2.5 oz. (74 ml) Tube

- Formulated for Dynabrade geared tools utilizing a wick-type lubrication system
- Apply every 8 hours of operation into tool's lubrication fitting
- Easy to apply using Dynabrade P/N 95541 Grease/Oil Gun



GEAR GREASE

- Part 95544** 2.5 oz. (74 ml) Tube

- Apply every 50 hours of use
- Easy to apply using with Dynabrade P/N 95541 Grease/Oil Gun



ULTRA GEAR GREASE

- Part 96664** 45 g Tube

- High-performance grease
- Extends gear life over conventional lithium grease
- Use on planetary gears and right angle gears



PUSH-TYPE OIL OR GREASE APPLICATOR

- Part 95541**

- Can be used with Gear Oil, Gear Grease and Ultra Gear Grease





ABRASIVES

Dynabrade abrasives are a key component to a total solution of tools, abrasives and accessories that deliver the lowest cost for the collision repair process. Dynabrade has a complete range of abrasives that optimize common operations technicians are confronted with like complete vehicle tear down, or damage repair and defect removal, body prep, painting and detailing.

Dynabrade offers multiple abrasive tiers for virtually every application. The broad selection meets the needs of all types and sizes of body shops with the specific goal of driving down overall costs by reducing labor and rework; while moving vehicles quickly and efficiently through the repair process and back to the owner.

The Dynabrade total solution approach will provide significant cost savings in comparison to traditional methods of collision repair or vehicle restoration based on a reduction in abrasives spend and usage, labor and time to complete each task.

ABRASIVES THAT PROVIDE RESULTS



DG 922 Film Discs

The smooth, high-performance, film backing provides the most uniform finish while the sharp free cutting abrasive and clog free coating cuts fast and eliminates pilling of body filler, primer and paint for maximum performance.



Clog Free Soft Film Discs

Part of the Dynabrade Finishing system the ultra-flexible, precision coated, clog free soft film discs products generate a defect-free, perfectly flat surface when damp or dry sanding clear coat prior to compounding and buffing.



DC 242 Coated Abrasives and Surface conditioning Belts

Dynaflex® belts are the ideal time savings solution for a myriad of applications in the body shop. From quick and easy spot weld removal for faster tear down, to weld grinding and blending on repairs, as well as blending and finishing exposed components prior to powder coating or chrome.



Buffing Pads and Compounds

The Dynabrade 2-Step finishing system optimizes the process of paint correction and polishing from up to 4 or 5 steps with conventional abrasives, compounds and pads; to a 2-step process for delivering a high-gloss and hologram-free finish. Whether using a rotary, gear-driven or random orbital tool the Dynabrade 2-step system delivers optimum results in less time.

SANDING AND FINISHING

FILM / PAPER DISCS, DISC ROLLS AND SHEETS

At Dynabrade we listen, we observe, and we optimize. There are a wide variety of sanding and finishing applications in today's modern body, fabrication and detail shops. Dynabrade offers a full selection of premium performance film and paper backed discs and sheets providing

an optimum solution for virtually any sanding and finishing application. DV 722 Sanding and Finishing abrasives include hook-face discs and sheets. These sanding and finishing abrasives are commonly used for stripping paint, sanding plastics, fiberglass and composites, leveling and

blending body filler, feather edging and sanding primer, color and clear coat.



DV722 COATED ABRASIVE DISCS & SHEETS - ALUMINUM OXIDE PAPER BACKING

The **GOOD** choice for all sanding and finishing applications. Available in B-weight and C-weight backings, aluminum oxide paper discs have a clog free coating and are the value choice where price is the only factor.

APPLICATIONS

- Surface sanding on any type of wood, metal, composite, solid surface, filler, e-coat, primer, paint coat, clear coat and gel coat

FEATURES

- Anti-loading stated topcoat provides long life and good cut rate without wild scratches
- Open coat of Aluminum oxide grain for less clogging
- Suitable for grinding new generation water based lacquers

BENEFITS

- Resinoid bonding ensures excellent performance and durability
- Excellent dust reduction with vacuum dust extraction system for a safe and work-friendly environment

INFORMATION



DV722 COATED ABRASIVE DISCS & SHEETS - ALOX/PAPER BACKING

C/B WEIGHT PAPER BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
80	22239	50	75 mm - 6 Holes	Disc
100	22241			
120	22258			
150	22259	100		
180	22260			
240	22261			
320	22262			
400	22263			
600	22264			
800	22265			
60	24629	50	150 mm - 0 Hole	
80	24630			
100	24631			
120	24632			
150	24633	100		
180	24634			
220	24635			
240	24636			
280	24637			
320	24638			
360	24639			
400	24640			
500	24641			
600	24642			
800	24643			
60	24644	50		150 mm - 21 Holes
80	24645			
100	24646			
120	24647			
150	24648	100		
180	24649			
220	24650			



DV722 COATED ABRASIVE DISCS & SHEETS - ALOX/PAPER BACKING

C/B WEIGHT PAPER BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape	
240	24651	100	150 mm - 21 Holes	Disc	
280	24652				
320	24653				
360	24654				
400	24655				
500	24656				
600	24657				
800	24658				
60	24682	50	150 mm - 6+1 Holes		
80	24683				
100	24684				
120	24685				
150	24686	100			
180	24687				
220	24688				
240	24689				
280	24690				
320	24691				
360	24692				
400	24693				
500	24694				
600	24695				
800	24696				
80	22231			50	70 x 198 mm - 8 Holes
120	22232				
180	22233	100			
240	22234				
320	22235				
400	22236				
120	22237		70 x 198 mm -10 Holes		
180	22595		80 x 130 mm - 0 Hole		
240	22572				
320	22593				



Model: 59029



Model: X61V



Model: 57404



Model: 58503

DV722 COATED ABRASIVE DISCS & SHEETS - ALOX/PAPER BACKING

C/B WEIGHT PAPER BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
400	22618	100	80 x 130 mm - 0 Hole	Rectangular
500	22619			
80	22266	50	80 x 130 mm - 4+4 Holes	
120	22267			
180	22268	100		
240	22269			
320	22270			
60	22384			
80	22385			
120	22386			
180	22387			
240	22388			
320	22389			
80	22207	50	95 x 175 mm - 10 Holes	
120	22208			
180	22209	100		
240	22210			
320	22211			
400	22212			
60	22464	50	115 x 280 mm - 10 Holes	
80	22465			
120	22466	100		
180	22467			
240	22468			
320	22469			
60	22390		115 x 400 mm - 14 Holes	
80	22391			
120	22392			
180	22393			
240	22394			
320	22395			



Model: 58502



Model: 57804



Model: 58552



Model: 58551

DV722 COATED ABRASIVE DISCS & SHEETS - ALOX/PAPER BACKING

C/B WEIGHT PAPER BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
80	22012	50	62 x 98 mm - 0 Hole	Tear Drop
100	22328	100		
120	22026	50		
180	22028	100		
240	22329			
320	22032			
400	22034			
500	22036	50		
80	22039			
120	22041			
180	22043			
240	22355	100		
320	22205			
400	22206			
80	22219			
120	22220			
180	22221	100		
240	22222			
320	22223			
400	22224			
80	22213	50		
120	22214			
180	22215	100		
240	22216			
320	22217			
400	22218			
80	22225	50		
120	22226			
180	22227	100		
240	22228			
320	22229			
400	22356			



DV722 COATED ABRASIVE ROLLS – ALOX/PAPER BACKING

C/B WEIGHT PAPER BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
240	22271	1	335 mm x 25 mt	Rolls
280	22272			
320	22273			

DG922 COATED ABRASIVE DISCS & SHEETS

FILM BACKING

The **BETTER** choice for all sanding and finishing applications.

APPLICATIONS

- Surface sanding on any type of wood, metal, composite, solid surface, filler, e-coat, primer, paint coat, clear coat and gel coat

FEATURES

- Aluminum oxide mineral together with film backing gives a very controlled and even sanding property
- Easily convertible from paper disc for better quality and longer life. Ideal for both dry and wet applications.

BENEFITS

- Polyester film backing allows long-lasting application time and better resistant to tear-off in difficult corners
- Anti-loading treatment greatly enhances the life of the product and also improves work piece finish
- Film works better than paper with uniform mineral coating on perfectly even film surface

INFORMATION

DG922 COATED ABRASIVE DAISY DISCS – ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
60	73316	500	42 mm - Ø Hole	Disc
80	22569			
120	73916			
150	73317			
320	73318			
400	73319			
600	24610			
800	73416			
1200	22570			
1500	22571			
2000	73214			



DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
1500	22556	100	75 mm - 0 Holes	Disc
40	73147	50	75 mm - 6 Holes	
60	73148	100		
80	73820			
100	73821			
120	73822			
150	73823			
180	73824			
220	73825			
240	73826			
280	73113			
320	73114			
400	73115			
500	73116			
600	73117			
800	73827			
1000	73828			
1200	73829			
1500	73830			
2000	73831			
40	73720	50	89 mm - 0 Hole	
60	73721	100		
80	73722			
100	73723			
120	73724			
150	73725			
180	73726			



DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
220	73727	100	89 mm - Ø Hole	Disc
240	73728			
280	73729			
320	73730			
360	73349			
400	73731			
500	73119			
600	73732			
800	73141			
1000	73142			
1200	73143			
1500	73144			
2000	73145			
40	73520	50	125 mm - Ø Hole	
60	73521			
80	73522	100		
100	73523			
120	73524			
150	73525			
180	73526			
220	73527			
240	73528			
280	73529			
320	73530			
400	73531			
500	73533			
600	73534			
800	73535			
1000	73536			
1200	73537			
1500	73538			
2000	73539			



DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
40	73620	50	125 mm - 8+1 Holes	Disc
60	73621			
80	73622	100		
100	73623			
120	73624			
150	73625			
180	73626			
220	73627			
240	73628			
280	73629			
320	73630			
360	73647			
400	73631			
500	73648			
600	73632			
800	73649			
1000	73243			
1200	73244			
1500	73245			
2000	73246			
40	73988	50	125 mm - 16 Holes	Disc
60	73989			
80	73295	100		
100	73946			
120	73947			
150	73948			
180	73996			
220	73997			
240	73998			
280	73999			
320	73149			
360	73241			
400	73992			



DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
500	73993	100	125 mm - 16 Holes	Disc
600	73994			
800	73995			
1000	73247			
1200	73248			
1500	73249			
2000	73341			
40	73220	50	150 mm - 0 Hole	
60	73221			
80	73222	100		
100	73223			
120	73224			
150	73225			
180	73226			
220	73227			
240	73228			
280	73229			
320	73230			
360	73231			
400	73232			
500	73233			
600	73234			
800	73235			
1000	73236			
1200	73237			
1500	73238			
2000	73239			
40	73120	50	150 mm - 15 Holes	
60	73121			
80	73122	100		
100	73123			
120	73124			
150	73125			



DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
180	73126	100	150 mm - 15 Holes	Disc
220	73127			
240	73128			
280	73129			
320	73130			
360	73131			
400	73132			
500	73133			
600	73134			
800	73135			
1000	73136			
1200	73137			
1500	73138			
2000	73139			
40	73420	50	200 mm - 0 Hole	Disc
60	73421	100		
80	73422			
100	73423			
120	73424			
150	73425			
180	73426			
220	73427			
240	73428			
280	73429			
320	73430			
360	73431			
400	73432			
500	73433			
600	73434			
800	73435			
1000	73436			
1200	73437			
1500	73438			



Model: XV62



Model: 58445

DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
2000	73439	100	200 mm - 0 Hole	Disc
40	73320	50	200 mm - 8 Holes	
60	73321			
80	73322	100		
100	73323			
120	73324			
150	73325			
180	73326			
220	73327			
240	73328			
280	73329			
320	73330			
360	73331			
400	73332			
500	73333			
600	73334			
800	73335			
1000	73336			
1200	73337			
1500	73338			
2000	73339			
40	73633	50	200 mm - 15 Holes	
60	73634			
80	73635	100		
100	73636			
120	73637			
150	73638			
180	73639			
220	73958			
240	73959			
280	73735			
320	73778			
360	73779			



Model: 57574



Model: 58414

DG922 COATED ABRASIVE DISCS & SHEETS - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
400	73838	100	200 mm - 15 Holes	Disc
500	73839			
600	73832			
800	73957			
1000	73834			
1200	73835			
1500	73836			
2000	73837			
800	24509		81 x 133 mm - 0 Hole	Rectangular
1200	73945			
40	22396		70 x 400 mm - 14 Holes	
60	22397			
80	22398			
120	22399			
180	22457			
240	22453			
320	22454			
40	73048			
60	22455			
80	73035			
120	73213			
180	73036			
240	73296			
320	22456			



Model: 58414



Model: 58550



Model: 58551

DG922 COATED ABRASIVE ROLL - ALOX/FILM BACKING

ALOX/FILM BACKING WITH HOOK-FACE ATTACHMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
40	73041	1	115 mm x 25 m - 0 Hole	Roll
80	73040			
120	73014			
180	73034			
240	73396			

CLOG FREE SOFT FILM DISCS

The **BEST** choice for clog free sanding of primer, paint and clear coats on flat to highly curved and contoured surfaces.

APPLICATIONS

- Intermediate to final finish before polishing

FEATURES

- Very soft and conformable polyester abrasive discs and sheets
- Very efficient anticlog treatment
- Available in grits from P280 to P3000

BENEFITS

- Allows to achieve very fine and even surfaces, ideal preparation to polishing
- Excellent on coatings, paints, clearcoats, laquers,...

INFORMATION

CLOG FREE SOFT FILM DISCS

POLYESTER BACKING WITH VELCRO ATTACHEMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
800	22479	50	76 mm - 0 Hole	Disc
1200	24659			
1500	24660			
2000	24661			
2500	24662			
3000	24663			
280	24519	25	125 mm - 0 Hole	
320	24520			
400	24521			
600	24522			
800	22363			
1200	24523			
1500	24524			
2000	24525			
2500	24526			
3000	24527			



CLOG FREE SOFT FILM DISCS

POLYESTER BACKING WITH VELCRO ATTACHEMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
400	24529	25	125 mm - 6+1 Holes	Disc
600	24531			
600	24549			
1200	24550			
1500	24551			
2000	24552			
2500	24553			
3000	24534			
3000	24554			
320	24528		125 mm - 8+1 Holes	
400	24530			
500	22492			
600	24670			
800	22364			
1200	24532			
1500	24671			
2000	24533			
2000	22482			
2500	22483			
3000	24672			



Model: 52760



Model: X51V

CLOG FREE SOFT FILM SHEET

POLYESTER BACKING WITH VELCRO ATTACHEMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
600	22484	25	170 x 130 mm - 0 Hole	Rectangular
800	24679			
1200	24559			
1500	24560			
2000	24561			
2500	24562			
3000	24563			




Sheet

CLOG FREE SOFT FILM DISC

POLYESTER BACKING WITH VELCRO ATTACHEMENT | 13,000 RPM MOS | ALUMINUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Shape
280	24535	25	150 mm - 0 Hole	Disc
320	24536			
400	24537			
600	24538			
1200	24539			
1500	24542			
2000	24543			
2500	24544			
3000	24545			
400	24548	25	150 mm - 15 Holes	Disc
600	24673			
800	24674			
1500	24675			
2000	24676			
2500	24677			
3000	24678			





BONDED ABRASIVES

BONDED CERAMIC ABRASIVES – GRINDING DISCS / CUT-OFF DISCS

Used for a variety of applications, such as cutting sheet metal, pipe, and framework.

APPLICATIONS

- ▶ Heavy stock removal and cut-off on steels/stainless steel

FEATURES

- ▶ 100% high-performance ceramic abrasive
- ▶ High-strength resin and fiberglass reinforcement

BENEFITS

- ▶ Fast, cool cutting action provides a longer productive life
- ▶ 3 – 5 times the life of conventional aluminum oxide cut-off wheels

INFORMATION

BONDED ABRASIVES

DYNABRADE CERAMIC GRINDING DISCS & CUT-OFF WHEELS

Grits	P/N	Qty/Box	Dimensions	Shape
24	22566	5	115mm x 7mm x 22mm	Grinding Discs
24	22567	5	125mm x 7mm x 22mm	
24	22568	5	230mm x 7mm x 22mm	
46	22613	15	115mm x 1.3mm x 22mm	Cut-Off Discs
46	22614	15	125mm x 1.3mm x 22mm	
60	22615	15	230mm x 2mm x 22mm	



COATED ABRASIVES BELTS

Dynabrade is the company that created the first portable power tool solution for automating the grinding and finishing of difficult to reach areas, The Dynaflex® Dynabrade's DC 242 coated

abrasive belt offering is a multi-tiered line engineered to deliver maximum benefit on virtually any application. The Dynaflex® II coupled with DC 242 belts are the ideal solution for

grinding and finishing in hard to reach areas like grinding away spot welds for faster tear down, grinding and blending welds on framing, tubing, exhaust and other components.

APPLICATIONS

- Grinding and sanding on metals, composites, plastics, wood with Dynabrade belt tools

FEATURES

- Zirconia Alumina with grinding aid grits are for heavy stock removal to intermediate finish
- Excellent on stainless steel, carbon steel, cast iron, exotic alloys, Aluminum, bronze and brass
- Grinding Aid – a chemical that reduces the temperature of the working area, minimizing the risk of discoloration and deformation, in particular on stainless steel metal fabrication
- Aluminum oxide grits are for general purpose finishing applications on any kind of metals and alloys Ceramic belts suitable for High pressure grinding Applications

BENEFITS

- Fast, cool cutting action provides a longer productive life
- no discoloration on stainless steel

INFORMATION



DC 242 COATED ABRASIVE BELTS CLOTH BACKING - A/O ALUMINIUM OXIDE

Grits	P/N	Qty/Box	Dimensions	Recommended speed
180	70092	30	13 x 305 mm	27-33m/s
240	70093			
320	70094			
180	24615		13 x 330 mm	
240	24616			
320	24617			
180	70104		13 x 457 mm	
240	70105			
320	70106			



MNF1



15003



DC 242 COATED ABRASIVE BELTS CLOTH BACKING - Z/A ZIRCONIA ALUMINIA

Grits	P/N	Qty/Box	Dimensions	Recommended speed
60	70931	30	13 x 305 mm	27-33m/s
80	70932			
120	70934			
60	24612		13 x 330 mm	
80	24613			
120	24614			
36	24501		13 x 457 mm	
40	24502			
60	70938			
80	70939			
120	70941			



MNF1



15003



DC 242 COATED ABRASIVE BELTS CERAMIC

Grits	P/N	Qty/Box	Dimensions	Recommended speed
60	24624	30	13 x 457 mm	27-33m/s
80	22230			
120	24625			



MNF1



15003

COATED ABRASIVES: FIBER DISCS

Quick-change discs are available in 2" and 3" diameters with a "twist on, twist off" TR style attachment. The tool-free fastening feature makes changing small diameter discs fast and efficient, maximizing technician productivity.

Used with mini-angle grinders Dynafire™ quick change discs are ideal for a variety of applications from heavier applications like weld grinding and blending to light deburring and finishing on flat and contoured surfaces.

APPLICATIONS

- Removal of thick weld seams, deburring, preparation for welding on thick steel, stainless steel and titanium workpieces

FEATURES

- Heavy duty fiber disc with new generation of ceramic aluminum oxide mineral with a special chemical which helps very efficiently to reduce heating in grinding applications

BENEFITS

- Ideal for heavy stock removal to finishing on stainless steel, carbon steel, titanium, exotic alloys and bronze

INFORMATION



DYNAFIRE LOCKING-TYPE FIBER DISC CERAMIC FIBER DISCS WITH GRINDING AID

Grits	P/N	Qty/Box (Sold per Pack)	Dimensions	Attachment	MOS
36	73593	100	50 mm	Locking-Type	30,000 RPM
60	73594				
80	73595				
120	73596				
36	73597		75 mm		
60	73598				
80	73599				
120	73670				
36	73675		100 mm		
60	73676				
80	73677				
120	73678				



47821



DS53



DYNAFIRE FLANGE-MOUNT FIBRE DISCS
CERAMIC FIBER DISCS WITH GRINDING AID

Grits	P/N	Qty/Box (Sold per Pack)	Dimensions	Attachment	MOS
36	73581	100	115 mm	Flange Mount	12,000 RPM
60	73582		115 mm		
80	73583		115 mm		
36	73682		125 mm		
60	73683		125 mm		
80	73684		125 mm		
36	73585		180 mm		
60	73586		180 mm		
80	73587		180 mm		

NON-WOVEN ABRASIVES: DYNABRADE SURFACE CONDITIONING MATERIAL

DC323 discs are made from a lightly compressed, tough, non-woven web that is saturated with specialized resins and extra coarse abrasives, this forms an open structured disc that will not load when used on soft metals or when removing

sticky coatings. DC323 discs will not snag or shed like traditional coated abrasive cloth or fiber discs even when stripping burrs and heavy scale, or cleaning weld beads and rusted surfaces. Being a 3D structure DC323 discs can be used

on edge as well as the face and are extremely versatile as a removal and finishing tool that won't gouge or cause rework.

APPLICATIONS

- ▶ Surface blending on car body panels for optimized processing, grinding down and smoothing welds
- ▶ Decorative finishing, wood sanding, deburring, cleaning, oxide removal
- ▶ Removing light edge burrs and other irregularities on the surface
- ▶ For use on stainless steel, aluminum, titanium, alloys, fiberglass and plastic


FEATURES

- ▶ Non-woven web structure for less clogging and better lifetime than ordinary coated abrasive discs
- ▶ High content of aluminum oxide

BENEFITS

- ▶ Disc can be easily changed with one turn of the locking-type system
- ▶ Greater resistance to loading due to the open structure of the discs compared to standard surface
- ▶ No slipping with the locking-type system and always central run. Less downtime for changes

INFORMATION



DC 323 SURFACE CONDITIONING DISCS

ALOX/NON-WOVEN NYLON DISCS - LOCKING TYPE OR HOOK-FACE ATTACHMENT

Grits	P/N	Qty/Box	Dimensions	Attachment
Coarse	72956	25	75 mm	Locking-Type
Medium	72957			
Very Fine	72958			
SSFN	22617			
Coarse	72953	50	50 mm	
Medium	72954			
Very Fine	72955			
SSFN	22616			
Coarse	72959	25	100 mm	
Medium	72960			



Grits	P/N	Qty/Box	Dimensions	Attachment
Very Fine	72961	25	100 mm	Locking-Type
Coarse	22341	10	150 mm	Velcro
Medium	22342			
Very Fine	22360		115 mm	
Coarse	72950			
Medium	72951			
Very Fine	72952			



SURFACE CONDITIONING BELTS

LOW-STRETCH NON-WOVEN NYLON - ALUMINUM OXIDE

APPLICATIONS

- Satin finish and surface conditioning on metals and alloys

FEATURES

- Controlled cut does not change the workpiece geometry
- Burrs and surface oxidations are easily removed

BENEFITS

- Easily blends the wild scratches from previous working steps
- Gives consistent and easily replicable finish on metals and alloys

INFORMATION

Grits	P/N	Qty/Box	Dimensions	Mineral
A CRS	73477	30	13 x 305 mm	A/O
A MED	73478			
A VFN	73479			
A VFN	22327			
A CRS	24618		13 x 330 mm	
A MED	24619			
A VFN	24620			
S SFN	24621			
A CRS	73480		13 x 457 mm	
A MED	73481			
A VFN	73482			



NON-WOVEN ABRASIVES: OXIDE REMOVAL ABRASIVES

NOTE

- ▶ DB 357 Conforms to work area, ideal for use in automotive paint removal
- ▶ DO 379 Made of rigid open web that is aggressive and long-lasting

APPLICATIONS

- ▶ Ideal for work on stainless steel, standard or alloyed steel, aluminum, titanium, non-ferrous materials and alloys, fiberglass, plastic, stone or wood
- ▶ Aggressively removes paint and rust from welding seams, undercoating, seam-sealers and stone guards
- ▶ Applications in trunk beds and door jambs for removing sealant
- ▶ Used to remove oxidation from tire rims and rust from brake assemblies
- ▶ Removing weld blueing and oxide on stainless steel containers
- ▶ Removing of old gasket material on cylinder heads of diesel engines
- ▶ For cleaning welds and light coating removal

FEATURES

- ▶ Strong 3-dimensional synthetic fiber construction, very open, with extra-coarse silicon carbide
- ▶ High resistance to clogging and fast removal. Long lifetime; safer than wire brushes.

BENEFITS

- ▶ Conforms to work piece and does not damage the surface
- ▶ Allows access to difficult areas like wheel wells and under-carriage
- ▶ Fast removal of rust and paint without base material removal

INFORMATION



DB 357 OXIDE REMOVAL ABRASIVES

SIC/NWN WHEELS & DISCS | CENTER HOLE, LOCKING-TYPE OR SHAFT ATTACHMENT

Grits	P/N	Qty/Box	Dimensions	Thickness	Attachment
Oxide Removal Wheels/Discs - Black	72962	10	75 mm	13 mm	13 mm Hole
	72963				Locking-Type
	72964				6 mm Shaft
Oxide Removal Wheels - Black	72965		100 mm	13 mm	13 mm Hole
	72966				6 mm Shaft
	72969			25 mm	6 mm Shaft
	72967		150 mm	13 mm	13 mm Hole
	72968				8 mm Shaft
	72970			25 mm	8 mm Shaft






DO 379 OXIDE REMOVAL DISCS

SIC/NWN WHEELS & DISCS | CENTER HOLE, LOCKING-TYPE OR SHAFT ATTACHMENT

Grits	P/N	Qty/Box	Dimensions	Thickness	Attachment
Oxide Removal Wheels/Discs - Orange	72971	10	75 mm	13 mm	13 mm Hole
	72973				Locking-Type
	72972				6 mm Shaft
Oxide Removal Wheels - Orange	72974		100 mm	13 mm	13 mm Hole
	72975				6 mm Shaft
	72978			25 mm	6 mm Shaft
	72976		150 mm	13 mm	13 mm Hole
	72949				20 mm Shaft
	72977			25 mm	8 mm Shaft
	72979				8 mm Shaft



DIAMOND CUT-OFF WHEELS

3/32" THICKNESS | 1/8" DIAMOND GRIT WRAP

Attachment	Type	Part Number	MOS	Qty/Box
76 mm Diameter				
3/8" Center Hole	Continuous Rim	93917	20,000 RPM	1
	Side Spoked	93646		
	Gulleted / Slotted	93658		
2-1/4" Shank	Continuous Rim	93906		
	Side Spoked	93907		
102 mm Diameter				
3/4" Center Hole	Side Spoked	93649	20,000 RPM	1
114 mm Diameter				
3/8" Center Hole	Gulleted / Slotted	94912	20,000 RPM	1
127 mm Diameter				
3/4" Center Hole	Continuous Rim	93921	20,000 RPM	1
	Side Spoked	93650		
	Gulleted / Slotted	93662		



Diamond cut-off wheels

BI-METAL RECIPROCATATING SAW BLADES

152 MM LONG

INFORMATION

NOTE

- ▶ 6 Teeth per Inch: Used for demolition work in nail-embedded wood; also for fast cutting of composites
- ▶ 10 Teeth per Inch: Used for demolition work in nail-embedded wood; also on pipe, stainless steel, carbon steel up to 6 mm thick
- ▶ 18 Teeth per Inch: Used on pipe, stainless steel, carbon steel up to 4.5 mm thick.

APPLICATIONS

- ▶ For use with Dynabrade Stockade Saws, for cutting and finishing metals, wood, plastics, carbon fibers, solid surface, etc

FEATURES & BENEFITS

- ▶ Shatter-resistant and excellent cut-rate

Teeth per Inch	Length x Width	Part Number	Qty/Box
6	152 mm x Taper	90934	1
10	152 mm x 19 mm	90939	
18	152 mm x 19 mm	90937	













Bi-metal blades

DYNABURR™ CARBIDE BURRS

DynaBurr™ carbide burrs are used with Dynabrade die grinders for rapid material removal, precise finishing, deburring, and removal of parting lines

and flash. Carbide burrs provide longer life than high-speed steel burrs.

		1/8" DYNABURRS™, DOUBLE CUT STYLE					1/4" DYNABURRS™, DOUBLE CUT STYLE				
		Model Number	Tool Style	Cutter Diameter	Flute Length	Shaft Size	Model Number	Tool Style	Cutter Diameter	Flute Length	Shaft Size
	Cylinder	93338	SA-42	3/32"	7/16"	1/8"	93330	SA-1	1/4"	5/8"	1/4"
		93339	SA-43	1/8"	9/16"	1/8"	93331	SA-3	3/8"	3/4"	1/4"
	Cylinder Radiused End	93340	SC-41	3/32"	7/16"	1/8"	93332	SC-1	1/4"	5/8"	1/4"
		93341	SC-42	1/8"	9/16"	1/8"	93333	SC-3	3/8"	3/4"	1/4"
	Ball	93342	SD-42	1/8"	1/8"	1/8"	93334	SD-3	3/8"	5/16"	1/4"
	Oval	93343	SE-41	1/8"	7/32"	1/8"	93335	SE-3	3/8"	5/8"	1/4"
	Tree	93344	SF-42	1/8"	1/2"	1/8"	—	—	—	—	—
	Tree Radiused End	93345	SG-44	1/8"	1/2"	1/8"	93336	SF-3	3/8"	3/4"	1/4"
	Flame Pointed End	93346	SH-41	1/8"	1/4"	1/8"	—	—	—	—	—
	Taper Radiused End	93347	SL-42	1/8"	1/2"	1/8"	93337	SL-3	3/8"	1-1/16"	1/4"
	14° Cone End	93348	SM-42	1/8"	7/16"	1/8"	—	—	—	—	—
	10° Inverted Cone	93349	SN-42	1/8"	3/16"	1/8"	—	—	—	—	—

Package Quantity: 1

DYNABURR™ KITS

Kits (1/8" or 1/4" mm) include one Carbide Burr of each shape, as shown above. Packaged in high-quality wooden case.

Model Number	Burr Shaft Size	Burr Qty
93351	1/8"	12
93350	1/4"	8





DYNABRADE FINISHING SYSTEM ABRASIVE TECHNOLOGY

Properly creating a high gloss surface, restoring a worn finish, or correcting defects in coatings, requires sanding to level the clear coat to with the base of the deepest scratch or defect. Using the Dynabrade Finishing System, polishing in one step can be achieved to restore a properly prepared, flat and highly reflective surface. (see Figure A)

Some compounds contain fillers and wax that will fill the defect and appear to generate a high gloss finish, but after a few washes the filler erodes and defects will re-appear. Dynabrade Finishing System compounds contain a unique, high-purity abrasive powder technology with no fillers, waxes, silicone or harmful chemicals. The unique characteristics of the high purity

abrasive allow it to begin polishing coarsely and gradually breakdown to an ultra-fine cut creating a high gloss shine or polish in one step for most colors, on all types of paints. (see Figure B) Without fillers or waxes the Dynabrade Finishing System leaves a completely smooth, flat and highly reflective surface and is easy to wipe away without leaving a residue.



THE DYNABRADE POLISHING SYSTEM | COMPOUNDS & PADS

The Dynabrade Polishing system is based on high performance compounds that are the result of decades of research and development. Utilizing a unique abrasive powder technology,

the abrasive grain in our high-performance compounds is based on an optimized high-purity, white aluminum oxide powder. The Dynabrade system can remove defects and scratches as well

as polish surfaces in only one step, creating a brilliant mirror-like gloss. Conventional polishing compounds require a minimum of two or more polishing steps to achieve similar results.

DYNARED COARSE + FINISH

APPLICATIONS

- New generation polishing compound in coarse grade. Dynared is ideal for removing scratches from grit P1500-P2000 and finer. More aggressive than DynaCoarse but gives a very good glossy finish (comparable to DynaTeal)

FEATURES AND BENEFITS

- Increase Productivity, Reduce Labor Time and Costs. Silicone Free, Enhance Final High Gloss Surface Finish
- Avoids swirl and bloom marks as well as holograms when used with our random orbital motion polishers

Container	P/N	Color	Size
Bottle	22017	Red	1 Liter
Jug	22019	Red	5 Liters



INFORMATION

DYNATEAL FINE FINISH

APPLICATIONS

- Removes deep scratches on any kind of surface.
- Polishing compound offers an aggressive cut that can flatten soft orange-peel effect in auto aftermarket.
- Removes medium defects such as swirl marks, water spots and sanding marks.
- Can be used to prepare the car body for the subsequent high gloss surface finish application..

FEATURES AND BENEFITS

- Increase productivity, reduce labor time and costs. Silicone free, enhance final high gloss surface finish
- Avoids swirl and bloom marks as well as holograms when used with our random orbital polishers

INFORMATION

Container	P/N	Color	Size
Bottle	22011	Teal	1 Liter
Jug	22013	Teal	5 Liters



DYNAORANGE VERY FINE FINISH

APPLICATIONS

- Ideal polish for the second step of our Dynabrade "Two-Step" System when used with the corresponding foam and random orbital polisher. Leaves a high gloss, hologram free surface finish on all type of Automotive clearcoats
- Final finish operation combined with more aggressive compounds

FEATURES AND BENEFITS

- Increase productivity, reduce labor time and costs. Silicone free, enhance final high gloss surface finish
- Avoids swirl and bloom marks as well as holograms when used with our random orbital polishers

INFORMATION

Container	P/N	Color	Size
Bottle	22021	Orange	1 Liter
Jug	22023	Orange	5 Liters



5 LITERS CONTAINER ACCESSORIES

DISPENSER OR HOLDER | 1 ITEM PER BOX

Product	Material	Part Number	Color
Dispenser	Plastic	22005	White
Holder	Metal	22006	-



DYNABRADE DENIBBING DISCS

DENIBBING DISCS T3, FILM BACKED, 32MM SIZE, SILICON CARBIDE

DYNABRADE DENIBBING DISCS : FILM BACKED, SILICON CARBIDE, PSA/VELCRO | 10,000 RPM MOS

APPLICATIONS

- For use with Dynabrade Denibber tools in wet/damp operations to remove nibs from paint and lacquers

FEATURES

- Even and consistent tri-dimensional coating
- Silicon carbide mineral

BENEFITS

- Fast removal of nibs without wild scratches
- Superior and even finish

INFORMATION

Product Name	P/N	Qty/Box	Dimensions	Grit	Package type
Denibbing Discs T3 A5 (roll of 500 discs PSA)	22670	500	32 mm	A5	Roll
Denibbing Discs T3 A7 (roll of 500 discs PSA)	22671	500		A7	
Denibbing Discs T3 A3 (roll of 500 discs PSA)	22672	500		A3	
Denibbing Disc A5, 32mm PSA, tube of 100 discs	22770	100		A5	Tube
Denibbing Disc A7, 32mm PSA, tube of 100 discs	22771	100		A7	
Denibbing Disc A3, 32mm PSA, tube of 100 discs	22772	100		A3	

INFO : A7 = P2500 - A5 = P3000 - A3 = P4000



POLISHING PADS & FOAMS

Dynabrade offers a variation of high-quality polishing products for the Automotive After Market professional. With our polishing product range, Dynabrade offers the best solution for the most critical and most time-consuming part of the repair process.

Using the right combination of our product range will lead to a serious cost reduction by decreasing labor time and achieving a faster end-result of the polishing job.

The Polishing Pads are mainly used for the more aggressive rotary polishing applications and makes it possible to re-fresh old, worn and weathered paint surfaces to high gloss polished Chrome and aluminum parts.

The Polishing Foams are mainly used to achieve the finishing touch by removing micro scratches while leaving a high gloss hologram free surface.

Due to the reticulated cell structure, the foams

keep the compound inside which reduce the consumption of polish compound while leaving a minimum of compound to wipe off.

The combination of the right compound with the right pad or foam allows you to achieve the best results in the shortest time and with the lowest consumption of products.

POLISHING PADS & FOAMS

TERRY CLOTH, SYNTHETIC WOOL AND SHEEP SKIN | 1 ITEM PER BOX

TERRY CLOTH

- The most aggressive polishing pad. To be used to (Mirror)polish Chrome and Aluminum parts.

SHEEPSKIN

- Less aggressive than Terry Cloth pad. To be used to refresh old, hard and weathered surfaces.

SYNTHETIC WHOOOL

- Less aggressive than Sheepskin pad. To be used to polish weathered and dull painted surfaces and plastics.

MICRO FIBER

- Less aggressive than Synthetic Whool pad. To be used to remove small scratches on paints, plastics and clearcoats

INFORMATION

P/N	Backup pad diameter (mm)	Outer foam diameter (mm)	Description	Holes	Qty/Pack
90027	75	80	Terry Cloth Polishing Pad	0	1
90028			Synthtic Whool Polishing Pad		
90080			Sheepskin Polishing Pad		
90081	125	135			
90082	150	180			
56150	75	80	Microfiber Polishing Pad		20
73502	125	135			5
73602	150	180			2



CYLINDRICAL RETICULATED POLISHING FOAMS

- High performance foams in different densities
- Ideal for rotary polishing applications
- Pineapple shaped to avoid that compound will splash around
- Strong & Heat resistant cell structure for long lifetime
- Oversized diameter to avoid that back-Up pad will touch surface
- 25 mm thick with Radius edge to achieve smooth surface results
- Grey=Hard, Blue=Medium, Black=Soft

P/N	Backup pad diameter (mm)	Outer foam diameter (mm)	Description	Holes	Qty/Pack
72801	75	80	Cylindrical polishing Foam Black	0	Tube 20 pcs
72800			Cylindrical polishing D-Foam Black		
73100			Cylindrical polishing Foam Blue	6	
73101			Cylindrical polishing Foam Blue	0	
73400			Cylindrical polishing Foam Grey	6	
72901	125	135	Cylindrical polishing Foam Black	0	5
73201			Cylindrical polishing Foam Blue		
73501			Cylindrical polishing Foam Grey		
73001	150	180	Cylindrical polishing Foam Black		2
73301			Cylindrical polishing Foam Blue		
73601			Cylindrical polishing Foam Grey		



POLISHING FOAM TUBE HOLDER

HOLDS TWENTY 80 MM POLISHING FOAMS | 1 ITEM PER BOX

Material	Part Number	Size
Metal	22008	94 x 548 mm

For cylindrical Foams 80 mm only



CONICAL RETICULATED POLISHING FOAMS

- High performance foams in different densities
- Ideal for Random Orbital polishing applications
- Pineapple shaped to avoid that compound will splash around
- Center hole to reduce friction caused by eccentric movement
- Strong & Heat resistant cell structure with stiff interface layer for long lifetime
- Oversized conical diameter to avoid that back-Up pad will touch workpiece
- 20 mm thick with Radius edge to achieve smooth and hologram-free surface results
- Grey=Hard, Green=Hard/Medium, Blue=Medium/soft, Black=Soft



P/N	Backup pad diameter (mm)	Outer foam diameter (mm)	Description	Holes	Qty/Pack
74000	75	87	Conical polishing Foam Black	1	5
74001			Conical polishing Foam Blue		
74002			Conical polishing Foam Grey		
74009	125	138	Conical polishing Foam Black		
74010			Conical polishing Foam Blue		
74011			Conical polishing Foam Green		
74012			Conical polishing Foam Grey		
74013	150	160	Conical polishing Foam Black		2
74014			Conical polishing Foam Blue		
74015			Conical polishing Foam Green		
74016			Conical polishing Foam Grey		
74017	32	45	Conical polishing Foam Mini Blue	0	50
74018			Conical polishing Foam Mini Green		
74019			Conical polishing Foam Mini Grey		

MICROFIBER WIPES

IDEAL FOR DYNABRADE'S "TWO-STEP" SYSTEM

APPLICATIONS

- Fast and complete removal of polish and paste residual after buffing/polishing.

FEATURES AND BENEFITS

- Silicone free. Excellent absorbency and quick drying.
- No edges (art. 22050) – totally scratch-free because there is no sewing tread (art. 22000: sewn edges)
- Transparent printing – special print is scratch-free with no damage to sensitive surfaces

INFORMATION

Container	Size	Part Number	Qty/Box
Blue & Yellow*	40 x 40 mm	22000	20
Orange	40 x 40 mm	22050	20

* Package includes 10x Blue & 10x Yellow colors can not be ordered individually



TIPS AND TECHNIQUES FOR POLISHING WITH DYNABRADE COMPOUNDS AND PADS / FOAMS

HOW AND WHEN SHOULD THE POLISHING PADS BE CLEANED?

- If the pad begins to dust or stick during polishing, it is time to clean and remove the accumulated dirt and used polish from it. After polishing, all pads can be washed with water and a little cleaning agent. Note that lambskin pads should be left wet and re-attached to the hook face of polishing plate in order to prevent them from shrinking and losing their shape.

THE POLISH OFTEN SPLATTERS WHEN I USE THE POLISHER. WHAT AM I DOING WRONG?

- This can be caused by various reasons:
 - a) The polisher is turned on before bringing the pad into contact with the paint (frequent beginner's error)
 - b) Polisher speed too high
 - c) Too much polish
 - d) Tilting of polisher / formation of dust when polishing edges
 - e) Use of new pad that has not yet been worn in
 - f) Fresh pad, into which the polishing compound has not been distributed evenly prior to polishing

CONSIDERATIONS WHEN USING A NEW POLISHING PAD

1. Make sure that the entire surface of each new pad is coated sparingly and evenly with the required polish. (Note: Any part of the pad that is not coated with polish may cause micro-scratches.)
2. The rubbing compound should be spread across several points onto the paint surface with the pad and then distributed evenly and rubbed in (BEFORE TURNING ON THE POLISHER). The aim is to have sufficient unused rubbing compound over the entire surface in order to ensure a uniform cut.
3. Now set the polisher/pad onto the paint surface and check whether you have set the polisher to the right speed.
4. Always START the polisher ON the surface and STOP the polisher OFF the surface.
5. The actual polishing process can now begin. Switch on the polisher.

IMPORTANT: you do not need to exert heavy downward force to keep the back-up pad and abrasive flat on the surface.

6. Make sure that the area of the surface you wish to work on is not too large.
Always remember: you should be able to cover the selected surface from one comfortable position. Do not reach or extend beyond a comfortable range. You want to be able to keep uniform pressure across the entire area being polished. A 50 x 50 cm area is a common size to work at one time
7. Follow a set pattern when buffing. It is suggested to pass over the surface, following a criss-cross "North, South, East, West" pattern, overlapping each pass by 50% of the diameter of the pad. (see diagram below) This ensures that a uniform finish is achieved. (See Figure A)

Check your progress and completely clean the surface with new microfiber towel. Wipe in a straight motion (not circular) to be able to detect any areas that might need additional work. If any defects are noticed, reapply compound to the pad and continue in that area until the surface is free of all defects. Always clear away and completely remove any polishing compound residues before progressing to the next area or polishing step. Do not use the same microfiber towel for different grades of compound.



22021

22017


22011



Terry Cloth

Synthetic Wool

Sheep Skin



DYNABRADE WARRANTY INFORMATION

Dynabrade Pneumatic "Teal" Tools Lifetime Warranty

LIFETIME WARRANTY

All tools must be registered at www.Dynabrade.com to qualify for Lifetime Warranty. Tools purchased beginning August 18, 2008 may be registered for Lifetime Warranty. Lifetime Warranty applies only to portable pneumatic tools manufactured by Dynabrade, Inc. in the USA. Warranty applies only to the original tool owner; warranty is non-transferable.

All Dynabrade portable pneumatic power tools are rigorously inspected and performance tested in our factory before shipping to our customers.

Dynabrade warrants all Dynabrade portable pneumatic power tools against defects of workmanship and materials under normal use and service for the lifetime of the tool as set forth herein.

Upon examination and review at Dynabrade's factory, Dynabrade shall confirm whether the tool qualifies for warranty status, in which case Dynabrade will repair or replace the tool at no charge to the customer.

This warranty is contingent upon proper use of the tool in accordance with factory recommendations, instructions and safety practices. It shall not apply to equipment that has been subjected to misuse, negligence, accident or tampering in any way so as to affect its normal performance.

This warranty does NOT cover normally wearable parts and accessories, including, but not limited to, bearings, contact wheels, rotor blades, regulators, valve stems, levers, shrouds, guards, O-rings, seals, gaskets and other wearable parts. Dynabrade only warrants such normally wearable parts and accessories against manufacturing defects at the time of receipt. If, upon receipt and prior to use, a normally wearable part or accessory is found to be defective, Dynabrade will repair or replace such part or accessory at no charge to the customer.

To activate Lifetime Warranty, customer must register each portable pneumatic power tool at www.dynabrade.com. Dynabrade will not honor Lifetime Warranty on unregistered tools. A one-year warranty will be honored on all unregistered portable pneumatic power tools. (In European countries, warranty on unregistered tools will be two years.) Customer must return the defective unregistered tool to Dynabrade within one year (or two years in European countries) from the date of purchase.

To be considered for warranty, tools must be sent back to our factory, transportation prepaid by user. Please send tool back to attention "Repair Department" with note fully explaining the nature of the problem along with a copy of original invoice indicating model and serial number.

THIS WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND THERE ARE NO OTHER WARRANTIES THAT EXTEND BEYOND THIS EXPRESS WARRANTY.

Dynabrade will not be liable for damages to products, other property or persons due to improper use or through attempts to use products for other than their intended use. DYNABRADE WILL NOT BE LIABLE TO CUSTOMER OR ANY THIRD PARTY FOR ANY SPECIAL, CONTINGENT, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES. Dynabrade's liability with respect to a claim for any other damages arising out of or connected with the manufacture, sale, purchase, non-delivery, use or performance of any product sold by Dynabrade will in no event exceed to the price paid for the product.

Dynabrade Nitro Series™ Tools Two-Years Warranty

2 YEAR WARRANTY

Dynabrade warrants all "Dynabrade Nitro Series™" tools against defects in workmanship and materials under normal use and service for a period of 2 Years from the date of purchase as set forth herein. Customer must return the defective tool to Dynabrade within 2 Years from the date of purchase. Upon examination and review at Dynabrade's factory, Dynabrade shall confirm whether the tool qualifies for warranty status, in which case Dynabrade shall repair or replace the tool at no charge to the customer. This warranty is contingent upon proper use of the "Dynabrade Nitro Series™" tool in accordance with factory recommendations, instructions and safety practices. It shall not apply to equipment that has been subjected to misuse, negligence, accident or tampering in any way so as to affect its normal performance. This warranty does NOT apply in the following cases: (i) consumables such as sanding pads, etc.; (ii) lack of lubrication or evidence of rust, dirt or corrosion; (iii) tools requiring normal tuneup or cleaning; (iv) tools being used after they are badly worn such as using ratchet with worn yoke; (v) ratchet anvils damaged by excessive hand torquing; (vi) use in production-type applications. This warranty does NOT cover normally wearable parts and accessories, including, but not limited to, bearings, contact wheels, rotor blades, regulators, valve stems, levers, shrouds, guards, O-rings, seals, gaskets and other wearable parts. Dynabrade only warrants such normally wearable parts and accessories against manufacturing defects at the time of receipt. If, upon receipt and prior to use, a normally wearable part or accessory is found to be defective, Dynabrade will repair or replace such part or accessory at no charge to the customer. To be considered for warranty, tools must be sent back to our factory, transportation prepaid by user. Please send tool back to attention "Repair Department" with note fully explaining the nature of the problem along with a copy of original invoice indicating model and serial number. THIS WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND THERE ARE NO OTHER WARRANTIES THAT EXTEND BEYOND THIS EXPRESS WARRANTY. Dynabrade will not be liable for damages to products, other property or persons due to improper use or through attempts to use products for other than their intended use. DYNABRADE WILL NOT BE LIABLE TO CUSTOMER OR ANY THIRD PARTY FOR ANY SPECIAL, CONTINGENT, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES. Dynabrade's liability with respect to a claim for any other damages arising out of or connected with the manufacture, sale, purchase, non-delivery, use or performance of any product sold by Dynabrade will in no event exceed to the price paid for the product.

Dynabrade Portable Vacuums Two-Year Warranty

2 YEAR WARRANTY

Dynabrade warrants all Portable Vacuums manufactured by Dynabrade against defects in workmanship and materials under normal use and service for a period of 2 years from the date of purchase as set forth herein.

Customer must return the defective vacuum to Dynabrade the local certified repair center within 2 years from the date of purchase. Upon examination and review at Dynabrade's repair center, it shall confirm whether the vacuum qualifies for warranty status, in which case Dynabrade's repair center shall repair or replace the vacuum at no charge to the customer.

This warranty is contingent upon proper use of the Portable Vacuum in accordance with factory recommendations, instructions and safety practices. It shall not apply to equipment that has been subjected to misuse, negligence, or accident, such as using incorrect filters. It shall also not apply to equipment that has been tampered with in any way so as to affect its normal performance.

This warranty does NOT cover normally wearable parts and products, including, but not limited to, electrical motor brushes, hoses, couplers, filters, dust bags and other wearable parts. Dynabrade only warrants such normally wearable parts and accessories against manufacturing defects at the time of receipt. If, upon receipt and prior to use, a normally wearable part or accessory is found to be defective, Dynabrade's repair center will repair or replace such part or accessory at no charge to the customer.

To be considered for warranty, vacuums must be sent back to the Dynabrade's repair center, transportation prepaid by user. Please send vacuum back to the repair center with note fully explaining the nature of the problem along with a copy of original invoice indicating model and serial number.

THIS WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND THERE ARE NO OTHER WARRANTIES THAT EXTEND BEYOND THIS EXPRESS WARRANTY.

Dynabrade will not be liable for damages to products, other property or persons due to improper use or through attempts to use products for other than their intended use. DYNABRADE WILL NOT BE LIABLE TO CUSTOMER OR ANY THIRD PARTY FOR ANY SPECIAL, CONTINGENT, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES. Dynabrade's liability with respect to a claim for any other damages arising out of or connected with the manufacture, sale, purchase, non-delivery, use or performance of any product sold by Dynabrade will in no event exceed to the price paid for the product.

CONVERSION TABLE

THE MEASURES

LENGTH

	Meters	Centimeters	Millimeters
1 Inch (in.)	0.0254 m	2.54 cm	25.4 mm
1 Foot (ft.)	0.3048 m	30.48 cm	304.8 mm

WEIGHT

	Kilograms	Grams
1 Ounce (oz.)	0.02835 kg	28.35 g
1 Pound (lb.)	0.454 kg	454 g

POWER

	Kilowatts	Watts
1 hp	0.745 kW	745 W

VOLUME

	Liters
1 US Gallon	3.785 l

TORQUE

	Newton Meters
1 Inch-ounce	0.00706 Nm
1 Inch-pound	0.11298 Nm

COMMON SIZES

Centimeters	Millimeters	Centimeters	Millimeters
3/32"	2.5 mm	4-1/2"	114 mm
1/8"	3 mm	5"	127 mm
3/16"	5 mm	6"	152 mm
1/4"	6 mm	7"	178 mm
3/8"	10 mm	8"	203 mm
1/2"	13 mm	9"	229 mm
3/4"	19 mm	11"	279 mm
1"	25 mm	12"	305 mm
1-1/4"	32 mm	18"	457 mm
2"	51 mm	20-1/2"	521 mm
2-3/4"	70 mm	24"	610 mm
3"	76 mm	30"	762 mm
3-1/2"	89 mm	34"	864 mm
4"	102 mm	44"	1118 mm

COMMON RECTANGULAR SIZES (W X L)

Inch	Millimeter
4" x 4-5/16"	102 mm x 110 mm
4-1/4" x 4-1/12"	108 mm x 114 mm
2-3/4" x 8"	70 mm x 203 mm
2-3/4" x 11"	70 mm x 279 mm
3-2/3" x 7"	93 mm x 178 mm
2-7/8" x 3-1/8"	73 mm x 79 mm
2-3/8" x 3-3/4"	60 mm x 95 mm

Dynabrade reserves the right to update this catalogue without notice, updated versions available on www.dynabrade.com

WE LISTEN. WE OBSERVE. **WE OPTIMIZE.**



Dynabrade Europe S.à r.l
Zone Artisanale Op Tomm, 6
L-5485 Wormeldange-Haut, Luxembourg
Tel: +352 768 494 1 / Fax: +352 768 495
Email: customer.service@dynabrade.lu
www.dynabrade.com

Distributed By:

Automotive Aftermarket – Dynabrade Product Line **EUR 19.12**